
Amazon Relational Database Service

API Reference

API Version 2014-10-31



Amazon Relational Database Service: API Reference

Copyright © 2016 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddRoleToDBCluster	5
Request Parameters	5
Errors	5
Example	5
AddSourceIdentifierToSubscription	7
Request Parameters	7
Response Elements	7
Errors	7
Example	7
AddTagsToResource	9
Request Parameters	9
Errors	9
Example	9
ApplyPendingMaintenanceAction	11
Request Parameters	11
Response Elements	11
Errors	11
Example	12
AuthorizeDBSecurityGroupIngress	13
Request Parameters	13
Response Elements	13
Errors	14
Example	14
CopyDBClusterParameterGroup	16
Request Parameters	16
Response Elements	16
Errors	17
Example	17
CopyDBClusterSnapshot	19
Request Parameters	19
Response Elements	19
Errors	19
Example	20
CopyDBParameterGroup	22
Request Parameters	22
Response Elements	22
Errors	22
Example	23
CopyDBSnapshot	24
Request Parameters	24
Response Elements	25
Errors	25
Example	25
CopyOptionGroup	27
Request Parameters	27
Response Elements	27
Errors	27
Example	28
CreateDBCluster	30
Request Parameters	30
Response Elements	33
Errors	33
Example	34

CreateDBClusterParameterGroup	36
Request Parameters	36
Response Elements	37
Errors	37
Example	37
CreateDBClusterSnapshot	39
Request Parameters	39
Response Elements	39
Errors	39
Example	40
CreateDBInstance	42
Request Parameters	42
Response Elements	51
Errors	52
Example	53
CreateDBInstanceReadReplica	55
Request Parameters	55
Response Elements	57
Errors	58
Example	59
CreateDBParameterGroup	61
Request Parameters	61
Response Elements	61
Errors	62
Example	62
CreateDBSecurityGroup	64
Request Parameters	64
Response Elements	64
Errors	64
Example	65
CreateDBSnapshot	66
Request Parameters	66
Response Elements	66
Errors	66
Example	67
CreateDBSubnetGroup	69
Request Parameters	69
Response Elements	69
Errors	69
Example	70
CreateEventSubscription	72
Request Parameters	72
Response Elements	73
Errors	73
Examples	74
CreateOptionGroup	76
Request Parameters	76
Response Elements	76
Errors	76
Example	77
DeleteDBCluster	78
Request Parameters	78
Response Elements	78
Errors	79
Example	79
DeleteDBClusterParameterGroup	81
Request Parameters	81
Errors	81

Example	81
DeleteDBClusterSnapshot	83
Request Parameters	83
Response Elements	83
Errors	83
Example	83
DeleteDBInstance	85
Request Parameters	85
Response Elements	86
Errors	86
Example	86
DeleteDBParameterGroup	89
Request Parameters	89
Errors	89
Example	89
DeleteDBSecurityGroup	91
Request Parameters	91
Errors	91
Example	91
DeleteDBSnapshot	93
Request Parameters	93
Response Elements	93
Errors	93
Example	93
DeleteDBSubnetGroup	95
Request Parameters	95
Errors	95
Example	95
DeleteEventSubscription	97
Request Parameters	97
Response Elements	97
Errors	97
Example	97
DeleteOptionGroup	99
Request Parameters	99
Errors	99
Example	99
DescribeAccountAttributes	101
Response Elements	101
Errors	101
Example	101
DescribeCertificates	104
Request Parameters	104
Response Elements	104
Errors	105
Example	105
DescribeDBClusterParameterGroups	106
Request Parameters	106
Response Elements	106
Errors	107
Example	107
DescribeDBClusterParameters	109
Request Parameters	109
Response Elements	109
Errors	110
Example	110
DescribeDBClusters	112
Request Parameters	112

Response Elements	112
Errors	113
Example	113
DescribeDBClusterSnapshotAttributes	115
Request Parameters	115
Response Elements	115
Errors	115
Example	115
DescribeDBClusterSnapshots	117
Request Parameters	117
Response Elements	118
Errors	118
Example	119
DescribeDBEngineVersions	121
Request Parameters	121
Response Elements	122
Errors	122
Example	122
DescribeDBInstances	124
Request Parameters	124
Response Elements	124
Errors	125
Example	125
DescribeDBLogFiles	128
Request Parameters	128
Response Elements	128
Errors	129
Example	129
DescribeDBParameterGroups	131
Request Parameters	131
Response Elements	131
Errors	131
Example	132
DescribeDBParameters	133
Request Parameters	133
Response Elements	133
Errors	134
Example	134
DescribeDBSecurityGroups	136
Request Parameters	136
Response Elements	136
Errors	136
Example	137
DescribeDBSnapshotAttributes	139
Request Parameters	139
Response Elements	139
Errors	139
Example	139
DescribeDBSnapshots	141
Request Parameters	141
Response Elements	142
Errors	142
Example	143
DescribeDBSubnetGroups	145
Request Parameters	145
Response Elements	145
Errors	145
Example	146

DescribeEngineDefaultClusterParameters	148
Request Parameters	148
Response Elements	148
Errors	148
Example	148
DescribeEngineDefaultParameters	150
Request Parameters	150
Response Elements	150
Errors	150
Example	150
DescribeEventCategories	153
Request Parameters	153
Response Elements	153
Errors	153
Example	153
DescribeEvents	155
Request Parameters	155
Response Elements	156
Errors	156
Example	156
DescribeEventSubscriptions	159
Request Parameters	159
Response Elements	159
Errors	159
Example	160
DescribeOptionGroupOptions	162
Request Parameters	162
Response Elements	162
Errors	162
Example	163
DescribeOptionGroups	165
Request Parameters	165
Response Elements	165
Errors	166
Examples	166
DescribeOrderableDBInstanceOptions	171
Request Parameters	171
Response Elements	172
Errors	172
Example	172
DescribePendingMaintenanceActions	174
Request Parameters	174
Response Elements	174
Errors	175
Example	175
DescribeReservedDBInstances	177
Request Parameters	177
Response Elements	178
Errors	178
Example	178
DescribeReservedDBInstancesOfferings	180
Request Parameters	180
Response Elements	181
Errors	181
Example	181
DescribeSourceRegions	183
Request Parameters	183
Response Elements	183

Errors	183
Example	184
DownloadDBLogFilePortion	185
Request Parameters	185
Response Elements	185
Errors	186
Example	186
FailoverDBCluster	189
Request Parameters	189
Response Elements	189
Errors	189
Example	190
ListTagsForResource	192
Request Parameters	192
Response Elements	192
Errors	192
Example	192
ModifyDBCluster	194
Request Parameters	194
Response Elements	196
Errors	196
Example	197
ModifyDBClusterParameterGroup	199
Request Parameters	199
Response Elements	199
Errors	199
Example	200
ModifyDBClusterSnapshotAttribute	201
Request Parameters	201
Response Elements	201
Errors	202
Example	202
ModifyDBInstance	204
Request Parameters	204
Response Elements	211
Errors	211
Example	212
ModifyDBParameterGroup	215
Request Parameters	215
Response Elements	215
Errors	216
Example	216
ModifyDBSnapshotAttribute	217
Request Parameters	217
Response Elements	217
Errors	218
Example	218
ModifyDBSubnetGroup	220
Request Parameters	220
Response Elements	220
Errors	220
Example	221
ModifyEventSubscription	223
Request Parameters	223
Response Elements	223
Errors	223
Example	224
ModifyOptionGroup	226

Request Parameters	226
Response Elements	226
Errors	226
Examples	227
PromoteReadReplica	230
Request Parameters	230
Response Elements	230
Errors	231
Example	231
PromoteReadReplicaDBCluster	233
Request Parameters	233
Response Elements	233
Errors	233
Example	233
PurchaseReservedDBInstancesOffering	236
Request Parameters	236
Response Elements	236
Errors	236
Example	237
RebootDBInstance	238
Request Parameters	238
Response Elements	238
Errors	238
Example	239
RemoveRoleFromDBCluster	241
Request Parameters	241
Errors	241
Example	241
RemoveSourceIdentifierFromSubscription	243
Request Parameters	243
Response Elements	243
Errors	243
Example	243
RemoveTagsFromResource	245
Request Parameters	245
Errors	245
Example	245
ResetDBClusterParameterGroup	247
Request Parameters	247
Response Elements	247
Errors	247
Example	248
ResetDBParameterGroup	249
Request Parameters	249
Response Elements	249
Errors	250
Examples	250
RestoreDBClusterFromS3	252
Request Parameters	252
Response Elements	255
Errors	255
Example	256
RestoreDBClusterFromSnapshot	258
Request Parameters	258
Response Elements	259
Errors	260
Example	261
RestoreDBClusterToPointInTime	263

Request Parameters	263
Response Elements	264
Errors	265
Example	266
RestoreDBInstanceFromDBSnapshot	268
Request Parameters	268
Response Elements	271
Errors	271
Example	272
RestoreDBInstanceToPointInTime	275
Request Parameters	275
Response Elements	278
Errors	278
Example	280
RevokeDBSecurityGroupIngress	282
Request Parameters	282
Response Elements	282
Errors	283
Example	283
Data Types	285
AccountQuota	287
Contents	287
AvailabilityZone	288
Contents	288
Certificate	289
Contents	289
CharacterSet	290
Contents	290
DBCluster	291
Contents	291
DBClusterMember	295
Contents	295
DBClusterOptionGroupStatus	296
Contents	296
DBClusterParameterGroup	297
Contents	297
DBClusterRole	298
Contents	298
DBClusterSnapshot	299
Contents	299
DBClusterSnapshotAttribute	301
Contents	301
DBClusterSnapshotAttributesResult	302
Contents	302
DBEngineVersion	303
Contents	303
DBInstance	304
Contents	304
DBInstanceStatusInfo	309
Contents	309
DBParameterGroup	310
Contents	310
DBParameterGroupStatus	311
Contents	311
DBSecurityGroup	312
Contents	312
DBSecurityGroupMembership	313
Contents	313

DBSnapshot	314
Contents	314
DBSnapshotAttribute	317
Contents	317
DBSnapshotAttributesResult	318
Contents	318
DBSubnetGroup	319
Contents	319
DescribeDBLogFilesDetails	320
Contents	320
DomainMembership	321
Contents	321
EC2SecurityGroup	322
Contents	322
Endpoint	323
Contents	323
EngineDefaults	324
Contents	324
Event	325
Contents	325
EventCategoriesMap	326
Contents	326
EventSubscription	327
Contents	327
Filter	329
Contents	329
IPRange	330
Contents	330
Option	331
Contents	331
OptionConfiguration	332
Contents	332
OptionGroup	333
Contents	333
OptionGroupMembership	334
Contents	334
OptionGroupOption	335
Contents	335
OptionGroupOptionSetting	337
Contents	337
OptionSetting	338
Contents	338
OptionVersion	339
Contents	339
OrderableDBInstanceOption	340
Contents	340
Parameter	342
Contents	342
PendingMaintenanceAction	344
Contents	344
PendingModifiedValues	345
Contents	345
RecurringCharge	347
Contents	347
ReservedDBInstance	348
Contents	348
ReservedDBInstancesOffering	350
Contents	350

ResourcePendingMaintenanceActions	351
Contents	351
SourceRegion	352
Contents	352
Subnet	353
Contents	353
Tag	354
Contents	354
Timezone	355
Contents	355
UpgradeTarget	356
Contents	356
VpcSecurityGroupMembership	357
Contents	357
Common Parameters	358
Common Errors	360

Welcome

Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. It provides cost-efficient, resizeable capacity for an industry-standard relational database and manages common database administration tasks, freeing up developers to focus on what makes their applications and businesses unique.

Amazon RDS gives you access to the capabilities of a MySQL, MariaDB, PostgreSQL, Microsoft SQL Server, Oracle, or Amazon Aurora database server. These capabilities mean that the code, applications, and tools you already use today with your existing databases work with Amazon RDS without modification. Amazon RDS automatically backs up your database and maintains the database software that powers your DB instance. Amazon RDS is flexible: you can scale your database instance's compute resources and storage capacity to meet your application's demand. As with all Amazon Web Services, there are no up-front investments, and you pay only for the resources you use. This interface reference for Amazon RDS contains documentation for a programming or command line interface you can use to manage Amazon RDS. Note that Amazon RDS is asynchronous, which means that some interfaces might require techniques such as polling or callback functions to determine when a command has been applied. In this reference, the parameter descriptions indicate whether a command is applied immediately, on the next instance reboot, or during the maintenance window. The reference structure is as follows, and we list following some related topics from the user guide.

Amazon RDS API Reference

- For the alphabetical list of API actions, see [API Actions](#).
- For the alphabetical list of data types, see [Data Types](#).
- For a list of common query parameters, see [Common Parameters](#).
- For descriptions of the error codes, see [Common Errors](#).

Amazon RDS User Guide

- For a summary of the Amazon RDS interfaces, see [Available RDS Interfaces](#).
- For more information about how to use the Query API, see [Using the Query API](#).

This document was last published on December 17, 2016.

Actions

The following actions are supported:

- [AddRoleToDBCluster](#) (p. 5)
- [AddSourceIdentifierToSubscription](#) (p. 7)
- [AddTagsToResource](#) (p. 9)
- [ApplyPendingMaintenanceAction](#) (p. 11)
- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [CopyDBClusterParameterGroup](#) (p. 16)
- [CopyDBClusterSnapshot](#) (p. 19)
- [CopyDBParameterGroup](#) (p. 22)
- [CopyDBSnapshot](#) (p. 24)
- [CopyOptionGroup](#) (p. 27)
- [CreateDBCluster](#) (p. 30)
- [CreateDBClusterParameterGroup](#) (p. 36)
- [CreateDBClusterSnapshot](#) (p. 39)
- [CreateDBInstance](#) (p. 42)
- [CreateDBInstanceReadReplica](#) (p. 55)
- [CreateDBParameterGroup](#) (p. 61)
- [CreateDBSecurityGroup](#) (p. 64)
- [CreateDBSnapshot](#) (p. 66)
- [CreateDBSubnetGroup](#) (p. 69)
- [CreateEventSubscription](#) (p. 72)
- [CreateOptionGroup](#) (p. 76)
- [DeleteDBCluster](#) (p. 78)
- [DeleteDBClusterParameterGroup](#) (p. 81)
- [DeleteDBClusterSnapshot](#) (p. 83)
- [DeleteDBInstance](#) (p. 85)
- [DeleteDBParameterGroup](#) (p. 89)
- [DeleteDBSecurityGroup](#) (p. 91)
- [DeleteDBSnapshot](#) (p. 93)
- [DeleteDBSubnetGroup](#) (p. 95)
- [DeleteEventSubscription](#) (p. 97)

- [DeleteOptionGroup](#) (p. 99)
- [DescribeAccountAttributes](#) (p. 101)
- [DescribeCertificates](#) (p. 104)
- [DescribeDBClusterParameterGroups](#) (p. 106)
- [DescribeDBClusterParameters](#) (p. 109)
- [DescribeDBClusters](#) (p. 112)
- [DescribeDBClusterSnapshotAttributes](#) (p. 115)
- [DescribeDBClusterSnapshots](#) (p. 117)
- [DescribeDBEngineVersions](#) (p. 121)
- [DescribeDBInstances](#) (p. 124)
- [DescribeDBLogFiles](#) (p. 128)
- [DescribeDBParameterGroups](#) (p. 131)
- [DescribeDBParameters](#) (p. 133)
- [DescribeDBSecurityGroups](#) (p. 136)
- [DescribeDBSnapshotAttributes](#) (p. 139)
- [DescribeDBSnapshots](#) (p. 141)
- [DescribeDBSubnetGroups](#) (p. 145)
- [DescribeEngineDefaultClusterParameters](#) (p. 148)
- [DescribeEngineDefaultParameters](#) (p. 150)
- [DescribeEventCategories](#) (p. 153)
- [DescribeEvents](#) (p. 155)
- [DescribeEventSubscriptions](#) (p. 159)
- [DescribeOptionGroupOptions](#) (p. 162)
- [DescribeOptionGroups](#) (p. 165)
- [DescribeOrderableDBInstanceOptions](#) (p. 171)
- [DescribePendingMaintenanceActions](#) (p. 174)
- [DescribeReservedDBInstances](#) (p. 177)
- [DescribeReservedDBInstancesOfferings](#) (p. 180)
- [DescribeSourceRegions](#) (p. 183)
- [DownloadDBLogFilePortion](#) (p. 185)
- [FailoverDBCluster](#) (p. 189)
- [ListTagsForResource](#) (p. 192)
- [ModifyDBCluster](#) (p. 194)
- [ModifyDBClusterParameterGroup](#) (p. 199)
- [ModifyDBClusterSnapshotAttribute](#) (p. 201)
- [ModifyDBInstance](#) (p. 204)
- [ModifyDBParameterGroup](#) (p. 215)
- [ModifyDBSnapshotAttribute](#) (p. 217)
- [ModifyDBSubnetGroup](#) (p. 220)
- [ModifyEventSubscription](#) (p. 223)
- [ModifyOptionGroup](#) (p. 226)
- [PromoteReadReplica](#) (p. 230)
- [PromoteReadReplicaDBCluster](#) (p. 233)
- [PurchaseReservedDBInstancesOffering](#) (p. 236)
- [RebootDBInstance](#) (p. 238)
- [RemoveRoleFromDBCluster](#) (p. 241)

- [RemoveSourceIdentifierFromSubscription](#) (p. 243)
- [RemoveTagsFromResource](#) (p. 245)
- [ResetDBClusterParameterGroup](#) (p. 247)
- [ResetDBParameterGroup](#) (p. 249)
- [RestoreDBClusterFromS3](#) (p. 252)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)
- [RestoreDBInstanceFromDBSnapshot](#) (p. 268)
- [RestoreDBInstanceToPointInTime](#) (p. 275)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

AddRoleToDBCluster

Associates an Identity and Access Management (IAM) role from an Aurora DB cluster. For more information, see [Authorizing Amazon Aurora to Access Other AWS Services On Your Behalf](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The name of the DB cluster to associate the IAM role with.

Type: String

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of the IAM role to associate with the Aurora DB cluster, for example `arn:aws:iam::123456789012:role/AuroraAccessRole`.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterRoleAlreadyExists

The specified IAM role Amazon Resource Name (ARN) is already associated with the specified DB cluster.

HTTP Status Code: 400

DBClusterRoleQuotaExceeded

You have exceeded the maximum number of IAM roles that can be associated with the specified DB cluster.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=AddRoleToDBCluster  
&DBClusterIdentifier=sample-cluster  
&RoleArn=arn%3Aaws%3Aiam%3A%3A123456789012%3Arole%2Fsample-role  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256
```

```
&X-Amz-Credential=AKIADQKE4SARGYLE/20161012/us-east-1/rds/aws4_request
&X-Amz-Date=20161012T204524Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=d73c069210f98e5377851fa4c4ab2fdd53e8bd5d5f02f4f8ef15d4daa5b04567
```

Sample Response

```
<AddRoleToDBClusterResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">
  <ResponseMetadata>
    <RequestId>ccccbdb6-90bc-11e6-8533-cd6447e421f8</RequestId>
  </ResponseMetadata>
</AddRoleToDBClusterResponse>
```

AddSourceIdentifierToSubscription

Adds a source identifier to an existing RDS event notification subscription.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

SourceIdentifier

The identifier of the event source to be added. An identifier must begin with a letter and must contain only ASCII letters, digits, and hyphens; it cannot end with a hyphen or contain two consecutive hyphens.

Constraints:

- If the source type is a DB instance, then a `DBInstanceIdentifier` must be supplied.
- If the source type is a DB security group, a `DBSecurityGroupName` must be supplied.
- If the source type is a DB parameter group, a `DBParameterGroupName` must be supplied.
- If the source type is a DB snapshot, a `DBSnapshotIdentifier` must be supplied.

Type: String

Required: Yes

SubscriptionName

The name of the RDS event notification subscription you want to add a source identifier to.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions](#) (p. 159) action.

Type: [EventSubscription](#) (p. 327) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

SourceNotFound

The requested source could not be found.

HTTP Status Code: 404

SubscriptionNotFound

The subscription name does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=AddSourceIdentifierToSubscription  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SourceIdentifier=mysqlldb  
&SubscriptionName=EventSubscription04  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140422/us-east-1/rds/aws4_request  
&X-Amz-Date=20140422T230442Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=347d5e788e809cd06c50214b12750a3c39716bf65b239bb6f7ee8ff5374e2df9
```

Sample Response

```
<AddSourceIdentifierToSubscriptionResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <AddSourceIdentifierToSubscriptionResult>  
    <EventSubscription>  
      <SourceType>db-instance</SourceType>  
      <Enabled>true</Enabled>  
      <CustomerAwsId>803#####</CustomerAwsId>  
      <Status>modifying</Status>  
      <SourceIdsList>  
        <SourceId>mysqlldb</SourceId>  
      </SourceIdsList>  
      <SubscriptionCreationTime>2014-04-22 23:03:19.776</  
SubscriptionCreationTime>  
      <EventCategoriesList>  
        <EventCategory>creation</EventCategory>  
        <EventCategory>deletion</EventCategory>  
      </EventCategoriesList>  
      <CustSubscriptionId>EventSubscription04</CustSubscriptionId>  
      <SnsTopicArn>arn:aws:sns:us-east-1:803#####:myawsuser-RDS</  
SnsTopicArn>  
    </EventSubscription>  
  </AddSourceIdentifierToSubscriptionResult>  
  <ResponseMetadata>  
    <RequestId>6c05f0b0-bf71-11d3-f4c6-37db295f7674</RequestId>  
  </ResponseMetadata>  
</AddSourceIdentifierToSubscriptionResponse>
```

AddTagsToResource

Adds metadata tags to an Amazon RDS resource. These tags can also be used with cost allocation reporting to track cost associated with Amazon RDS resources, or used in a Condition statement in an IAM policy for Amazon RDS.

For an overview on tagging Amazon RDS resources, see [Tagging Amazon RDS Resources](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

ResourceName

The Amazon RDS resource the tags will be added to. This value is an Amazon Resource Name (ARN). For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Type: String

Required: Yes

Tags.Tag.N

The tags to be assigned to the Amazon RDS resource.

Type: array of [Tag](#) (p. 354) objects

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=AddTagsToResource
&ResourceName=arn%3Aaws%3Aards%3Aus-west-2%3A123456789012%3Aadb%3Asample
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Tags.member.1.Key=InstanceType
&Tags.member.1.Value=Development
&Tags.member.2.Key=Owner
&Tags.member.2.Value=Admin123
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
```

```
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request
&X-Amz-Date=20160913T173915Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=90a257aa949fab364b7db0964a255986922f933f2e55e7b582ce6f9ccca2a4e0
```

Sample Response

```
<AddTagsToResourceResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">
  <ResponseMetadata>
    <RequestId>fd9cd844-79d8-11e6-956c-915ad715fa2f</RequestId>
  </ResponseMetadata>
</AddTagsToResourceResponse>
```

ApplyPendingMaintenanceAction

Applies a pending maintenance action to a resource (for example, to a DB instance).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

ApplyAction

The pending maintenance action to apply to this resource.

Valid values: `system-update`, `db-upgrade`

Type: String

Required: Yes

OptInType

A value that specifies the type of opt-in request, or undoes an opt-in request. An opt-in request of type `immediate` cannot be undone.

Valid values:

- `immediate` - Apply the maintenance action immediately.
- `next-maintenance` - Apply the maintenance action during the next maintenance window for the resource.
- `undo-opt-in` - Cancel any existing `next-maintenance` opt-in requests.

Type: String

Required: Yes

ResourceIdentifier

The RDS Amazon Resource Name (ARN) of the resource that the pending maintenance action applies to. For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

ResourcePendingMaintenanceActions

Describes the pending maintenance actions for a resource.

Type: [ResourcePendingMaintenanceActions \(p. 351\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

ResourceNotFoundFault

The specified resource ID was not found.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=ApplyPendingMaintenanceAction  
  &ResourceIdentifier=arn:aws:rds:us-east-1:123456781234:db:my-instance  
  &ApplyAction=system-update  
  &OptInType=immediate  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20141216/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194732Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=6e25c542bf96fe24b28c12976ec92d2f856ab1d2a158e21c35441a736e4fde2b
```

Sample Response

```
<ApplyPendingMaintenanceActionResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ApplyPendingMaintenanceActionResult>  
    <ResourcePendingMaintenanceActions>  
      <ResourceIdentifier>arn:aws:rds:us-east-1:123456781234:db:my-instance</  
ResourceIdentifier>  
      <PendingMaintenanceActionDetails>  
        <PendingMaintenanceAction>  
          <Action>system-update</Action>  
          <OptInStatus>immediate</OptInStatus>  
        </PendingMaintenanceAction>  
      </PendingMaintenanceActionDetails>  
    </ResourcePendingMaintenanceActions>  
  </ApplyPendingMaintenanceActionResult>  
  <ResponseMetadata>  
    <RequestId>dcfe0682-870c-11e4-9833-b3ad657ea9da</RequestId>  
  </ResponseMetadata>  
</ApplyPendingMaintenanceActionResponse>
```


AuthorizeDBSecurityGroupIngress

Enables ingress to a DBSecurityGroup using one of two forms of authorization. First, EC2 or VPC security groups can be added to the DBSecurityGroup if the application using the database is running on EC2 or VPC instances. Second, IP ranges are available if the application accessing your database is running on the Internet. Required parameters for this API are one of CIDR range, EC2SecurityGroupId for VPC, or (EC2SecurityGroupOwnerId and either EC2SecurityGroupName or EC2SecurityGroupId for non-VPC).

Note

You cannot authorize ingress from an EC2 security group in one region to an Amazon RDS DB instance in another. You cannot authorize ingress from a VPC security group in one VPC to an Amazon RDS DB instance in another.

For an overview of CIDR ranges, go to the [Wikipedia Tutorial](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

CIDRIP

The IP range to authorize.

Type: String

Required: No

DBSecurityGroupName

The name of the DB security group to add authorization to.

Type: String

Required: Yes

EC2SecurityGroupId

Id of the EC2 security group to authorize. For VPC DB security groups, `EC2SecurityGroupId` must be provided. Otherwise, `EC2SecurityGroupOwnerId` and either `EC2SecurityGroupName` or `EC2SecurityGroupId` must be provided.

Type: String

Required: No

EC2SecurityGroupName

Name of the EC2 security group to authorize. For VPC DB security groups, `EC2SecurityGroupId` must be provided. Otherwise, `EC2SecurityGroupOwnerId` and either `EC2SecurityGroupName` or `EC2SecurityGroupId` must be provided.

Type: String

Required: No

EC2SecurityGroupOwnerId

AWS account number of the owner of the EC2 security group specified in the `EC2SecurityGroupName` parameter. The AWS Access Key ID is not an acceptable value. For VPC DB security groups, `EC2SecurityGroupId` must be provided. Otherwise, `EC2SecurityGroupOwnerId` and either `EC2SecurityGroupName` or `EC2SecurityGroupId` must be provided.

Type: String

Required: No

Response Elements

The following element is returned by the service.

DBSecurityGroup

Contains the result of a successful invocation of the following actions:

- [DescribeDBSecurityGroups](#) (p. 136)
- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [CreateDBSecurityGroup](#) (p. 64)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

This data type is used as a response element in the [DescribeDBSecurityGroups](#) (p. 136) action.

Type: [DBSecurityGroup](#) (p. 312) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

AuthorizationAlreadyExists

The specified CIDRIP or EC2 security group is already authorized for the specified DB security group.

HTTP Status Code: 400

AuthorizationQuotaExceeded

DB security group authorization quota has been reached.

HTTP Status Code: 400

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

InvalidDBSecurityGroupState

The state of the DB security group does not allow deletion.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=AuthorizeDBSecurityGroupIngress  
&CIDRIP=54.241.217.9%2F32  
&DBSecurityGroupName=default  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request  
&X-Amz-Date=20140423T154632Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=7803146e430626f47b0da058921cdb9f2ab7ffd881bd99fc859f2f635e4472bd
```

Sample Response

```
<AuthorizeDBSecurityGroupIngressResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <AuthorizeDBSecurityGroupIngressResult>
```

```
<DBSecurityGroup>
  <EC2SecurityGroups>
    <EC2SecurityGroup>
      <Status>authorized</Status>
      <EC2SecurityGroupName>elasticbeanstalk-windows</
EC2SecurityGroupName>
      <EC2SecurityGroupOwnerId>803#####</EC2SecurityGroupOwnerId>
      <EC2SecurityGroupId>sg-7f476617</EC2SecurityGroupId>
    </EC2SecurityGroup>
  </EC2SecurityGroups>
  <DBSecurityGroupDescription>default</DBSecurityGroupDescription>
  <IPRanges>
    <IPRange>
      <CIDRIP>192.0.0.0/24</CIDRIP>
      <Status>authorized</Status>
    </IPRange>
    <IPRange>
      <CIDRIP>190.0.1.0/29</CIDRIP>
      <Status>authorized</Status>
    </IPRange>
    <IPRange>
      <CIDRIP>190.0.2.0/29</CIDRIP>
      <Status>authorized</Status>
    </IPRange>
    <IPRange>
      <CIDRIP>10.0.0.0/8</CIDRIP>
      <Status>authorized</Status>
    </IPRange>
  </IPRanges>
  <OwnerId>803#####</OwnerId>
  <DBSecurityGroupName>default</DBSecurityGroupName>
</DBSecurityGroup>
</AuthorizedDBSecurityGroupIngressResult>
<ResponseMetadata>
  <RequestId>6176b5f8-bfed-11d3-f92b-31fa5e8dbc99</RequestId>
</ResponseMetadata>
</AuthorizedDBSecurityGroupIngressResponse>
```

CopyDBClusterParameterGroup

Copies the specified DB cluster parameter group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

SourceDBClusterParameterGroupIdentifier

The identifier or Amazon Resource Name (ARN) for the source DB cluster parameter group. For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Constraints:

- Must specify a valid DB cluster parameter group.
- If the source DB cluster parameter group is in the same region as the copy, specify a valid DB parameter group identifier, for example `my-db-cluster-param-group`, or a valid ARN.
- If the source DB parameter group is in a different region than the copy, specify a valid DB cluster parameter group ARN, for example `arn:aws:rds:us-east-1:123456789012:cluster-pg:custom-cluster-group1`.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TargetDBClusterParameterGroupDescription

A description for the copied DB cluster parameter group.

Type: String

Required: Yes

TargetDBClusterParameterGroupIdentifier

The identifier for the copied DB cluster parameter group.

Constraints:

- Cannot be null, empty, or blank
- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-cluster-param-group1`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBClusterParameterGroup

Contains the result of a successful invocation of the [CreateDBClusterParameterGroup \(p. 36\)](#) or [CopyDBClusterParameterGroup \(p. 16\)](#) action.

This data type is used as a request parameter in the [DeleteDBClusterParameterGroup \(p. 81\)](#) action, and as a response element in the [DescribeDBClusterParameterGroups \(p. 106\)](#) action.

Type: [DBClusterParameterGroup \(p. 297\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBParameterGroupAlreadyExists

A DB parameter group with the same name exists.

HTTP Status Code: 400

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

DBParameterGroupQuotaExceeded

Request would result in user exceeding the allowed number of DB parameter groups.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
  ?Action=CopyDBClusterParameterGroup
  &SignatureMethod=HmacSHA256
  &SignatureVersion=4
  &SourceDBClusterParameterGroupIdentifier=arn%3Aaws%3Aards%3Aus-
east-1%3A815981987263%3Acluster-pg%3Amy-cluster-pg
  &TargetDBParameterGroupIdentifier=new-cluster-pg
  &TargetDBParameterGroupDescription=New%20cluster%20group
  &Version=2014-10-31
  &X-Amz-Algorithm=AWS4-HMAC-SHA256
  &X-Amz-Credential=AKIADQKE4SARGYLE/20160705/us-east-1/rds/aws4_request
  &X-Amz-Date=20160705T143101Z
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
  &X-Amz-
Signature=9164337efa99caf850e874a1cb7ef62f3cea29d0b448b9e0e7c53b288ddffed2
```

Sample Response

```
<CopyDBClusterParameterGroupResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <CreateDBClusterParameterGroupResult>
    <DBClusterParameterGroup>
      <DBParameterGroupFamily>aurora5.6</DBParameterGroupFamily>
      <Description>New cluster group</Description>
      <DBClusterParameterGroupName>new-cluster-pg</
DBClusterParameterGroupName>
    </DBClusterParameterGroup>
  </CreateDBClusterParameterGroupResult>
  <ResponseMetadata>
    <RequestId>ae81a963-cd9d-11e4-8b88-8351746a4c92</RequestId>
  </ResponseMetadata>
</CopyDBClusterParameterGroupResponse>
```


CopyDBClusterSnapshot

Creates a snapshot of a DB cluster. For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

SourceDBClusterSnapshotIdentifier

The identifier of the DB cluster snapshot to copy. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster-snapshot1`

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

TargetDBClusterSnapshotIdentifier

The identifier of the new DB cluster snapshot to create from the source DB cluster snapshot. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster-snapshot2`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBClusterSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBClusterSnapshot](#) (p. 39)
- [DeleteDBClusterSnapshot](#) (p. 83)

This data type is used as a response element in the [DescribeDBClusterSnapshots](#) (p. 117) action.

Type: [DBClusterSnapshot](#) (p. 299) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterSnapshotAlreadyExistsFault

User already has a DB cluster snapshot with the given identifier.

HTTP Status Code: 400

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=CopyDBClusterSnapshot  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &SourceDBClusterSnapshotIdentifier=rds%3Asample-cluster-2016-09-14-10-38  
  &TargetDBClusterSnapshotIdentifier=cluster-snapshot-copy-1  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20160914/us-west-2/rds/aws4_request  
  &X-Amz-Date=20160914T164919Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=4503d6112f2ab5332d7d1871cba6b97ddcc9748d3d4da0cb2c219ace80cfd384
```

Sample Response

```
<CopyDBClusterSnapshotResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <CopyDBClusterSnapshotResult>  
    <DBClusterSnapshot>  
      <MasterUsername>mymasteruser</MasterUsername>  
      <AllocatedStorage>1</AllocatedStorage>  
      <SnapshotType>>manual</SnapshotType>  
      <AvailabilityZones>  
        <AvailabilityZone>us-west-2a</AvailabilityZone>  
        <AvailabilityZone>us-west-2b</AvailabilityZone>  
        <AvailabilityZone>us-west-2c</AvailabilityZone>  
      </AvailabilityZones>  
      <StorageEncrypted>>false</StorageEncrypted>  
      <Engine>aurora</Engine>
```



```
<Port>0</Port>
<LicenseModel>aurora</LicenseModel>
<SnapshotCreateTime>2016-09-14T10:38:05.616Z</SnapshotCreateTime>
<PercentProgress>100</PercentProgress>
<VpcId>vpc-e97e7d8d</VpcId>
<DBClusterSnapshotIdentifier>cluster-snapshot-copy-1</
DBClusterSnapshotIdentifier>
  <DBClusterSnapshotArn>arn:aws:rds:us-west-2:123456789012:cluster-
snapshot:cluster-snapshot-copy-1</DBClusterSnapshotArn>
  <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>
  <ClusterCreateTime>2016-09-13T16:57:52.695Z</ClusterCreateTime>
  <Status>available</Status>
</DBClusterSnapshot>
</CopyDBClusterSnapshotResult>
<ResponseMetadata>
  <RequestId>2e861f29-7a9b-11e6-94c8-21ac69ee8f8c</RequestId>
</ResponseMetadata>
</CopyDBClusterSnapshotResponse>
```

CopyDBParameterGroup

Copies the specified DB parameter group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

SourceDBParameterGroupIdentifier

The identifier or ARN for the source DB parameter group. For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Constraints:

- Must specify a valid DB parameter group.
- Must specify a valid DB parameter group identifier, for example `my-db-param-group`, or a valid ARN.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TargetDBParameterGroupDescription

A description for the copied DB parameter group.

Type: String

Required: Yes

TargetDBParameterGroupIdentifier

The identifier for the copied DB parameter group.

Constraints:

- Cannot be null, empty, or blank
- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-db-parameter-group`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBParameterGroup

Contains the result of a successful invocation of the [CreateDBParameterGroup \(p. 61\)](#) action.

This data type is used as a request parameter in the [DeleteDBParameterGroup \(p. 89\)](#) action, and as a response element in the [DescribeDBParameterGroups \(p. 131\)](#) action.

Type: [DBParameterGroup \(p. 310\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBParameterGroupAlreadyExists

A DB parameter group with the same name exists.

HTTP Status Code: 400

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

DBParameterGroupQuotaExceeded

Request would result in user exceeding the allowed number of DB parameter groups.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CopyDBParameterGroup  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &SourceDBParameterGroupIdentifier=arn%3Aaws%3Aards%3Aus-  
west-2%3A815981987263%3pg%3Amy-remote-param-group  
  &TargetDBParameterGroupIdentifier=new-local-param-group  
  &TargetDBParameterGroupDescription=description  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140429/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140429T175351Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=9164337efa99caf850e874a1cb7ef62f3cea29d0b448b9e0e7c53b288ddffed2
```

Sample Response

```
<CopyDBParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <CopyDBParameterGroupResult>  
    <DBParameterGroup>  
      <DBParameterGroupFamily>mysql5.6</DBParameterGroupFamily>  
      <Description>description</Description>  
      <DBParameterGroupName>new-local-param-group</DBParameterGroupName>  
    </DBParameterGroup>  
  </CopyDBParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>2928d60e-beb6-11d3-8e5c-3ccda5460c46</RequestId>  
  </ResponseMetadata>  
</CopyDBParameterGroupResponse>
```

CopyDBSnapshot

Copies the specified DB snapshot. The source DB snapshot must be in the "available" state.

To copy a DB snapshot from a shared manual DB snapshot, `SourceDBSnapshotIdentifier` must be the Amazon Resource Name (ARN) of the shared DB snapshot.

You can not copy an encrypted DB snapshot from another AWS region.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

CopyTags

True to copy all tags from the source DB snapshot to the target DB snapshot; otherwise false. The default is false.

Type: Boolean

Required: No

KmsKeyId

The AWS KMS key ID for an encrypted DB snapshot. The KMS key ID is the Amazon Resource Name (ARN), KMS key identifier, or the KMS key alias for the KMS encryption key.

If you copy an unencrypted DB snapshot and specify a value for the `KmsKeyId` parameter, Amazon RDS encrypts the target DB snapshot using the specified KMS encryption key.

If you copy an encrypted DB snapshot from your AWS account, you can specify a value for `KmsKeyId` to encrypt the copy with a new KMS encryption key. If you don't specify a value for `KmsKeyId`, then the copy of the DB snapshot is encrypted with the same KMS key as the source DB snapshot.

If you copy an encrypted DB snapshot that is shared from another AWS account, then you must specify a value for `KmsKeyId`.

Type: String

Required: No

SourceDBSnapshotIdentifier

The identifier for the source DB snapshot.

If you are copying from a shared manual DB snapshot, this must be the ARN of the shared DB snapshot.

You cannot copy an encrypted, shared DB snapshot from one AWS region to another.

Constraints:

- Must specify a valid system snapshot in the "available" state.
- If the source snapshot is in the same region as the copy, specify a valid DB snapshot identifier.
- If the source snapshot is in a different region than the copy, specify a valid DB snapshot ARN. For more information, go to [Copying a DB Snapshot](#).

Example: `rds:mydb-2012-04-02-00-01`

Example: `arn:aws:rds:us-west-2:123456789012:snapshot:mysql-instance1-snapshot-20130805`

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TargetDBSnapshotIdentifier

The identifier for the copied snapshot.

Constraints:

- Cannot be null, empty, or blank
- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-db-snapshot`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBSnapshot](#) (p. 66)
- [DeleteDBSnapshot](#) (p. 93)

This data type is used as a response element in the [DescribeDBSnapshots](#) (p. 141) action.

Type: [DBSnapshot](#) (p. 314) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSnapshotAlreadyExists

DBSnapshotIdentifier is already used by an existing snapshot.

HTTP Status Code: 400

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=CopyDBSnapshot  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SourceDBSnapshotIdentifier=arn%3Aaws%3Aards%3Aus-  
east-1%3A815981987263%3Asnapshot%3Aards%3Amysql-2014-04-27-08-15
```

```
&TargetDBSnapshotIdentifier=mysqldb-arn
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140429/us-east-1/rds/aws4_request
&X-Amz-Date=20140429T175351Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=9164337efa99caf850e874a1cb7ef62f3cea29d0b448b9e0e7c53b288ddffed2
```

Sample Response

```
<CopyDBSnapshotResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <CopyDBSnapshotResult>
    <DBSnapshot>
      <Port>3306</Port>
      <OptionGroupName>default:mysql-5-6</OptionGroupName>
      <Engine>mysql</Engine>
      <Status>available</Status>
      <SnapshotType>manual</SnapshotType>
      <LicenseModel>general-public-license</LicenseModel>
      <EngineVersion>5.6.13</EngineVersion>
      <DBInstanceIdentifier>mysqldb</DBInstanceIdentifier>
      <DBSnapshotIdentifier>mysqldb-arn</DBSnapshotIdentifier>
      <SnapshotCreateTime>2014-04-27T08:16:05.356Z</SnapshotCreateTime>
      <AvailabilityZone>us-east-1a</AvailabilityZone>
      <InstanceCreateTime>2014-04-21T22:24:26.573Z</InstanceCreateTime>
      <PercentProgress>100</PercentProgress>
      <AllocatedStorage>100</AllocatedStorage>
      <MasterUsername>awsmasteruser</MasterUsername>
    </DBSnapshot>
  </CopyDBSnapshotResult>
  <ResponseMetadata>
    <RequestId>2928d60e-beb6-11d3-8e5c-3ccda5460c46</RequestId>
  </ResponseMetadata>
</CopyDBSnapshotResponse>
```

CopyOptionGroup

Copies the specified option group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

SourceOptionGroupIdentifier

The identifier or ARN for the source option group. For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Constraints:

- Must specify a valid option group.
- If the source option group is in the same region as the copy, specify a valid option group identifier, for example `my-option-group`, or a valid ARN.
- If the source option group is in a different region than the copy, specify a valid option group ARN, for example `arn:aws:rds:us-west-2:123456789012:og:special-options`.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

TargetOptionGroupDescription

The description for the copied option group.

Type: String

Required: Yes

TargetOptionGroupIdentifier

The identifier for the copied option group.

Constraints:

- Cannot be null, empty, or blank
- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-option-group`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

OptionGroup

Type: [OptionGroup](#) (p. 333) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

OptionGroupAlreadyExistsFault

The option group you are trying to create already exists.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

OptionGroupQuotaExceededFault

The quota of 20 option groups was exceeded for this AWS account.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
?Action=CopyOptionGroup
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&SourceOptionGroupIdentifier=arn%3Aaws%3Aards%3Aus-
west-2%3A815981987263%3og%3Amy-remote-option-group
&TargetOptionGroupDescription=New%20option%20group
&TargetOptionGroupIdentifier=new-local-option-group
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140429/us-east-1/rds/aws4_request
&X-Amz-Date=20140429T175351Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=9164337efa99caf850e874a1cb7ef62f3cea29d0b448b9e0e7c53b288ddffed2
```

Sample Response

```
<CopyOptionGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <CopyOptionGroupResult>
    <OptionGroup>
      <OptionGroupName>new-local-option-group</OptionGroupName>
      <MajorEngineVersion>5.6</MajorEngineVersion>
      <AllowsVpcAndNonVpcInstanceMemberships>>false</
AllowsVpcAndNonVpcInstanceMemberships>
      <EngineName>mysql</EngineName>
      <OptionGroupDescription>description</OptionGroupDescription>
      <Options>
        <Option>
          <Port>11211</Port>
          <OptionName>MEMCACHED</OptionName>
          <OptionDescription>InnoDB Memcached for MySQL</OptionDescription>
          <Persistent>>false</Persistent>
          <OptionSettings>
            <OptionSetting>
              <DataType>BOOLEAN</DataType>
              <IsModifiable>>true</IsModifiable>
              <IsCollection>>false</IsCollection>
            </OptionSetting>
          </OptionSettings>
        </Option>
      </Options>
    </OptionGroup>
  </CopyOptionGroupResult>
</CopyOptionGroupResponse>
```



```
<Description>If enabled when there is no more memory to
store items, memcached will return an error rather than evicting items.</
Description>
  <Name>ERROR_ON_MEMORY_EXHAUSTED</Name>
  <Value>0</Value>
  <ApplyType>STATIC</ApplyType>
  <AllowedValues>0,1</AllowedValues>
  <DefaultValue>0</DefaultValue>
</OptionSetting>
<OptionSetting>
  <DataType>INTEGER</DataType>
  <IsModifiable>true</IsModifiable>
  <IsCollection>>false</IsCollection>
  <Description>The backlog queue configures how many network
connections can be waiting to be processed by memcached</Description>
  <Name>BACKLOG_QUEUE_LIMIT</Name>
  <Value>1024</Value>
  <ApplyType>STATIC</ApplyType>
  <AllowedValues>1-2048</AllowedValues>
  <DefaultValue>1024</DefaultValue>
</OptionSetting>
</OptionSettings>
<VpcSecurityGroupMemberships/>
<Permanent>>false</Permanent>
<DBSecurityGroupMemberships>
  <DBSecurityGroup>
    <Status>authorized</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroupMemberships>
</Option>
</Options>
</OptionGroup>
</CopyOptionGroupResult>
<ResponseMetadata>
  <RequestId>2928d60e-beb6-11d3-8e5c-3ccda5460c46</RequestId>
</ResponseMetadata>
</CopyOptionGroupResponse>
```

CreateDBCluster

Creates a new Amazon Aurora DB cluster.

You can use the `ReplicationSourceIdentifier` parameter to create the DB cluster as a Read Replica of another DB cluster.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

AvailabilityZones.AvailabilityZone.N

A list of EC2 Availability Zones that instances in the DB cluster can be created in. For information on regions and Availability Zones, see [Regions and Availability Zones](#).

Type: array of Strings

Required: No

BackupRetentionPeriod

The number of days for which automated backups are retained. You must specify a minimum value of 1.

Default: 1

Constraints:

- Must be a value from 1 to 35

Type: Integer

Required: No

CharacterSetName

A value that indicates that the DB cluster should be associated with the specified CharacterSet.

Type: String

Required: No

DatabaseName

The name for your database of up to 8 alpha-numeric characters. If you do not provide a name, Amazon RDS will not create a database in the DB cluster you are creating.

Type: String

Required: No

DBClusterIdentifier

The DB cluster identifier. This parameter is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster1`

Type: String

Required: Yes

DBClusterParameterGroupName

The name of the DB cluster parameter group to associate with this DB cluster. If this argument is omitted, `default.aurora5.6` will be used.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter

- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DBSubnetGroupName

A DB subnet group to associate with this DB cluster.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Engine

The name of the database engine to be used for this DB cluster.

Valid Values: `aurora`

Type: String

Required: Yes

EngineVersion

The version number of the database engine to use.

Aurora

Example: `5.6.10a`

Type: String

Required: No

KmsKeyId

The KMS key identifier for an encrypted DB cluster.

The KMS key identifier is the Amazon Resource Name (ARN) for the KMS encryption key. If you are creating a DB cluster with the same AWS account that owns the KMS encryption key used to encrypt the new DB cluster, then you can use the KMS key alias instead of the ARN for the KMS encryption key.

If the `StorageEncrypted` parameter is true, and you do not specify a value for the `KmsKeyId` parameter, then Amazon RDS will use your default encryption key. AWS KMS creates the default encryption key for your AWS account. Your AWS account has a different default encryption key for each AWS region.

Type: String

Required: No

MasterUsername

The name of the master user for the DB cluster.

Constraints:

- Must be 1 to 16 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

Type: String

Required: No

MasterUserPassword

The password for the master database user. This password can contain any printable ASCII character except `/`, `""`, or `@`.

Constraints: Must contain from 8 to 41 characters.

Type: String

Required: No

OptionGroupName

A value that indicates that the DB cluster should be associated with the specified option group.

Permanent options cannot be removed from an option group. The option group cannot be removed from a DB cluster once it is associated with a DB cluster.

Type: String

Required: No

Port

The port number on which the instances in the DB cluster accept connections.

Default: 3306

Type: Integer

Required: No

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled using the `BackupRetentionPeriod` parameter.

Default: A 30-minute window selected at random from an 8-hour block of time per region. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Constraints:

- Must be in the format `hh24:mi-hh24:mi`.
- Times should be in Universal Coordinated Time (UTC).
- Must not conflict with the preferred maintenance window.
- Must be at least 30 minutes.

Type: String

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Format: `ddd:hh24:mi-ddd:hh24:mi`

Default: A 30-minute window selected at random from an 8-hour block of time per region, occurring on a random day of the week. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Valid Days: Mon, Tue, Wed, Thu, Fri, Sat, Sun

Constraints: Minimum 30-minute window.

Type: String

Required: No

ReplicationSourceIdentifier

The Amazon Resource Name (ARN) of the source DB cluster if this DB cluster is created as a Read Replica.

Type: String

Required: No

StorageEncrypted

Specifies whether the DB cluster is encrypted.

Type: Boolean

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

VpcSecurityGroupIds.VpcSecurityGroupId.N

A list of EC2 VPC security groups to associate with this DB cluster.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)
- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterAlreadyExistsFault

User already has a DB cluster with the given identifier.

HTTP Status Code: 400

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterParameterGroupNotFound

DBClusterParameterGroupName does not refer to an existing DB Cluster parameter group.

HTTP Status Code: 404

DBClusterQuotaExceededFault

User attempted to create a new DB cluster and the user has already reached the maximum allowed DB cluster quota.

HTTP Status Code: 403

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InsufficientStorageClusterCapacity

There is insufficient storage available for the current action. You may be able to resolve this error by updating your subnet group to use different Availability Zones that have more storage available.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

InvalidDBSubnetGroupStateFault

The DB subnet group cannot be deleted because it is in use.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=CreateDBCluster  
&DBClusterIdentifier=sample-cluster  
&Engine=aurora  
  &MasterUserPassword=<password>  
&MasterUsername=myawsuser  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20150927/us-east-1/rds/aws4_request  
&X-Amz-Date=20150927T164851Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=6a8f4bd6a98f649c75ea04a6b3929ecc75ac09739588391cd7250f5280e716db
```

Sample Response

```
<CreateDBClusterResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">  
  <CreateDBClusterResult>  
    <DBCluster>  
      <Port>3306</Port>  
      <Engine>aurora</Engine>  
      <Status>creating</Status>  
      <BackupRetentionPeriod>1</BackupRetentionPeriod>  
      <VpcSecurityGroups>  
        <VpcSecurityGroupMembership>  
          <Status>active</Status>  
          <VpcSecurityGroupId>sg-2103dc23</VpcSecurityGroupId>  
        </VpcSecurityGroupMembership>  
      </VpcSecurityGroups>  
      <DBSubnetGroup>default</DBSubnetGroup>  
      <EngineVersion>5.6.10a</EngineVersion>
```

```
<Endpoint>sample-cluster.cluster-ctrayan0ryng.us-  
east-1.rds.amazonaws.com</Endpoint>  
<DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>  
<AvailabilityZones>  
  <AvailabilityZone>us-east-1a</AvailabilityZone>  
  <AvailabilityZone>us-east-1c</AvailabilityZone>  
  <AvailabilityZone>us-east-1e</AvailabilityZone>  
</AvailabilityZones>  
<DBClusterIdentifier>sample-cluster</DBClusterIdentifier>  
<PreferredBackupWindow>04:22-04:52</PreferredBackupWindow>  
<PreferredMaintenanceWindow>fri:06:44-fri:07:14</  
PreferredMaintenanceWindow>  
<DBClusterMembers/>  
<AllocatedStorage>1</AllocatedStorage>  
<MasterUsername>myawsuser</MasterUsername>  
</DBCluster>  
</CreateDBClusterResult>  
<ResponseMetadata>  
  <RequestId>46d2b228-7681-11e5-3e8b-9b2c0d5d51a9</RequestId>  
</ResponseMetadata>  
</CreateDBClusterResponse>
```

CreateDBClusterParameterGroup

Creates a new DB cluster parameter group.

Parameters in a DB cluster parameter group apply to all of the instances in a DB cluster.

A DB cluster parameter group is initially created with the default parameters for the database engine used by instances in the DB cluster. To provide custom values for any of the parameters, you must modify the group after creating it using [ModifyDBClusterParameterGroup \(p. 199\)](#). Once you've created a DB cluster parameter group, you need to associate it with your DB cluster using [ModifyDBCluster \(p. 194\)](#). When you associate a new DB cluster parameter group with a running DB cluster, you need to reboot the DB instances in the DB cluster without failover for the new DB cluster parameter group and associated settings to take effect.

Important

After you create a DB cluster parameter group, you should wait at least 5 minutes before creating your first DB cluster that uses that DB cluster parameter group as the default parameter group. This allows Amazon RDS to fully complete the create action before the DB cluster parameter group is used as the default for a new DB cluster. This is especially important for parameters that are critical when creating the default database for a DB cluster, such as the character set for the default database defined by the `character_set_database` parameter. You can use the *Parameter Groups* option of the [Amazon RDS console](#) or the [DescribeDBClusterParameters \(p. 109\)](#) command to verify that your DB cluster parameter group has been created or modified.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBClusterParameterGroupName

The name of the DB cluster parameter group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Note

This value is stored as a lowercase string.

Type: String

Required: Yes

DBParameterGroupFamily

The DB cluster parameter group family name. A DB cluster parameter group can be associated with one and only one DB cluster parameter group family, and can be applied only to a DB cluster running a database engine and engine version compatible with that DB cluster parameter group family.

Type: String

Required: Yes

Description

The description for the DB cluster parameter group.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

Response Elements

The following element is returned by the service.

DBClusterParameterGroup

Contains the result of a successful invocation of the [CreateDBClusterParameterGroup](#) (p. 36) or [CopyDBClusterParameterGroup](#) (p. 16) action.

This data type is used as a request parameter in the [DeleteDBClusterParameterGroup](#) (p. 81) action, and as a response element in the [DescribeDBClusterParameterGroups](#) (p. 106) action.

Type: [DBClusterParameterGroup](#) (p. 297) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupAlreadyExists

A DB parameter group with the same name exists.

HTTP Status Code: 400

DBParameterGroupQuotaExceeded

Request would result in user exceeding the allowed number of DB parameter groups.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CreateDBClusterParameterGroup  
  &DBClusterParameterGroupName=samplegroup  
  &DBParameterGroupFamily=aurora5.6  
  &Description=Sample%20group  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20150318/us-east-1/rds/aws4_request  
  &X-Amz-Date=20150318T183624Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=86d521a3a117a033df0aa381fde0cd8a5ab5c7ab87a29aa9154438c3790ba611
```

Sample Response

```
<CreateDBClusterParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <CreateDBClusterParameterGroupResult>  
    <DBClusterParameterGroup>
```

```
<DBParameterGroupFamily>aurora5.6</DBParameterGroupFamily>
<Description>Sample group</Description>
<DBClusterParameterGroupName>samplegroup</DBClusterParameterGroupName>
</DBClusterParameterGroup>
</CreateDBClusterParameterGroupResult>
<ResponseMetadata>
  <RequestId>ae81a963-cd9d-11e4-8b88-8351746a4c92</RequestId>
</ResponseMetadata>
</CreateDBClusterParameterGroupResponse>
```

CreateDBClusterSnapshot

Creates a snapshot of a DB cluster. For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The identifier of the DB cluster to create a snapshot for. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster1`

Type: String

Required: Yes

DBClusterSnapshotIdentifier

The identifier of the DB cluster snapshot. This parameter is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster1-snapshot1`

Type: String

Required: Yes

Tags.Tag.N

The tags to be assigned to the DB cluster snapshot.

Type: array of [Tag](#) (p. 354) objects

Required: No

Response Elements

The following element is returned by the service.

DBClusterSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBClusterSnapshot](#) (p. 39)
- [DeleteDBClusterSnapshot](#) (p. 83)

This data type is used as a response element in the [DescribeDBClusterSnapshots](#) (p. 117) action.

Type: [DBClusterSnapshot](#) (p. 299) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterSnapshotAlreadyExistsFault

User already has a DB cluster snapshot with the given identifier.

HTTP Status Code: 400

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=CreateDBClusterSnapshot  
&DBClusterIdentifier=sample-cluster  
&DBClusterSnapshotIdentifier=sample-cluster-snapshot  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20150318/us-east-1/rds/aws4_request  
&X-Amz-Date=20150318T205321Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=9573ced573a41cdec8e2ef1d9b5235a141f97ae30b4469fc9b0f16149399c4bf
```

Sample Response

```
<CreateDBClusterSnapshotResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <CreateDBClusterSnapshotResult>  
    <DBClusterSnapshot>  
      <Port>0</Port>  
      <Engine>aurora</Engine>  
      <Status>creating</Status>  
      <SnapshotType>>manual</SnapshotType>  
      <LicenseModel>aurora</LicenseModel>  
      <DBClusterSnapshotIdentifier>sample-cluster-snapshot</  
DBClusterSnapshotIdentifier>  
      <SnapshotCreateTime>2015-03-18T20:53:22.523Z</SnapshotCreateTime>  
      <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>  
      <VpcId>vpc-3faffe54</VpcId>  
      <ClusterCreateTime>2015-03-06T22:11:13.826Z</ClusterCreateTime>  
      <PercentProgress>0</PercentProgress>
```

```
<AllocatedStorage>1</AllocatedStorage>
  <MasterUsername>awsuser</MasterUsername>
</DBClusterSnapshot>
</CreateDBClusterSnapshotResult>
<ResponseMetadata>
  <RequestId>d070d0d2-cea0-11e4-8c88-8351226c8c92</RequestId>
</ResponseMetadata>
</CreateDBClusterSnapshotResponse>
```

CreateDBInstance

Creates a new DB instance.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

AllocatedStorage

The amount of storage (in gigabytes) to be initially allocated for the database instance.

Type: Integer

MySQL

Constraints: Must be an integer from 5 to 6144.

MariaDB

Constraints: Must be an integer from 5 to 6144.

PostgreSQL

Constraints: Must be an integer from 5 to 6144.

Oracle

Constraints: Must be an integer from 10 to 6144.

SQL Server

Constraints: Must be an integer from 200 to 4096 (Standard Edition and Enterprise Edition) or from 20 to 4096 (Express Edition and Web Edition)

Type: Integer

Required: No

AutoMinorVersionUpgrade

Indicates that minor engine upgrades will be applied automatically to the DB instance during the maintenance window.

Default: `true`

Type: Boolean

Required: No

AvailabilityZone

The EC2 Availability Zone that the database instance will be created in. For information on regions and Availability Zones, see [Regions and Availability Zones](#).

Default: A random, system-chosen Availability Zone in the endpoint's region.

Example: `us-east-1d`

Constraint: The `AvailabilityZone` parameter cannot be specified if the `MultiAZ` parameter is set to `true`. The specified Availability Zone must be in the same region as the current endpoint.

Type: String

Required: No

BackupRetentionPeriod

The number of days for which automated backups are retained. Setting this parameter to a positive number enables backups. Setting this parameter to 0 disables automated backups.

Default: 1

Constraints:

- Must be a value from 0 to 35
- Cannot be set to 0 if the DB instance is a source to Read Replicas

Type: Integer

Required: No

CharacterSetName

For supported engines, indicates that the DB instance should be associated with the specified CharacterSet.

Type: String

Required: No

CopyTagsToSnapshot

True to copy all tags from the DB instance to snapshots of the DB instance; otherwise false. The default is false.

Type: Boolean

Required: No

DBClusterIdentifier

The identifier of the DB cluster that the instance will belong to.

For information on creating a DB cluster, see [CreateDBCluster \(p. 30\)](#).

Type: String

Type: String

Required: No

DBInstanceClass

The compute and memory capacity of the DB instance.

Valid Values: db.t1.micro | db.m1.small | db.m1.medium | db.m1.large | db.m1.xlarge | db.m2.xlarge | db.m2.2xlarge | db.m2.4xlarge | db.m3.medium | db.m3.large | db.m3.xlarge | db.m3.2xlarge | db.m4.large | db.m4.xlarge | db.m4.2xlarge | db.m4.4xlarge | db.m4.10xlarge | db.r3.large | db.r3.xlarge | db.r3.2xlarge | db.r3.4xlarge | db.r3.8xlarge | db.t2.micro | db.t2.small | db.t2.medium | db.t2.large

Type: String

Required: Yes

DBInstanceIdentifier

The DB instance identifier. This parameter is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens (1 to 15 for SQL Server).
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: mydbinstance

Type: String

Required: Yes

DBName

The meaning of this parameter differs according to the database engine you use.

Type: String

MySQL

The name of the database to create when the DB instance is created. If this parameter is not specified, no database is created in the DB instance.

Constraints:

- Must contain 1 to 64 alphanumeric characters
- Cannot be a word reserved by the specified database engine

MariaDB

The name of the database to create when the DB instance is created. If this parameter is not specified, no database is created in the DB instance.

Constraints:

- Must contain 1 to 64 alphanumeric characters
- Cannot be a word reserved by the specified database engine

PostgreSQL

The name of the database to create when the DB instance is created. If this parameter is not specified, the default "postgres" database is created in the DB instance.

Constraints:

- Must contain 1 to 63 alphanumeric characters
- Must begin with a letter or an underscore. Subsequent characters can be letters, underscores, or digits (0-9).
- Cannot be a word reserved by the specified database engine

Oracle

The Oracle System ID (SID) of the created DB instance.

Default: ORCL

Constraints:

- Cannot be longer than 8 characters

SQL Server

Not applicable. Must be null.

Amazon Aurora

The name of the database to create when the primary instance of the DB cluster is created. If this parameter is not specified, no database is created in the DB instance.

Constraints:

- Must contain 1 to 64 alphanumeric characters
- Cannot be a word reserved by the specified database engine

Type: String

Required: No

DBParameterGroupName

The name of the DB parameter group to associate with this DB instance. If this argument is omitted, the default DBParameterGroup for the specified engine will be used.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DBSecurityGroups.DBSecurityGroupName.N

A list of DB security groups to associate with this DB instance.

Default: The default DB security group for the database engine.

Type: array of Strings

Required: No

DBSubnetGroupName

A DB subnet group to associate with this DB instance.

If there is no DB subnet group, then it is a non-VPC DB instance.

Type: String

Required: No

Domain

Specify the Active Directory Domain to create the instance in.

Type: String

Required: No

DomainIAMRoleName

Specify the name of the IAM role to be used when making API calls to the Directory Service.

Type: String

Required: No

Engine

The name of the database engine to be used for this instance.

Valid Values: `mysql` | `mariadb` | `oracle-se1` | `oracle-se2` | `oracle-se` | `oracle-ee` | `sqlserver-ee` | `sqlserver-se` | `sqlserver-ex` | `sqlserver-web` | `postgres` | `aurora`

Not every database engine is available for every AWS region.

Type: String

Required: Yes

EngineVersion

The version number of the database engine to use.

The following are the database engines and major and minor versions that are available with Amazon RDS. Not every database engine is available for every AWS region.

Amazon Aurora

- **Version 5.6 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-2, eu-west-1, us-east-1, us-east-2, us-west-2):** 5.6.10a

MariaDB

- **Version 10.1 (available in these AWS regions: us-east-2):** 10.1.16
- **Version 10.1 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-west-1, us-west-2):** 10.1.14
- **Version 10.0 (available in all AWS regions):** 10.0.24
- **Version 10.0 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 10.0.17

Microsoft SQL Server 2016

- 13.00.2164.0.v1 (supported for all editions, and all AWS regions except sa-east-1)

Microsoft SQL Server 2014

- 12.00.5000.0.v1 (supported for all editions, and all AWS regions)
- 12.00.4422.0.v1 (supported for all editions except Enterprise Edition, and all AWS regions except us-east-2)

Microsoft SQL Server 2012

- 11.00.6020.0.v1 (supported for all editions, and all AWS regions)
- 11.00.5058.0.v1 (supported for all editions, and all AWS regions except us-east-2)
- 11.00.2100.60.v1 (supported for all editions, and all AWS regions except us-east-2)

Microsoft SQL Server 2008 R2

- 10.50.6529.0.v1 (supported for all editions, and all AWS regions except us-east-2)
- 10.50.6000.34.v1 (supported for all editions, and all AWS regions except us-east-2)
- 10.50.2789.0.v1 (supported for all editions, and all AWS regions except us-east-2)

MySQL

- **Version 5.7 (available in all AWS regions):** 5.7.11
- **Version 5.7 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.7.10
- **Version 5.6 (available in all AWS regions):** 5.6.29
- **Version 5.6 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.6.27
- **Version 5.6 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.6.23

- **Version 5.6 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.6.19a | 5.6.19b | 5.6.21 | 5.6.21b | 5.6.22
- **Version 5.5 (available in all AWS regions):** 5.5.46
- **Version 5.5 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.5.42
- **Version 5.5 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.5.40b | 5.5.41
- **Version 5.5 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 5.5.40 | 5.5.40a

Oracle 12c

- 12.1.0.2.v6 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.2.v5 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.2.v4 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.2.v3 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.2.v2 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.2.v1 (supported for EE in all AWS regions, and SE2 in all AWS regions except us-gov-west-1)
- 12.1.0.1.v6 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)
- 12.1.0.1.v5 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)
- 12.1.0.1.v4 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)
- 12.1.0.1.v3 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)
- 12.1.0.1.v2 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)
- 12.1.0.1.v1 (supported for EE, SE1, and SE, in all AWS regions except ap-south-1, ap-northeast-2)

Oracle 11g

- 11.2.0.4.v10 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v9 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v8 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v7 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v6 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v5 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v4 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v3 (supported for EE, SE1, and SE, in all AWS regions)
- 11.2.0.4.v1 (supported for EE, SE1, and SE, in all AWS regions)

PostgreSQL

- **Version 9.5 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-west-1, us-west-2):** 9.5.4
- **Version 9.5 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-east-2, us-west-1, us-west-2):** 9.5.2
- **Version 9.4 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-west-1, us-west-2):** 9.4.9
- **Version 9.4 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-south-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-east-2, us-west-1, us-west-2):** 9.4.7
- **Version 9.4 (available in all AWS regions):** 9.4.5
- **Version 9.4 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 9.4.4
- **Version 9.4 (available in these AWS regions: ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-east-2, us-gov-west-1, us-west-1, us-west-2):** 9.4.1
- **Version 9.3 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 9.3.10 | 9.3.3 | 9.3.5 | 9.3.6 | 9.3.9
- **Version 9.3 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-west-1, sa-east-1, us-east-1, us-gov-west-1, us-west-1, us-west-2):** 9.3.11 | 9.3.2
- **Version 9.3 (available in these AWS regions: ap-northeast-1, ap-southeast-1, ap-southeast-2, eu-central-1, eu-west-1, sa-east-1, us-east-1, us-west-1, us-west-2):** 9.3.12 | 9.3.14

Type: String

Required: No

Iops

The amount of Provisioned IOPS (input/output operations per second) to be initially allocated for the DB instance.

Constraints: Must be a multiple between 3 and 10 of the storage amount for the DB instance. Must also be an integer multiple of 1000. For example, if the size of your DB instance is 500 GB, then your `Iops` value can be 2000, 3000, 4000, or 5000.

Type: Integer

Required: No

KmsKeyId

The KMS key identifier for an encrypted DB instance.

The KMS key identifier is the Amazon Resource Name (ARN) for the KMS encryption key. If you are creating a DB instance with the same AWS account that owns the KMS encryption key used to encrypt the new DB instance, then you can use the KMS key alias instead of the ARN for the KMS encryption key.

If the `StorageEncrypted` parameter is true, and you do not specify a value for the `KmsKeyId` parameter, then Amazon RDS will use your default encryption key. AWS KMS creates the default encryption key for your AWS account. Your AWS account has a different default encryption key for each AWS region.

Type: String

Required: No

LicenseModel

License model information for this DB instance.

Valid values: `license-included` | `bring-your-own-license` | `general-public-license`

Type: String

Required: No

MasterUsername

The name of master user for the client DB instance.

MySQL

Constraints:

- Must be 1 to 16 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

MariaDB

Constraints:

- Must be 1 to 16 alphanumeric characters.
- Cannot be a reserved word for the chosen database engine.

Type: String

Oracle

Constraints:

- Must be 1 to 30 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

SQL Server

Constraints:

- Must be 1 to 128 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

PostgreSQL

Constraints:

- Must be 1 to 63 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

Type: String

Required: No

MasterUserPassword

The password for the master database user. Can be any printable ASCII character except `"/`, `""`, or `"@"`.

Type: String

MySQL

Constraints: Must contain from 8 to 41 characters.

MariaDB

Constraints: Must contain from 8 to 41 characters.

Oracle

Constraints: Must contain from 8 to 30 characters.

SQL Server

Constraints: Must contain from 8 to 128 characters.

PostgreSQL

Constraints: Must contain from 8 to 128 characters.

Amazon Aurora

Constraints: Must contain from 8 to 41 characters.

Type: String

Required: No

MonitoringInterval

The interval, in seconds, between points when Enhanced Monitoring metrics are collected for the DB instance. To disable collecting Enhanced Monitoring metrics, specify 0. The default is 0.

If `MonitoringRoleArn` is specified, then you must also set `MonitoringInterval` to a value other than 0.

Valid Values: 0, 1, 5, 10, 15, 30, 60

Type: Integer

Required: No

MonitoringRoleArn

The ARN for the IAM role that permits RDS to send enhanced monitoring metrics to CloudWatch Logs. For example, `arn:aws:iam:123456789012:role/emaccess`. For information on creating a monitoring role, go to [To create an IAM role for Amazon RDS Enhanced Monitoring](#).

If `MonitoringInterval` is set to a value other than 0, then you must supply a `MonitoringRoleArn` value.

Type: String

Required: No

MultiAZ

Specifies if the DB instance is a Multi-AZ deployment. You cannot set the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to true.

Type: Boolean

Required: No

OptionGroupName

Indicates that the DB instance should be associated with the specified option group.

Permanent options, such as the TDE option for Oracle Advanced Security TDE, cannot be removed from an option group, and that option group cannot be removed from a DB instance once it is associated with a DB instance

Type: String

Required: No

Port

The port number on which the database accepts connections.

MySQL

Default: 3306

Valid Values: 1150-65535

Type: Integer

MariaDB

Default: 3306

Valid Values: 1150-65535

Type: Integer

PostgreSQL

Default: 5432

Valid Values: 1150-65535

Type: Integer

Oracle

Default: 1521

Valid Values: 1150-65535

SQL Server

Default: 1433

Valid Values: 1150-65535 except for 1434, 3389, 47001, 49152, and 49152 through 49156.

Amazon Aurora

Default: 3306

Valid Values: 1150-65535

Type: Integer

Type: Integer

Required: No

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled, using the `BackupRetentionPeriod` parameter. For more information, see [DB Instance Backups](#).

Default: A 30-minute window selected at random from an 8-hour block of time per region. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Constraints:

- Must be in the format `hh24:mi-hh24:mi`.
- Times should be in Universal Coordinated Time (UTC).
- Must not conflict with the preferred maintenance window.
- Must be at least 30 minutes.

Type: String

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC). For more information, see [DB Instance Maintenance](#).

Format: `ddd:hh24:mi-ddd:hh24:mi`

Default: A 30-minute window selected at random from an 8-hour block of time per region, occurring on a random day of the week. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Valid Days: Mon, Tue, Wed, Thu, Fri, Sat, Sun

Constraints: Minimum 30-minute window.

Type: String

Required: No

PromotionTier

A value that specifies the order in which an Aurora Replica is promoted to the primary instance after a failure of the existing primary instance. For more information, see [Fault Tolerance for an Aurora DB Cluster](#).

Default: 1

Valid Values: 0 - 15

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance. A value of `true` specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address. A value of `false` specifies an internal instance with a DNS name that resolves to a private IP address.

Default: The default behavior varies depending on whether a VPC has been requested or not. The following list shows the default behavior in each case.

- **Default VPC:** `true`
- **VPC:** `false`

If no DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be publicly accessible. If a specific DB subnet group has

been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be private.

Type: Boolean

Required: No

StorageEncrypted

Specifies whether the DB instance is encrypted.

Default: false

Type: Boolean

Required: No

StorageType

Specifies the storage type to be associated with the DB instance.

Valid values: `standard` | `gp2` | `io1`

If you specify `io1`, you must also include a value for the `Iops` parameter.

Default: `io1` if the `Iops` parameter is specified; otherwise `standard`

Type: String

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TdeCredentialArn

The ARN from the Key Store with which to associate the instance for TDE encryption.

Type: String

Required: No

TdeCredentialPassword

The password for the given ARN from the Key Store in order to access the device.

Type: String

Required: No

Timezone

The time zone of the DB instance. The time zone parameter is currently supported only by [Microsoft SQL Server](#).

Type: String

Required: No

VpcSecurityGroupIds.VpcSecurityGroupID.N

A list of EC2 VPC security groups to associate with this DB instance.

Default: The default EC2 VPC security group for the DB subnet group's VPC.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance \(p. 42\)](#)
- [DeleteDBInstance \(p. 85\)](#)
- [ModifyDBInstance \(p. 204\)](#)

This data type is used as a response element in the [DescribeDBInstances \(p. 124\)](#) action.

Type: [DBInstance](#) (p. 304) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

AuthorizationNotFound

Specified CIDRIP or EC2 security group is not authorized for the specified DB security group. RDS may not also be authorized via IAM to perform necessary actions on your behalf.

HTTP Status Code: 404

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBInstanceAlreadyExists

User already has a DB instance with the given identifier.

HTTP Status Code: 400

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DomainNotFoundFault

Domain does not refer to an existing Active Directory Domain.

HTTP Status Code: 404

InstanceQuotaExceeded

Request would result in user exceeding the allowed number of DB instances.

HTTP Status Code: 400

InsufficientDBInstanceCapacity

Specified DB instance class is not available in the specified Availability Zone.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

ProvisionedIopsNotAvailableInAZFault

Provisioned IOPS not available in the specified Availability Zone.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageTypeNotSupported

StorageType specified cannot be associated with the DB Instance.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CreateDBInstance  
  &AllocatedStorage=15  
  &DBInstanceClass=db.m1.large  
  &DBInstanceIdentifier=myawsuser-dbi01  
  &Engine=MySQL  
  &MasterUserPassword=<password>  
  &MasterUsername=myawsuser  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140424/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140424T194844Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=bee4aabc750bf7dad0cd9e22b952bd6089d91e2a16592c2293e532eeaab8bc77
```

Sample Response

```
<CreateDBInstanceResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <CreateDBInstanceResult>  
    <DBInstance>  
      <BackupRetentionPeriod>7</BackupRetentionPeriod>  
      <DBInstanceStatus>creating</DBInstanceStatus>  
      <MultiAZ>false</MultiAZ>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>myawsuser-dbi01</DBInstanceIdentifier>
```

```
<PreferredBackupWindow>03:50-04:20</PreferredBackupWindow>
<PreferredMaintenanceWindow>wed:06:38-wed:07:08</
PreferredMaintenanceWindow>
<ReadReplicaDBInstanceIdentifiers/>
<Engine>mysql</Engine>
<PendingModifiedValues>
  <MasterUserPassword>****</MasterUserPassword>
</PendingModifiedValues>
<LicenseModel>general-public-license</LicenseModel>
<EngineVersion>5.6.13</EngineVersion>
<DBParameterGroups>
  <DBParameterGroup>
    <ParameterApplyStatus>in-sync</ParameterApplyStatus>
    <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
  </DBParameterGroup>
</DBParameterGroups>
<OptionGroupMemberships>
  <OptionGroupMembership>
    <OptionGroupName>default:mysql-5-6</OptionGroupName>
    <Status>in-sync</Status>
  </OptionGroupMembership>
</OptionGroupMemberships>
<DBSecurityGroups>
  <DBSecurityGroup>
    <Status>active</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
<PubliclyAccessible>true</PubliclyAccessible>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<AllocatedStorage>15</AllocatedStorage>
<DBInstanceClass>db.m1.large</DBInstanceClass>
<MasterUsername>myawsuser</MasterUsername>
</DBInstance>
</CreateDBInstanceResult>
<ResponseMetadata>
  <RequestId>523e3218-afc7-11c3-90f5-f90431260ab4</RequestId>
</ResponseMetadata>
</CreateDBInstanceResponse>
```

CreateDBInstanceReadReplica

Creates a DB instance for a DB instance running MySQL, MariaDB, or PostgreSQL that acts as a Read Replica of a source DB instance.

All Read Replica DB instances are created as Single-AZ deployments with backups disabled. All other DB instance attributes (including DB security groups and DB parameter groups) are inherited from the source DB instance, except as specified below.

Important

The source DB instance must have backup retention enabled.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

AutoMinorVersionUpgrade

Indicates that minor engine upgrades will be applied automatically to the Read Replica during the maintenance window.

Default: Inherits from the source DB instance

Type: Boolean

Required: No

AvailabilityZone

The Amazon EC2 Availability Zone that the Read Replica will be created in.

Default: A random, system-chosen Availability Zone in the endpoint's region.

Example: `us-east-1d`

Type: String

Required: No

CopyTagsToSnapshot

True to copy all tags from the Read Replica to snapshots of the Read Replica; otherwise false. The default is false.

Type: Boolean

Required: No

DBInstanceClass

The compute and memory capacity of the Read Replica.

Valid Values: `db.m1.small` | `db.m1.medium` | `db.m1.large` | `db.m1.xlarge` | `db.m2.xlarge` | `db.m2.2xlarge` | `db.m2.4xlarge` | `db.m3.medium` | `db.m3.large` | `db.m3.xlarge` | `db.m3.2xlarge` | `db.m4.large` | `db.m4.xlarge` | `db.m4.2xlarge` | `db.m4.4xlarge` | `db.m4.10xlarge` | `db.r3.large` | `db.r3.xlarge` | `db.r3.2xlarge` | `db.r3.4xlarge` | `db.r3.8xlarge` | `db.t2.micro` | `db.t2.small` | `db.t2.medium` | `db.t2.large`

Default: Inherits from the source DB instance.

Type: String

Required: No

DBInstanceIdentifier

The DB instance identifier of the Read Replica. This identifier is the unique key that identifies a DB instance. This parameter is stored as a lowercase string.

Type: String

Required: Yes

DBSubnetGroupName

Specifies a DB subnet group for the DB instance. The new DB instance will be created in the VPC associated with the DB subnet group. If no DB subnet group is specified, then the new DB instance is not created in a VPC.

Constraints:

- Can only be specified if the source DB instance identifier specifies a DB instance in another region.
- The specified DB subnet group must be in the same region in which the operation is running.
- All Read Replicas in one region that are created from the same source DB instance must either:>
 - Specify DB subnet groups from the same VPC. All these Read Replicas will be created in the same VPC.
 - Not specify a DB subnet group. All these Read Replicas will be created outside of any VPC.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Iops

The amount of Provisioned IOPS (input/output operations per second) to be initially allocated for the DB instance.

Type: Integer

Required: No

MonitoringInterval

The interval, in seconds, between points when Enhanced Monitoring metrics are collected for the Read Replica. To disable collecting Enhanced Monitoring metrics, specify 0. The default is 0.

If `MonitoringRoleArn` is specified, then you must also set `MonitoringInterval` to a value other than 0.

Valid Values: 0, 1, 5, 10, 15, 30, 60

Type: Integer

Required: No

MonitoringRoleArn

The ARN for the IAM role that permits RDS to send enhanced monitoring metrics to CloudWatch Logs. For example, `arn:aws:iam:123456789012:role/emaccess`. For information on creating a monitoring role, go to [To create an IAM role for Amazon RDS Enhanced Monitoring](#).

If `MonitoringInterval` is set to a value other than 0, then you must supply a `MonitoringRoleArn` value.

Type: String

Required: No

OptionGroupName

The option group the DB instance will be associated with. If omitted, the default option group for the engine specified will be used.

Type: String

Required: No

Port

The port number that the DB instance uses for connections.

Default: Inherits from the source DB instance

Valid Values: 1150-65535

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance. A value of true specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address. A value of false specifies an internal instance with a DNS name that resolves to a private IP address.

Default: The default behavior varies depending on whether a VPC has been requested or not. The following list shows the default behavior in each case.

- **Default VPC:**true
- **VPC:**false

If no DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be publicly accessible. If a specific DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be private.

Type: Boolean

Required: No

SourceDBInstanceIdentifier

The identifier of the DB instance that will act as the source for the Read Replica. Each DB instance can have up to five Read Replicas.

Constraints:

- Must be the identifier of an existing MySQL, MariaDB, or PostgreSQL DB instance.
- Can specify a DB instance that is a MySQL Read Replica only if the source is running MySQL 5.6.
- Can specify a DB instance that is a PostgreSQL Read Replica only if the source is running PostgreSQL 9.3.5.
- The specified DB instance must have automatic backups enabled, its backup retention period must be greater than 0.
- If the source DB instance is in the same region as the Read Replica, specify a valid DB instance identifier.
- If the source DB instance is in a different region than the Read Replica, specify a valid DB instance ARN. For more information, go to [Constructing a Amazon RDS Amazon Resource Name \(ARN\)](#).

Type: String

Required: Yes

StorageType

Specifies the storage type to be associated with the Read Replica.

Valid values: `standard` | `gp2` | `io1`

If you specify `io1`, you must also include a value for the `Iops` parameter.

Default: `io1` if the `Iops` parameter is specified; otherwise `standard`

Type: String

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance \(p. 42\)](#)
- [DeleteDBInstance \(p. 85\)](#)
- [ModifyDBInstance \(p. 204\)](#)

This data type is used as a response element in the [DescribeDBInstances \(p. 124\)](#) action.

Type: [DBInstance \(p. 304\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBInstanceAlreadyExists

User already has a DB instance with the given identifier.

HTTP Status Code: 400

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 400

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 400

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 400

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupNotAllowedFault

Indicates that the DBSubnetGroup should not be specified while creating read replicas that lie in the same region as the source instance.

HTTP Status Code: 400

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 400

InstanceQuotaExceeded

Request would result in user exceeding the allowed number of DB instances.

HTTP Status Code: 400

InsufficientDBInstanceCapacity

Specified DB instance class is not available in the specified Availability Zone.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

InvalidDBSubnetGroupFault

Indicates the DBSubnetGroup does not belong to the same VPC as that of an existing cross region read replica of the same source instance.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

ProvisionedIopsNotAvailableInAZFault

Provisioned IOPS not available in the specified Availability Zone.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageTypeNotSupported

StorageType specified cannot be associated with the DB Instance.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CreateDBInstanceReadReplica  
  &DBInstanceIdentifier=mysqldb-rr  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &SourceDBInstanceIdentifier=mysqldb  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140425T170525Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=a5bc7bb9648272e9967c76fc582b308d3ee37d6c4f7a4eb62c2d885ec595c373
```

Sample Response

```
<CreateDBInstanceReadReplicaResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <CreateDBInstanceReadReplicaResult>  
    <DBInstance>  
      <BackupRetentionPeriod>0</BackupRetentionPeriod>  
      <MultiAZ>>false</MultiAZ>  
      <DBInstanceStatus>creating</DBInstanceStatus>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>mysqldb-rr</DBInstanceIdentifier>  
      <PreferredBackupWindow>08:14-08:44</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</  
PreferredMaintenanceWindow>  
      <ReadReplicaDBInstanceIdentifiers/>  
      <Engine>mysql</Engine>  
      <PendingModifiedValues/>  
      <LicenseModel>general-public-license</LicenseModel>
```

```
<EngineVersion>5.6.13</EngineVersion>
<DBParameterGroups>
  <DBParameterGroup>
    <ParameterApplyStatus>in-sync</ParameterApplyStatus>
    <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
  </DBParameterGroup>
</DBParameterGroups>
<ReadReplicaSourceDBInstanceIdentifier>mysqldb</
ReadReplicaSourceDBInstanceIdentifier>
<OptionGroupMemberships>
  <OptionGroupMembership>
    <OptionGroupName>default:mysql-5-6</OptionGroupName>
    <Status>pending-apply</Status>
  </OptionGroupMembership>
</OptionGroupMemberships>
<PubliclyAccessible>true</PubliclyAccessible>
<DBSecurityGroups>
  <DBSecurityGroup>
    <Status>active</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
<DBName>mysqldb</DBName>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<AllocatedStorage>100</AllocatedStorage>
<MasterUsername>myawsuser</MasterUsername>
<DBInstanceClass>db.m1.medium</DBInstanceClass>
</DBInstance>
</CreateDBInstanceReadReplicaResult>
<ResponseMetadata>
  <RequestId>ba8dedf0-bb9a-11d3-855b-576787000e19</RequestId>
</ResponseMetadata>
</CreateDBInstanceReadReplicaResponse>
```


CreateDBParameterGroup

Creates a new DB parameter group.

A DB parameter group is initially created with the default parameters for the database engine used by the DB instance. To provide custom values for any of the parameters, you must modify the group after creating it using *ModifyDBParameterGroup*. Once you've created a DB parameter group, you need to associate it with your DB instance using *ModifyDBInstance*. When you associate a new DB parameter group with a running DB instance, you need to reboot the DB instance without failover for the new DB parameter group and associated settings to take effect.

Important

After you create a DB parameter group, you should wait at least 5 minutes before creating your first DB instance that uses that DB parameter group as the default parameter group. This allows Amazon RDS to fully complete the create action before the parameter group is used as the default for a new DB instance. This is especially important for parameters that are critical when creating the default database for a DB instance, such as the character set for the default database defined by the `character_set_database` parameter. You can use the *Parameter Groups* option of the [Amazon RDS console](#) or the *DescribeDBParameters* command to verify that your DB parameter group has been created or modified.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupFamily

The DB parameter group family name. A DB parameter group can be associated with one and only one DB parameter group family, and can be applied only to a DB instance running a database engine and engine version compatible with that DB parameter group family.

Type: String

Required: Yes

DBParameterGroupName

The name of the DB parameter group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Note

This value is stored as a lowercase string.

Type: String

Required: Yes

Description

The description for the DB parameter group.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

Response Elements

The following element is returned by the service.

DBParameterGroup

Contains the result of a successful invocation of the [CreateDBParameterGroup](#) (p. 61) action. This data type is used as a request parameter in the [DeleteDBParameterGroup](#) (p. 89) action, and as a response element in the [DescribeDBParameterGroups](#) (p. 131) action.
Type: [DBParameterGroup](#) (p. 310) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupAlreadyExists

A DB parameter group with the same name exists.
HTTP Status Code: 400

DBParameterGroupQuotaExceeded

Request would result in user exceeding the allowed number of DB parameter groups.
HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=CreateDBParameterGroup  
&DBParameterGroupFamily=MySQL5.1  
&DBParameterGroupName=mydbparamgroup3  
&Description=My%20new%20DB%20Parameter%20Group  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request  
&X-Amz-Date=20140423T201938Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=e9e5e723f627e872e8bccdc6ccc60bdfcf4a32ae6758ef0a3717ffae49097ae
```

Sample Response

```
<CreateDBParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <CreateDBParameterGroupResult>  
    <DBParameterGroup>  
      <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>  
      <Description>My new DB Parameter Group</Description>  
      <DBParameterGroupName>mydbparamgroup3</DBParameterGroupName>  
    </DBParameterGroup>  
  </CreateDBParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>7805c127-af22-11c3-96ac-6999cc5f7e72</RequestId>
```

```
</ResponseMetadata>  
</CreateDBParameterGroupResponse>
```

CreateDBSecurityGroup

Creates a new DB security group. DB security groups control access to a DB instance.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBSecurityGroupDescription

The description for the DB security group.

Type: String

Required: Yes

DBSecurityGroupName

The name for the DB security group. This value is stored as a lowercase string.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens
- Must not be "Default"

Example: mysecuritygroup

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

Response Elements

The following element is returned by the service.

DBSecurityGroup

Contains the result of a successful invocation of the following actions:

- [DescribeDBSecurityGroups](#) (p. 136)
- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [CreateDBSecurityGroup](#) (p. 64)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

This data type is used as a response element in the [DescribeDBSecurityGroups](#) (p. 136) action.

Type: [DBSecurityGroup](#) (p. 312) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSecurityGroupAlreadyExists

A DB security group with the name specified in *DBSecurityGroupName* already exists.

HTTP Status Code: 400

DBSecurityGroupNotSupported

A DB security group is not allowed for this action.

HTTP Status Code: 400

QuotaExceeded.DBSecurityGroup

Request would result in user exceeding the allowed number of DB security groups.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
?Action=CreateDBSecurityGroup
&DBSecurityGroupDescription=My%20new%20DB%20Security%20Group
&DBSecurityGroupName=mydbsecuritygroup00
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140424/us-east-1/rds/aws4_request
&X-Amz-Date=20140424T190716Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=c2f180a3f0f5d73b47f9c229937a78f3569bf14392db8093d9b2e6785609ab45
```

Sample Response

```
<CreateDBSecurityGroupResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <CreateDBSecurityGroupResult>
    <DBSecurityGroup>
      <EC2SecurityGroups/>
      <DBSecurityGroupDescription>My new DB Security Group</
DBSecurityGroupDescription>
      <IPRanges/>
      <OwnerId>803#####</OwnerId>
      <DBSecurityGroupName>mydbsecuritygroup00</DBSecurityGroupName>
    </DBSecurityGroup>
  </CreateDBSecurityGroupResult>
  <ResponseMetadata>
    <RequestId>e68ef6fa-afc1-11c3-845a-476777009d19</RequestId>
  </ResponseMetadata>
</CreateDBSecurityGroupResponse>
```

CreateDBSnapshot

Creates a DBSnapshot. The source DBInstance must be in "available" state.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBInstanceIdentifier

The DB instance identifier. This is the unique key that identifies a DB instance.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

DBSnapshotIdentifier

The identifier for the DB snapshot.

Constraints:

- Cannot be null, empty, or blank
- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-snapshot-id`

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

Response Elements

The following element is returned by the service.

DBSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBSnapshot \(p. 66\)](#)
- [DeleteDBSnapshot \(p. 93\)](#)

This data type is used as a response element in the [DescribeDBSnapshots \(p. 141\)](#) action.

Type: [DBSnapshot \(p. 314\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSnapshotAlreadyExists

DBSnapshotIdentifier is already used by an existing snapshot.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=CreateDBSnapshot  
&DBInstanceIdentifier=mysqldb-02  
&DBSnapshotIdentifier=mysqldb-snap-1  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request  
&X-Amz-Date=20140423T161105Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=e9649af6edcfbab4016f04d72e1b7fc16d8734c37477afcf25b3def625484ed2
```

Sample Response

```
<CreateDBSnapshotResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
<CreateDBSnapshotResult>  
<DBSnapshot>  
<Port>3306</Port>  
<OptionGroupName>default:mysql-5-6</OptionGroupName>  
<Engine>mysql</Engine>  
<Status>creating</Status>  
<SnapshotType>manual</SnapshotType>  
<LicenseModel>general-public-license</LicenseModel>  
<EngineVersion>5.6.13</EngineVersion>  
<DBInstanceIdentifier>mysqldb-02</DBInstanceIdentifier>  
<DBSnapshotIdentifier>mysqldb-snap-1</DBSnapshotIdentifier>  
<AvailabilityZone>us-east-1a</AvailabilityZone>  
<InstanceCreateTime>2014-04-21T22:24:26.573Z</InstanceCreateTime>  
<PercentProgress>0</PercentProgress>  
<AllocatedStorage>100</AllocatedStorage>  
<MasterUsername>myawsuser</MasterUsername>  
</DBSnapshot>  
</CreateDBSnapshotResult>  
<ResponseMetadata>
```

```
<RequestId>bd80a25a-af09-11c3-ed11-23c32f9aa7d3</RequestId>  
</ResponseMetadata>  
</CreateDBSnapshotResponse>
```


CreateDBSubnetGroup

Creates a new DB subnet group. DB subnet groups must contain at least one subnet in at least two AZs in the region.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBSubnetGroupDescription

The description for the DB subnet group.

Type: String

Required: Yes

DBSubnetGroupName

The name for the DB subnet group. This value is stored as a lowercase string.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: Yes

SubnetIds.SubnetIdentifier.N

The EC2 Subnet IDs for the DB subnet group.

Type: array of Strings

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

Response Elements

The following element is returned by the service.

DBSubnetGroup

Contains the result of a successful invocation of the following actions:

- [CreateDBSubnetGroup \(p. 69\)](#)
- [ModifyDBSubnetGroup \(p. 220\)](#)
- [DescribeDBSubnetGroups \(p. 145\)](#)
- [DeleteDBSubnetGroup \(p. 95\)](#)

This data type is used as a response element in the [DescribeDBSubnetGroups \(p. 145\)](#) action.

Type: [DBSubnetGroup \(p. 319\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSubnetGroupAlreadyExists

DBSubnetGroupName is already used by an existing DB subnet group.

HTTP Status Code: 400

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupQuotaExceeded

Request would result in user exceeding the allowed number of DB subnet groups.

HTTP Status Code: 400

DBSubnetQuotaExceededFault

Request would result in user exceeding the allowed number of subnets in a DB subnet groups.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
  ?Action=CreateDBSubnetGroup
  &DBSubnetGroupDescription=My%20new%20DB%20Subnet%20Group
  &DBSubnetGroupName=myawsuser-dbsubnetgroup
  &SignatureMethod=HmacSHA256
  &SignatureVersion=4
  &SubnetIds.member.1=subnet-e4d398a1
  &SubnetIds.member.2=subnet-c2bdb6ba
  &Version=2014-09-01
  &X-Amz-Algorithm=AWS4-HMAC-SHA256
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request
  &X-Amz-Date=20140425T173028Z
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
  &X-Amz-
Signature=f434cd02a766ea034637deb6f67996a743ca3e098efc9a5881c61e0c6859259d3
```

Sample Response

```
<CreateDBSubnetGroupResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <CreateDBSubnetGroupResult>
    <DBSubnetGroup>
      <VpcId>vpc-33dc97ea</VpcId>
      <SubnetGroupStatus>Complete</SubnetGroupStatus>
      <DBSubnetGroupDescription>My new DB Subnet Group</
DBSubnetGroupDescription>
      <DBSubnetGroupName>myawsuser-dbsubnetgroup</DBSubnetGroupName>
      <Subnets>
        <Subnet>
          <SubnetStatus>Active</SubnetStatus>
          <SubnetIdentifier>subnet-e4d398a1</SubnetIdentifier>
```

```
<SubnetAvailabilityZone>
  <Name>us-east-1b</Name>
  <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
</SubnetAvailabilityZone>
</Subnet>
<Subnet>
  <SubnetStatus>Active</SubnetStatus>
  <SubnetIdentifier>subnet-c2bdb6ba</SubnetIdentifier>
  <SubnetAvailabilityZone>
    <Name>us-east-1c</Name>
    <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
  </SubnetAvailabilityZone>
</Subnet>
</Subnets>
</DBSubnetGroup>
</CreateDBSubnetGroupResult>
<ResponseMetadata>
  <RequestId>3a401b3f-bb9e-11d3-f4c6-37db295f7674</RequestId>
</ResponseMetadata>
</CreateDBSubnetGroupResponse>
```

CreateEventSubscription

Creates an RDS event notification subscription. This action requires a topic ARN (Amazon Resource Name) created by either the RDS console, the SNS console, or the SNS API. To obtain an ARN with SNS, you must create a topic in Amazon SNS and subscribe to the topic. The ARN is displayed in the SNS console.

You can specify the type of source (`SourceType`) you want to be notified of, provide a list of RDS sources (`SourceIds`) that triggers the events, and provide a list of event categories (`EventCategories`) for events you want to be notified of. For example, you can specify `SourceType = db-instance`, `SourceIds = mydbinstance1, mydbinstance2` and `EventCategories = Availability, Backup`.

If you specify both the `SourceType` and `SourceIds`, such as `SourceType = db-instance` and `SourceIdentifier = myDBInstance1`, you will be notified of all the db-instance events for the specified source. If you specify a `SourceType` but do not specify a `SourceIdentifier`, you will receive notice of the events for that source type for all your RDS sources. If you do not specify either the `SourceType` nor the `SourceIdentifier`, you will be notified of events generated from all RDS sources belonging to your customer account.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

Enabled

A Boolean value; set to **true** to activate the subscription, set to **false** to create the subscription but not active it.

Type: Boolean

Required: No

EventCategories.EventCategory.N

A list of event categories for a `SourceType` that you want to subscribe to. You can see a list of the categories for a given `SourceType` in the [Events](#) topic in the Amazon RDS User Guide or by using the **DescribeEventCategories** action.

Type: array of Strings

Required: No

SnsTopicArn

The Amazon Resource Name (ARN) of the SNS topic created for event notification. The ARN is created by Amazon SNS when you create a topic and subscribe to it.

Type: String

Required: Yes

SourceIds.SourceId.N

The list of identifiers of the event sources for which events will be returned. If not specified, then all sources are included in the response. An identifier must begin with a letter and must contain only ASCII letters, digits, and hyphens; it cannot end with a hyphen or contain two consecutive hyphens.

Constraints:

- If `SourceIds` are supplied, `SourceType` must also be provided.
- If the source type is a DB instance, then a `DBInstanceIdentifier` must be supplied.
- If the source type is a DB security group, a `DBSecurityGroupName` must be supplied.
- If the source type is a DB parameter group, a `DBParameterGroupName` must be supplied.
- If the source type is a DB snapshot, a `DBSnapshotIdentifier` must be supplied.

Type: array of Strings

Required: No

SourceType

The type of source that will be generating the events. For example, if you want to be notified of events generated by a DB instance, you would set this parameter to `db-instance`. If this value is not specified, all events are returned.

Valid values: `db-instance` | `db-cluster` | `db-parameter-group` | `db-security-group` | `db-snapshot` | `db-cluster-snapshot`

Type: String

Required: No

SubscriptionName

The name of the subscription.

Constraints: The name must be less than 255 characters.

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

Response Elements

The following element is returned by the service.

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions \(p. 159\)](#) action.

Type: [EventSubscription \(p. 327\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

EventSubscriptionQuotaExceeded

You have reached the maximum number of event subscriptions.

HTTP Status Code: 400

SNSInvalidTopic

SNS has responded that there is a problem with the SNS topic specified.

HTTP Status Code: 400

SNSNoAuthorization

You do not have permission to publish to the SNS topic ARN.

HTTP Status Code: 400

SNSTopicArnNotFound

The SNS topic ARN does not exist.

HTTP Status Code: 404

SourceNotFound

The requested source could not be found.

HTTP Status Code: 404

SubscriptionAlreadyExist

The supplied subscription name already exists.

HTTP Status Code: 400

SubscriptionCategoryNotFound

The supplied category does not exist.

HTTP Status Code: 404

Examples

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
?Action=CreateEventSubscription
&Enabled=true
&EventCategories.member.1=failure
&EventCategories.member.2=configuration%20change
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&SnsTopicArn=arn%3Aaws%3Asns%3Aus-east-1%3A802#####%3Amyawsuser-RDS
&SourceType=db-security-group
&SubscriptionName=myawsuser-secgrp
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request
&X-Amz-Date=20140425T214325Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=7045960f6ab15609571fb05278004256e186b7633ab2a3ae46826d7713e0b461
```

Sample Response

```
<CreateEventSubscriptionResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <CreateEventSubscriptionResult>
    <EventSubscription>
      <SourceType>db-security-group</SourceType>
      <Enabled>true</Enabled>
      <CustomerAwsId>803#####</CustomerAwsId>
      <Status>creating</Status>
      <SubscriptionCreationTime>Fri Apr 25 21:43:25 UTC 2014</
SubscriptionCreationTime>
      <EventCategoriesList>
        <EventCategory>configuration change</EventCategory>
        <EventCategory>failure</EventCategory>
      </EventCategoriesList>
      <CustSubscriptionId>myawsuser-secgrp</CustSubscriptionId>
      <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</
SnsTopicArn>
    </EventSubscription>
  </CreateEventSubscriptionResult>
  <ResponseMetadata>
    <RequestId>f15e9dc3-bbb1-11d3-f4c6-37db295f7674</RequestId>
  </ResponseMetadata>
</CreateEventSubscriptionResponse>
```

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CreateEventSubscription  
  &Enabled=true  
  &EventCategories.member.1=creation  
  &EventCategories.member.2=deletion  
  &EventCategories.member.3=failover  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &SnsTopicArn=arn:aws:sns:us-east-1:802#####:myawsuser-RDS  
  &SourceType=db-instance  
  &SubscriptionName=myawsuser-inst  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140429/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140429T184410Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=1e1879f20ef3aec07135d69cc192426bf1cc5c42fc9dlacc7726bcd93155fb71
```

Sample Response

```
<CreateEventSubscriptionResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <CreateEventSubscriptionResult>  
    <EventSubscription>  
      <SourceType>db-instance</SourceType>  
      <Enabled>true</Enabled>  
      <CustomerAwsId>803#####</CustomerAwsId>  
      <Status>creating</Status>  
      <SubscriptionCreationTime>Tue Apr 29 18:44:10 UTC 2014</  
SubscriptionCreationTime>  
      <EventCategoriesList>  
        <EventCategory>creation</EventCategory>  
        <EventCategory>deletion</EventCategory>  
        <EventCategory>failover</EventCategory>  
      </EventCategoriesList>  
      <CustSubscriptionId>myawsuser-inst</CustSubscriptionId>  
      <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</  
SnsTopicArn>  
    </EventSubscription>  
  </CreateEventSubscriptionResult>  
  <ResponseMetadata>  
    <RequestId>30feb307-bebd-11d3-f4c6-37db295f7674</RequestId>  
  </ResponseMetadata>  
</CreateEventSubscriptionResponse>
```

CreateOptionGroup

Creates a new option group. You can create up to 20 option groups.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

EngineName

Specifies the name of the engine that this option group should be associated with.

Type: String

Required: Yes

MajorEngineVersion

Specifies the major version of the engine that this option group should be associated with.

Type: String

Required: Yes

OptionGroupDescription

The description of the option group.

Type: String

Required: Yes

OptionGroupName

Specifies the name of the option group to be created.

Constraints:

- Must be 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `myoptiongroup`

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

Response Elements

The following element is returned by the service.

OptionGroup

Type: [OptionGroup](#) (p. 333) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

OptionGroupAlreadyExistsFault

The option group you are trying to create already exists.

HTTP Status Code: 400

OptionGroupQuotaExceededFault

The quota of 20 option groups was exceeded for this AWS account.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=CreateOptionGroup  
  &EngineName=mysql  
  &MajorEngineVersion=5.6  
  &OptionGroupDescription=My%20Option%20Group  
  &OptionGroupName=myawsuser-og00  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140425T174519Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=d3a89afa4511d0c4ecab046d6dc760a72bfe6bb15999cce053adeb2617b60384
```

Sample Response

```
<CreateOptionGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <CreateOptionGroupResult>  
    <OptionGroup>  
      <AllowsVpcAndNonVpcInstanceMemberships>>true</  
AllowsVpcAndNonVpcInstanceMemberships>  
      <MajorEngineVersion>5.6</MajorEngineVersion>  
      <OptionGroupName>myawsuser-og00</OptionGroupName>  
      <EngineName>mysql</EngineName>  
      <OptionGroupDescription>My Option Group</OptionGroupDescription>  
      <Options/>  
    </OptionGroup>  
  </CreateOptionGroupResult>  
  <ResponseMetadata>  
    <RequestId>4d7f11f2-bbf0-11d3-ae4f-ee568ed6b36</RequestId>  
  </ResponseMetadata>  
</CreateOptionGroupResponse>
```

DeleteDBCluster

The DeleteDBCluster action deletes a previously provisioned DB cluster. When you delete a DB cluster, all automated backups for that DB cluster are deleted and cannot be recovered. Manual DB cluster snapshots of the specified DB cluster are not deleted.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The DB cluster identifier for the DB cluster to be deleted. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

FinalDBSnapshotIdentifier

The DB cluster snapshot identifier of the new DB cluster snapshot created when `SkipFinalSnapshot` is set to `false`.

Note

Specifying this parameter and also setting the `SkipFinalShapshot` parameter to `true` results in an error.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

SkipFinalSnapshot

Determines whether a final DB cluster snapshot is created before the DB cluster is deleted. If `true` is specified, no DB cluster snapshot is created. If `false` is specified, a DB cluster snapshot is created before the DB cluster is deleted.

Note

You must specify a `FinalDBSnapshotIdentifier` parameter if `SkipFinalSnapshot` is `false`.

Default: `false`

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)

- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterSnapshotAlreadyExistsFault

User already has a DB cluster snapshot with the given identifier.

HTTP Status Code: 400

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBCluster  
&DBClusterIdentifier=sample-cluster2  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140725/us-east-1/rds/aws4_request  
&X-Amz-Date=20140725T162148Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=815910f78c5a9813e1c15300fcf206e04da071b3586770169765292dc6aa2ed4
```

Sample Response

Amazon Relational Database Service API Reference
Example

```
<DeleteDBClusterResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">
  <DeleteDBClusterResult>
    <DBCluster>
      <Engine>aurora5.6</Engine>
      <Status>available</Status>
      <BackupRetentionPeriod>0</BackupRetentionPeriod>
      <DBSubnetGroup>my-subgroup</DBSubnetGroup>
      <EngineVersion>5.6.10a</EngineVersion>
      <Endpoint>sample-cluster2.cluster-cbfvmgb0y5fy.us-
east-1.rds.amazonaws.com</Endpoint>
      <DBClusterIdentifier>sample-cluster2</DBClusterIdentifier>
      <PreferredBackupWindow>04:45-05:15</PreferredBackupWindow>
      <PreferredMaintenanceWindow>sat:05:56-sat:06:26</
PreferredMaintenanceWindow>
      <DBClusterMembers/>
      <AllocatedStorage>15</AllocatedStorage>
      <MasterUsername>awsuser</MasterUsername>
    </DBCluster>
  </DeleteDBClusterResult>
  <ResponseMetadata>
    <RequestId>c72118dc-1417-11e4-8c7b-931a6c1fef28</RequestId>
  </ResponseMetadata>
</DeleteDBClusterResponse>
```

DeleteDBClusterParameterGroup

Deletes a specified DB cluster parameter group. The DB cluster parameter group to be deleted cannot be associated with any DB clusters.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterParameterGroupName

The name of the DB cluster parameter group.

Constraints:

- Must be the name of an existing DB cluster parameter group.
- You cannot delete a default DB cluster parameter group.
- Cannot be associated with any DB clusters.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=DeleteDBClusterParameterGroup
&DBClusterParameterGroupName=sample-cluster-pg
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request
&X-Amz-Date=20160913T172430Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=3f54b5ee720c2644296e98a1c0393a9abd91bc0847dfe7dd9be02ede8fd95ae5
```

Sample Response

```
<DeleteDBClusterParameterGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">
  <ResponseMetadata>
    <RequestId>ee0201e1-79d6-11e6-9b94-838991bd60c6</RequestId>
  </ResponseMetadata>
</DeleteDBClusterParameterGroupResponse>
```

DeleteDBClusterSnapshot

Deletes a DB cluster snapshot. If the snapshot is being copied, the copy operation is terminated.

Note

The DB cluster snapshot must be in the `available` state to be deleted.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBClusterSnapshotIdentifier

The identifier of the DB cluster snapshot to delete.

Constraints: Must be the name of an existing DB cluster snapshot in the `available` state.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBClusterSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBClusterSnapshot \(p. 39\)](#)
- [DeleteDBClusterSnapshot \(p. 83\)](#)

This data type is used as a response element in the [DescribeDBClusterSnapshots \(p. 117\)](#) action.

Type: [DBClusterSnapshot \(p. 299\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBClusterSnapshot  
&DBClusterSnapshotIdentifier=sample-cluster-snapshot  
&SignatureMethod=HmacSHA256
```

```
&SignatureVersion=4
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20150318/us-east-1/rds/aws4_request
&X-Amz-Date=20150318T215614Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=7aaab0a295151051bc4723f5b1f7b6b535615b8db9256bd56993c4dc6df4c2c4
```

Sample Response

```
<DeleteDBClusterSnapshotResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <DeleteDBClusterSnapshotResult>
    <DBClusterSnapshot>
      <Port>0</Port>
      <Status>available</Status>
      <Engine>aurora</Engine>
      <SnapshotType>manual</SnapshotType>
      <LicenseModel>aurora</LicenseModel>
      <DBClusterSnapshotIdentifier>sample-cluster-snapshot</
DBClusterSnapshotIdentifier>
      <SnapshotCreateTime>2015-03-18T20:53:22.523Z</SnapshotCreateTime>
      <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>
      <VpcId>vpc-3fabee54</VpcId>
      <ClusterCreateTime>2015-03-06T22:11:13.826Z</ClusterCreateTime>
      <PercentProgress>100</PercentProgress>
      <AllocatedStorage>1</AllocatedStorage>
      <MasterUsername>awsuser</MasterUsername>
    </DBClusterSnapshot>
  </DeleteDBClusterSnapshotResult>
  <ResponseMetadata>
    <RequestId>994ab08d-cdb9-2ce4-abf9-7528e6348483</RequestId>
  </ResponseMetadata>
</DeleteDBClusterSnapshotResponse>
```


DeleteDBInstance

The DeleteDBInstance action deletes a previously provisioned DB instance. When you delete a DB instance, all automated backups for that instance are deleted and cannot be recovered. Manual DB snapshots of the DB instance to be deleted by DeleteDBInstance are not deleted.

If you request a final DB snapshot the status of the Amazon RDS DB instance is `deleting` until the DB snapshot is created. The API action DescribeDBInstance is used to monitor the status of this operation. The action cannot be canceled or reverted once submitted.

Note that when a DB instance is in a failure state and has a status of `failed`, `incompatible-restore`, or `incompatible-network`, you can only delete it when the `SkipFinalSnapshot` parameter is set to `true`.

If the specified DB instance is part of an Amazon Aurora DB cluster, you cannot delete the DB instance if the following are true:

- The DB cluster is a Read Replica of another Amazon Aurora DB cluster.
- The DB instance is the only instance in the DB cluster.

To delete a DB instance in this case, first call the [PromoteReadReplicaDBCluster \(p. 233\)](#) API action to promote the DB cluster so it's no longer a Read Replica. After the promotion completes, then call the DeleteDBInstance API action to delete the final instance in the DB cluster.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBInstanceIdentifier

The DB instance identifier for the DB instance to be deleted. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

FinalDBSnapshotIdentifier

The DBSnapshotIdentifier of the new DBSnapshot created when SkipFinalSnapshot is set to `false`.

Note

Specifying this parameter and also setting the SkipFinalSnapshot parameter to `true` results in an error.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens
- Cannot be specified when deleting a Read Replica.

Type: String

Required: No

SkipFinalSnapshot

Determines whether a final DB snapshot is created before the DB instance is deleted. If `true` is specified, no DBSnapshot is created. If `false` is specified, a DB snapshot is created before the DB instance is deleted.

Note that when a DB instance is in a failure state and has a status of 'failed', 'incompatible-restore', or 'incompatible-network', it can only be deleted when the `SkipFinalSnapshot` parameter is set to "true".

Specify `true` when deleting a Read Replica.

Note

The `FinalDBSnapshotIdentifier` parameter must be specified if `SkipFinalSnapshot` is `false`.

Default: `false`

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance](#) (p. 42)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)

This data type is used as a response element in the [DescribeDBInstances](#) (p. 124) action.

Type: [DBInstance](#) (p. 304) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSnapshotAlreadyExists

DBSnapshotIdentifier is already used by an existing snapshot.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

SnapshotQuotaExceeded

Request would result in user exceeding the allowed number of DB snapshots.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
```

```
?Action=DeleteDBInstance
&DBInstanceIdentifier=mydatabase
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&SkipFinalSnapshot=true
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20131109/us-east-1/rds/aws4_request
&X-Amz-Date=20131109T001924Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=70e774e243c0fbb7ffe84029637005bf543e9e321cdf432c0b272be5687d32d8
```

Sample Response

```
<DeleteDBInstanceResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <DeleteDBInstanceResult>
    <DBInstance>
      <BackupRetentionPeriod>7</BackupRetentionPeriod>
      <DBInstanceStatus>deleting</DBInstanceStatus>
      <MultiAZ>>false</MultiAZ>
      <VpcSecurityGroups/>
      <DBInstanceIdentifier>mydatabase</DBInstanceIdentifier>
      <PreferredBackupWindow>08:14-08:44</PreferredBackupWindow>
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</
PreferredMaintenanceWindow>
      <AvailabilityZone>us-east-1a</AvailabilityZone>
      <ReadReplicaDBInstanceIdentifiers/>
      <LatestRestorableTime>2013-11-09T00:15:00Z</LatestRestorableTime>
      <Engine>mysql</Engine>
      <PendingModifiedValues/>
      <LicenseModel>general-public-license</LicenseModel>
      <EngineVersion>5.6.13</EngineVersion>
      <Endpoint>
        <Port>3306</Port>
        <Address>mydatabase.cf037hpkuvt.us-east-1.rds.amazonaws.com</
Address>
      </Endpoint>
      <DBParameterGroups>
        <DBParameterGroup>
          <ParameterApplyStatus>in-sync</ParameterApplyStatus>
          <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
        </DBParameterGroup>
      </DBParameterGroups>
      <OptionGroupMemberships>
        <OptionGroupMembership>
          <OptionGroupName>default:mysql-5-6</OptionGroupName>
          <Status>in-sync</Status>
        </OptionGroupMembership>
      </OptionGroupMemberships>
      <PubliclyAccessible>true</PubliclyAccessible>
      <DBSecurityGroups>
        <DBSecurityGroup>
          <Status>active</Status>
          <DBSecurityGroupName>default</DBSecurityGroupName>
        </DBSecurityGroup>
      </DBSecurityGroups>
    </DBInstance>
  </DeleteDBInstanceResult>
</DeleteDBInstanceResponse>
```

```
</DBSecurityGroups>
<DBName>mysqldb</DBName>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<InstanceCreateTime>2011-04-28T23:33:54.909Z</InstanceCreateTime>
<AllocatedStorage>100</AllocatedStorage>
<MasterUsername>myawsuser</MasterUsername>
<DBInstanceClass>db.m1.medium</DBInstanceClass>
</DBInstance>
</DeleteDBInstanceResult>
<ResponseMetadata>
  <RequestId>7369556f-b70d-11c3-faca-6ba18376ea1b</RequestId>
</ResponseMetadata>
</DeleteDBInstanceResponse>
```

DeleteDBParameterGroup

Deletes a specified DBParameterGroup. The DBParameterGroup to be deleted cannot be associated with any DB instances.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupName

The name of the DB parameter group.

Constraints:

- Must be the name of an existing DB parameter group
- You cannot delete a default DB parameter group
- Cannot be associated with any DB instances

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBParameterGroup  
&DBParameterGroupName=mydbparamgroup3  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request  
&X-Amz-Date=20140423T203550Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=7364d4d88b4200d14da46aac748781a6da08bc18c5fdc468ee18780e6f84b19e
```

Sample Response

```
<DeleteDBParameterGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <ResponseMetadata>  
    <RequestId>cad6c267-ba25-11d3-fe11-33d33a9bb7e3</RequestId>  
  </ResponseMetadata>  
</DeleteDBParameterGroupResponse>
```

DeleteDBSecurityGroup

Deletes a DB security group.

Note

The specified DB security group must not be associated with any DB instances.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBSecurityGroupName

The name of the DB security group to delete.

Note

You cannot delete the default DB security group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens
- Must not be "Default"

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

InvalidDBSecurityGroupState

The state of the DB security group does not allow deletion.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBSecurityGroup  
&DBSecurityGroupName=mydbsecuritygroup  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request  
&X-Amz-Date=20140423T203336Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date
```

```
&X-Amz-  
Signature=873c15061fe60b9db8ea63137e5af82b157019696fc3e9764ef2abd9d71c640a
```

Sample Response

```
<DeleteDBSecurityGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ResponseMetadata>  
    <RequestId>7aec7454-ba25-11d3-855b-576787000e19</RequestId>  
  </ResponseMetadata>  
</DeleteDBSecurityGroupResponse>
```


DeleteDBSnapshot

Deletes a DBSnapshot. If the snapshot is being copied, the copy operation is terminated.

Note

The DBSnapshot must be in the `available` state to be deleted.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBSnapshotIdentifier

The DBSnapshot identifier.

Constraints: Must be the name of an existing DB snapshot in the `available` state.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBSnapshot \(p. 66\)](#)
- [DeleteDBSnapshot \(p. 93\)](#)

This data type is used as a response element in the [DescribeDBSnapshots \(p. 141\)](#) action.

Type: [DBSnapshot \(p. 314\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBSnapshot  
&DBSnapshotIdentifier=mysqldb-snap-02  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256
```

```
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request
&X-Amz-Date=20140423T203337Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=619f04acffeb4b80d2f442526b1c9da79d0b3097151c24f28e83e851d6541414
```

Sample Response

```
<DeleteDBSnapshotResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <DeleteDBSnapshotResult>
    <DBSnapshot>
      <Port>3306</Port>
      <OptionGroupName>default:mysql-5-6</OptionGroupName>
      <Status>deleted</Status>
      <Engine>mysql</Engine>
      <SnapshotType>manual</SnapshotType>
      <LicenseModel>general-public-license</LicenseModel>
      <DBInstanceIdentifier>mysqldb</DBInstanceIdentifier>
      <EngineVersion>5.6.13</EngineVersion>
      <DBSnapshotIdentifier>mysqldb-snap-02</DBSnapshotIdentifier>
      <SnapshotCreateTime>2014-04-23T16:11:25.371Z</SnapshotCreateTime>
      <AvailabilityZone>us-east-1a</AvailabilityZone>
      <InstanceCreateTime>2014-04-21T22:24:26.573Z</InstanceCreateTime>
      <PercentProgress>100</PercentProgress>
      <AllocatedStorage>100</AllocatedStorage>
      <MasterUsername>myawsuser</MasterUsername>
    </DBSnapshot>
  </DeleteDBSnapshotResult>
  <ResponseMetadata>
    <RequestId>7b17b2b1-ba25-11d3-a537-cef97546330c</RequestId>
  </ResponseMetadata>
</DeleteDBSnapshotResponse>
```

DeleteDBSubnetGroup

Deletes a DB subnet group.

Note

The specified database subnet group must not be associated with any DB instances.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBSubnetGroupName

The name of the database subnet group to delete.

Note

You cannot delete the default subnet group.

Constraints:

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InvalidDBSubnetGroupStateFault

The DB subnet group cannot be deleted because it is in use.

HTTP Status Code: 400

InvalidDBSubnetStateFault

The DB subnet is not in the *available* state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteDBSubnetGroup  
&DBSubnetGroupName=myawsuser-dbsubnetgroup  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
&X-Amz-Date=20140425T180721Z
```

```
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=0f461da21ec03527fdc98acba8a11c36863a399065f9b4ff891ab7cb5e70de74
```

Sample Response

```
<DeleteDBSubnetGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ResponseMetadata>  
    <RequestId>6295e5ab-bbf3-11d3-f4c6-37db295f7674</RequestId>  
  </ResponseMetadata>  
</DeleteDBSubnetGroupResponse>
```

DeleteEventSubscription

Deletes an RDS event notification subscription.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

SubscriptionName

The name of the RDS event notification subscription you want to delete.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions](#) (p. 159) action.

Type: [EventSubscription](#) (p. 327) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

InvalidEventSubscriptionState

This error can occur if someone else is modifying a subscription. You should retry the action.

HTTP Status Code: 400

SubscriptionNotFound

The subscription name does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
?Action=DeleteEventSubscription
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&SubscriptionName=EventSubscription04
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140423/us-east-1/rds/aws4_request
&X-Amz-Date=20140423T203337Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=05aa834e364a9e1a279d44cc955694518fc96fff638c74faa2be45783102e785
```

Sample Response

```
<DeleteEventSubscriptionResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <DeleteEventSubscriptionResult>
    <EventSubscription>
      <Enabled>true</Enabled>
      <CustomerAwsId>803#####</CustomerAwsId>
      <SourceType>db-instance</SourceType>
      <Status>deleting</Status>
      <SourceIdsList>
        <SourceId>mysqldb</SourceId>
      </SourceIdsList>
      <SubscriptionCreationTime>2014-04-22 23:03:19.776</SubscriptionCreationTime>
      <CustSubscriptionId>EventSubscription04</CustSubscriptionId>
      <SnsTopicArn>arn:aws:sns:us-east-1:803#####:myawsuser-RDS</SnsTopicArn>
    </EventSubscription>
  </DeleteEventSubscriptionResult>
  <ResponseMetadata>
    <RequestId>7b4cf02a-ba25-11d3-a691-857dc0addcc9</RequestId>
  </ResponseMetadata>
</DeleteEventSubscriptionResponse>
```

DeleteOptionGroup

Deletes an existing option group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

OptionGroupName

The name of the option group to be deleted.

Note

You cannot delete default option groups.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

InvalidOptionGroupStateFault

The option group is not in the *available* state.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DeleteOptionGroup  
&OptionGroupName=myawsuser-og00  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
&X-Amz-Date=20140425T181205Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=8a684aeb6d5219bb3572316a341963324d6ef339bd0dcfa5854f1a01d401214
```

Sample Response

```
<DeleteOptionGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <ResponseMetadata>  
    <RequestId>0ac9cda2-bbf4-11d3-f92b-31fa5e8dbc99</RequestId>
```

```
</ResponseMetadata>  
</DeleteOptionGroupResponse>
```


DescribeAccountAttributes

Lists all of the attributes for a customer account. The attributes include Amazon RDS quotas for the account, such as the number of DB instances allowed. The description for a quota includes the quota name, current usage toward that quota, and the quota's maximum value.

This command does not take any parameters.

Response Elements

The following element is returned by the service.

AccountQuotas.AccountQuota.N

A list of [AccountQuota](#) (p. 287) objects. Within this list, each quota has a name, a count of usage toward the quota maximum, and a maximum value for the quota.

Type: array of [AccountQuota](#) (p. 287) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
  ?Action=DescribeAccountAttributes
  &SignatureMethod=HmacSHA256
  &SignatureVersion=4
  &Version=2014-10-31
  &X-Amz-Algorithm=AWS4-HMAC-SHA256
  &X-Amz-Credential=AKIADQKE4SARGYLE/20141216/us-west-2/rds/
aws4_request
  &X-Amz-Date=20141216T192233Z
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-
sha256;x-amz-date
  &X-Amz-
Signature=b49545dd3c933bdded80655d433d84bf743261ea1bebb33a7922c5c2c5240cd8
```

Sample Response

```
<DescribeAccountAttributesResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <DescribeAccountAttributesResult>
    <AccountQuotaList>
      <AccountQuota>
        <AccountQuotaName>DBInstances</AccountQuotaName>
        <Used>22</Used>
        <Max>40</Max>
      </AccountQuota>
      <AccountQuota>
        <AccountQuotaName>ReservedDBInstances</AccountQuotaName>
        <Used>6</Used>
        <Max>40</Max>
      </AccountQuota>
    </AccountQuotaList>
  </DescribeAccountAttributesResult>
</DescribeAccountAttributesResponse>
```

Amazon Relational Database Service API Reference
Example

```
<AccountQuota>
  <AccountQuotaName>AllocatedStorage</AccountQuotaName>
  <Used>27459</Used>
  <Max>100000</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>DBSecurityGroupsPerVPC</AccountQuotaName>
  <Used>11</Used>
  <Max>25</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>AuthorizationsPerDBSecurityGroup</AccountQuotaName>
  <Used>10</Used>
  <Max>20</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>DBParameterGroups</AccountQuotaName>
  <Used>40</Used>
  <Max>50</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>ManualSnapshots</AccountQuotaName>
  <Used>32</Used>
  <Max>50</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>EventSubscriptions</AccountQuotaName>
  <Used>3</Used>
  <Max>20</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>DBSubnetGroups</AccountQuotaName>
  <Used>19</Used>
  <Max>20</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>OptionGroups</AccountQuotaName>
  <Used>14</Used>
  <Max>20</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>SubnetsPerDBSubnetGroup</AccountQuotaName>
  <Used>6</Used>
  <Max>20</Max>
</AccountQuota>
<AccountQuota>
  <AccountQuotaName>ReadReplicasPerMaster</AccountQuotaName>
  <Used>2</Used>
  <Max>5</Max>
</AccountQuota>
<AccountQuota>
  <Used>1</Used>
  <AccountQuotaName>DBClusterRoles</AccountQuotaName>
  <Max>5</Max>
</AccountQuota>
</AccountQuotaList>
</DescribeAccountAttributesResult>
<ResponseMetadata>
  <RequestId>0ce48079-68e4-11de-8c8e-eb648410240d</RequestId>
```

```
</ResponseMetadata>  
</DescribeAccountAttributesResponse>
```

DescribeCertificates

Lists the set of CA certificates provided by Amazon RDS for this AWS account.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

CertificateIdentifier

The user-supplied certificate identifier. If this parameter is specified, information for only the identified certificate is returned. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous [DescribeCertificates \(p. 104\)](#) request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

Certificates.Certificate.N

The list of [Certificate \(p. 289\)](#) objects for the AWS account.

Type: array of [Certificate \(p. 289\)](#) objects

Marker

An optional pagination token provided by a previous [DescribeCertificates \(p. 104\)](#) request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

CertificateNotFound

CertificateIdentifier does not refer to an existing certificate.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.amazonaws.com/  
?Action=DescribeCertificates  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20141121/us-west-2/rds/aws4_request  
&X-Amz-Date=20141121T164732Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=6e25c542bf96fe24b28c12976ec92d2f856abd2a158e21c35441a736e4fde2b
```

Sample Response

```
<DescribeCertificatesResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribeCertificatesResult>  
    <Certificates>  
      <Certificate>  
        <CertificateIdentifier>rdscacertificate</CertificateIdentifier>  
        <CertificateType>ca</CertificateType>  
        <ThumbPrint>xxxxxxxxxxxx</ThumbPrint>  
        <ValidFrom>2010-05-22T01:12:00.000Z</ValidFrom>  
        <ValidTill>2014-05-22T01:12:00.000Z</ValidTill>  
      </Certificate>  
    </Certificates>  
  </DescribeCertificatesResult>  
  <ResponseMetadata>  
    <RequestId>9135fff3-8509-11e0-bd9b-a7b1ece36d51</RequestId>  
  </ResponseMetadata>  
</DescribeCertificatesResponse>
```

DescribeDBClusterParameterGroups

Returns a list of `DBClusterParameterGroup` descriptions. If a `DBClusterParameterGroupName` parameter is specified, the list will contain only the description of the specified DB cluster parameter group.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterParameterGroupName

The name of a specific DB cluster parameter group to return details for.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBClusterParameterGroups` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBClusterParameterGroups.DBClusterParameterGroup.N

A list of DB cluster parameter groups.

Type: array of [DBClusterParameterGroup](#) (p. 297) objects

Marker

An optional pagination token provided by a previous `DescribeDBClusterParameterGroups` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=DescribeDBClusterParameterGroups  
  &MaxRecords=30  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20150318/us-east-1/rds/aws4_request  
  &X-Amz-Date=20150318T184307Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=d9922fdf06b86b870c072b896745251ea8b52bad64bf90e30b0e46f1bb488cca
```

Sample Response

```
<DescribeDBClusterParameterGroupsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribeDBClusterParameterGroupsResult>  
    <DBClusterParameterGroups>  
      <DBClusterParameterGroup>  
        <DBParameterGroupFamily>aurora5.6</DBParameterGroupFamily>  
        <Description>Default cluster parameter group for aurora5.6</  
Description>  
        <DBClusterParameterGroupName>default.aurora5.6</  
DBClusterParameterGroupName>  
      </DBClusterParameterGroup>  
      <DBClusterParameterGroup>  
        <DBParameterGroupFamily>aurora5.6</DBParameterGroupFamily>  
        <Description>Sample group</Description>  
        <DBClusterParameterGroupName>samplegroup</  
DBClusterParameterGroupName>  
      </DBClusterParameterGroup>  
      <DBClusterParameterGroup>  
        <DBParameterGroupFamily>aurora5.6</DBParameterGroupFamily>  
        <Description>Custom group</Description>  
        <DBClusterParameterGroupName>custom-group</  
DBClusterParameterGroupName>  
      </DBClusterParameterGroup>  
    </DBClusterParameterGroups>  
  </DescribeDBClusterParameterGroupsResult>  
</DescribeDBClusterParameterGroupsResponse>
```

```
</DescribeDBClusterParameterGroupsResult>  
<ResponseMetadata>  
  <RequestId>9e6503d0-cd9e-11e4-ccf9-7528e6a28483</RequestId>  
</ResponseMetadata>  
</DescribeDBClusterParameterGroupsResponse>
```


DescribeDBClusterParameters

Returns the detailed parameter list for a particular DB cluster parameter group.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterParameterGroupName

The name of a specific DB cluster parameter group to return parameter details for.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBClusterParameters` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Source

A value that indicates to return only parameters for a specific source. Parameter sources can be `engine`, `service`, or `customer`.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous `DescribeDBClusterParameters` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Parameters.Parameter.N

Provides a list of parameters for the DB cluster parameter group.

Type: array of [Parameter](#) (p. 342) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeDBClusterParameters  
  &DBClusterParameterGroupName=default.aurora5.6  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20151231/us-west-2/rds/aws4_request  
  &X-Amz-Date=20151231T225813Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=cf8b9ab9c4a36bbb5f5043209b1985784a226d132ed61a5c35163c40506e83f7
```

Sample Response

```
<DescribeDBClusterParametersResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribeDBClusterParametersResult>  
    <Parameters>  
      <Parameter>  
        <ApplyMethod>pending-reboot</ApplyMethod>  
        <DataType>integer</DataType>  
        <Source>engine-default</Source>  
        <IsModifiable>true</IsModifiable>  
        <Description>Intended for use with master-to-master replication, and  
can be used to control the operation of AUTO_INCREMENT columns</Description>  
        <ApplyType>dynamic</ApplyType>  
        <AllowedValues>1-65535</AllowedValues>  
        <ParameterName>auto_increment_increment</ParameterName>  
      </Parameter>  
      <Parameter>  
        <ApplyMethod>pending-reboot</ApplyMethod>  
        <DataType>integer</DataType>  
        <Source>engine-default</Source>
```

```
<IsModifiable>true</IsModifiable>
<Description>Determines the starting point for the AUTO_INCREMENT
column value</Description>
<ApplyType>dynamic</ApplyType>
<AllowedValues>1-65535</AllowedValues>
<ParameterName>auto_increment_offset</ParameterName>
</Parameter>
<Parameter>
  <ApplyMethod>pending-reboot</ApplyMethod>
  <DataType>string</DataType>
  <Source>engine-default</Source>
  <IsModifiable>true</IsModifiable>
  <Description>When enabled, this variable causes the master to write a
checksum for each event in the binary log.</Description>
  <ApplyType>dynamic</ApplyType>
  <AllowedValues>NONE,CRC32</AllowedValues>
  <ParameterName>binlog_checksum</ParameterName>
</Parameter>
<Parameter>
  <ParameterValue>OFF</ParameterValue>
  <ApplyMethod>pending-reboot</ApplyMethod>
  <DataType>string</DataType>
  <Source>system</Source>
  <IsModifiable>true</IsModifiable>
  <Description>Binary logging format for replication</Description>
  <ApplyType>dynamic</ApplyType>
  <AllowedValues>ROW,STATEMENT,MIXED,OFF</AllowedValues>
  <ParameterName>binlog_format</ParameterName>
</Parameter>
<Parameter>
  <ApplyMethod>pending-reboot</ApplyMethod>
  <DataType>string</DataType>
  <Source>engine-default</Source>
  <IsModifiable>false</IsModifiable>
  <Description>Whether the server logs full or minmal rows with row-
based replication.</Description>
  <ApplyType>dynamic</ApplyType>
  <AllowedValues>full,minimal,noblob</AllowedValues>
  <ParameterName>binlog_row_image</ParameterName>
</Parameter>
</Parameters>
</DescribeDBClusterParametersResult>
<ResponseMetadata>
  <RequestId>c4e42d91-cb92-11e5-895a-99e063757579</RequestId>
</ResponseMetadata>
</DescribeDBClusterParametersResponse>
```

DescribeDBClusters

Returns information about provisioned Aurora DB clusters. This API supports pagination. For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The user-supplied DB cluster identifier. If this parameter is specified, information from only the specific DB cluster is returned. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

Filters.Filter.N

A filter that specifies one or more DB clusters to describe.

Supported filters:

- `db-cluster-id` - Accepts DB cluster identifiers and DB cluster Amazon Resource Names (ARNs). The results list will only include information about the DB clusters identified by these ARNs.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous [DescribeDBClusters](#) (p. 112) request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBClusters.DBCluster.N

Contains a list of DB clusters for the user.

Type: array of [DBCluster](#) (p. 291) objects

Marker

A pagination token that can be used in a subsequent [DescribeDBClusters](#) request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DescribeDBClusters  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140722/us-east-1/rds/aws4_request  
&X-Amz-Date=20140722T200807Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=2d4f2b9e8abc31122b5546f94c0499bba47de813cb875f9b9c78e8e19c9afe1b
```

Sample Response

```
<DescribeDBClustersResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">  
  <DescribeDBClustersResult>  
    <DBClusters>  
      <DBCluster>  
        <AssociatedRoles>  
          <DBClusterRole>  
            <RoleArn>arn:aws:iam::123456789012:role/sample-role</RoleArn>  
            <Status>ACTIVE</Status>  
          </DBClusterRole>  
        </AssociatedRoles>  
        <Engine>aurora</Engine>  
        <Status>available</Status>  
        <BackupRetentionPeriod>0</BackupRetentionPeriod>  
        <DBSubnetGroup>my-subgroup</DBSubnetGroup>  
        <EngineVersion>5.6.10a</EngineVersion>  
        <Endpoint>sample-cluster2.cluster-cbfvmgb0y5fy.us-  
east-1.rds.amazonaws.com</Endpoint>  
        <DBClusterIdentifier>sample-cluster2</DBClusterIdentifier>  
        <PreferredBackupWindow>04:45-05:15</PreferredBackupWindow>  
        <PreferredMaintenanceWindow>sat:05:56-sat:06:26</  
PreferredMaintenanceWindow>
```

```
<DBClusterMembers/>
  <AllocatedStorage>15</AllocatedStorage>
  <MasterUsername>awsuser</MasterUsername>
</DBCluster>
<DBCluster>
  <AssociatedRoles />
  <Engine>aurora5.6</Engine>
  <Status>available</Status>
  <BackupRetentionPeriod>0</BackupRetentionPeriod>
  <DBSubnetGroup>my-subgroup</DBSubnetGroup>
  <EngineVersion>5.6.10a</EngineVersion>
  <Endpoint>sample-cluster3.cluster-cefgqfx9y5fy.us-
east-1.rds.amazonaws.com</Endpoint>
  <DBClusterIdentifier>sample-cluster3</DBClusterIdentifier>
  <PreferredBackupWindow>07:06-07:36</PreferredBackupWindow>
  <PreferredMaintenanceWindow>tue:10:18-tue:10:48</
PreferredMaintenanceWindow>
  <DBClusterMembers>
    <DBClusterMember>
      <IsClusterWriter>true</IsClusterWriter>
      <DBInstanceIdentifier>sample-cluster3-master</
DBInstanceIdentifier>
    </DBClusterMember>
    <DBClusterMember>
      <IsClusterWriter>false</IsClusterWriter>
      <DBInstanceIdentifier>sample-cluster3-read1</
DBInstanceIdentifier>
    </DBClusterMember>
  </DBClusterMembers>
  <AllocatedStorage>15</AllocatedStorage>
  <MasterUsername>awsuser</MasterUsername>
</DBCluster>
</DBClusters>
</DescribeDBClustersResult>
<ResponseMetadata>
  <RequestId>d682b02c-1383-11b4-a6bb-172dfac7f170</RequestId>
</ResponseMetadata>
</DescribeDBClustersResponse>
```

DescribeDBClusterSnapshotAttributes

Returns a list of DB cluster snapshot attribute names and values for a manual DB cluster snapshot. When sharing snapshots with other AWS accounts, `DescribeDBClusterSnapshotAttributes` returns the `restore` attribute and a list of IDs for the AWS accounts that are authorized to copy or restore the manual DB cluster snapshot. If `all` is included in the list of values for the `restore` attribute, then the manual DB cluster snapshot is public and can be copied or restored by all AWS accounts.

To add or remove access for an AWS account to copy or restore a manual DB cluster snapshot, or to make the manual DB cluster snapshot public or private, use the [ModifyDBClusterSnapshotAttribute](#) (p. 201) API action.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterSnapshotIdentifier

The identifier for the DB cluster snapshot to describe the attributes for.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBClusterSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBClusterSnapshotAttributes](#) (p. 115) API action.

Manual DB cluster snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB cluster snapshot. For more information, see the [ModifyDBClusterSnapshotAttribute](#) (p. 201) API action.

Type: [DBClusterSnapshotAttributesResult](#) (p. 302) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeDBClusterSnapshotAttributes  
&DBClusterSnapshotIdentifier>manual-cluster-snapshot1  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4
```

```
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20151027/us-east-1/rds/aws4_request
&X-Amz-Date=20151027T210706Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=27413f450dfac3d68b2197453e52109bacd3863f9df1a02d6e40022165bb2e09
```

Sample Response

```
<DescribeDBClusterSnapshotAttributesResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <DescribeDBClusterSnapshotAttributesResult>
    <DBClusterSnapshotAttributesResult>
      <DBClusterSnapshotAttributes>
        <DBClusterSnapshotAttribute>
          <AttributeName>restore</AttributeName>
          <AttributeValues>
            <AttributeValue>012345678901</AttributeValue>
          </AttributeValues>
        </DBClusterSnapshotAttribute>
      </DBClusterSnapshotAttributes>
      <DBSnapshotIdentifier>manual-cluster-snapshot1</DBSnapshotIdentifier>
    </DBClusterSnapshotAttributesResult>
  </DescribeDBClusterSnapshotAttributesResult>
  <ResponseMetadata>
    <RequestId>ae5be4a2-7cee-11e5-a056-f1c189649a47</RequestId>
  </ResponseMetadata>
</DescribeDBClusterSnapshotAttributesResponse>
```


DescribeDBClusterSnapshots

Returns information about DB cluster snapshots. This API action supports pagination.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The ID of the DB cluster to retrieve the list of DB cluster snapshots for. This parameter cannot be used in conjunction with the `DBClusterSnapshotIdentifier` parameter. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DBClusterSnapshotIdentifier

A specific DB cluster snapshot identifier to describe. This parameter cannot be used in conjunction with the `DBClusterIdentifier` parameter. This value is stored as a lowercase string.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens
- If this identifier is for an automated snapshot, the `SnapshotType` parameter must also be specified.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

IncludePublic

Set this value to `true` to include manual DB cluster snapshots that are public and can be copied or restored by any AWS account, otherwise set this value to `false`. The default is `false`. The default is `false`.

You can share a manual DB cluster snapshot as public by using the [ModifyDBClusterSnapshotAttribute](#) (p. 201) API action.

Type: Boolean

Required: No

IncludeShared

Set this value to `true` to include shared manual DB cluster snapshots from other AWS accounts that this AWS account has been given permission to copy or restore, otherwise set this value to `false`. The default is `false`.

You can give an AWS account permission to restore a manual DB cluster snapshot from another AWS account by the [ModifyDBClusterSnapshotAttribute](#) (p. 201) API action.

Type: Boolean

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBClusterSnapshots` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

SnapshotType

The type of DB cluster snapshots to be returned. You can specify one of the following values:

- `automated` - Return all DB cluster snapshots that have been automatically taken by Amazon RDS for my AWS account.
- `manual` - Return all DB cluster snapshots that have been taken by my AWS account.
- `shared` - Return all manual DB cluster snapshots that have been shared to my AWS account.
- `public` - Return all DB cluster snapshots that have been marked as public.

If you don't specify a `SnapshotType` value, then both `automated` and `manual` DB cluster snapshots are returned. You can include shared DB cluster snapshots with these results by setting the `IncludeShared` parameter to `true`. You can include public DB cluster snapshots with these results by setting the `IncludePublic` parameter to `true`.

The `IncludeShared` and `IncludePublic` parameters don't apply for `SnapshotType` values of `manual` or `automated`. The `IncludePublic` parameter doesn't apply when `SnapshotType` is set to `shared`. The `IncludeShared` parameter doesn't apply when `SnapshotType` is set to `public`.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

DBClusterSnapshots.DBClusterSnapshot.N

Provides a list of DB cluster snapshots for the user.

Type: array of [DBClusterSnapshot \(p. 299\)](#) objects

Marker

An optional pagination token provided by a previous [DescribeDBClusterSnapshots \(p. 117\)](#) request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterSnapshotNotFoundFault

`DBClusterSnapshotIdentifier` does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=DescribeDBClusterSnapshots  
  &IncludePublic=false  
  &IncludeShared=true  
  &MaxRecords=40  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20150318/us-east-1/rds/aws4_request  
  &X-Amz-Date=20150318T204210Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=913f0ec1dfc684ff9c6ef3eab5885258dbb22017c47b1bcd4fed4680e35aef4b
```

Sample Response

```
<DescribeDBClusterSnapshotsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribeDBClusterSnapshotsResult>  
    <DBClusterSnapshots>  
      <DBClusterSnapshot>  
        <Port>0</Port>  
        <Status>available</Status>  
        <Engine>aurora</Engine>  
        <SnapshotType>>manual</SnapshotType>  
        <LicenseModel>aurora</LicenseModel>  
        <DBClusterSnapshotIdentifier>sample-cluster-snapshot1</  
DBClusterSnapshotIdentifier>  
        <SnapshotCreateTime>2015-03-12T17:42:48.271Z</SnapshotCreateTime>  
        <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>  
        <VpcId>vpc-3fabee54</VpcId>  
        <ClusterCreateTime>2015-03-06T22:11:13.826Z</ClusterCreateTime>  
        <PercentProgress>100</PercentProgress>  
        <AllocatedStorage>1</AllocatedStorage>  
        <MasterUsername>awsuser</MasterUsername>  
      </DBClusterSnapshot>  
      <DBClusterSnapshot>  
        <Port>0</Port>  
        <Status>creating</Status>  
        <Engine>aurora</Engine>  
        <SnapshotType>automated</SnapshotType>  
        <LicenseModel>aurora</LicenseModel>  
        <DBClusterSnapshotIdentifier>rds:sample2-cluster-2014-10-22-03-12</  
DBClusterSnapshotIdentifier>  
        <SnapshotCreateTime>2014-10-22T03:12:09.445Z</SnapshotCreateTime>  
        <DBClusterIdentifier>sample2-cluster</DBClusterIdentifier>  
        <VpcId>vpc-3fabee54</VpcId>
```

```
<ClusterCreateTime>2014-10-16T18:44:13.633Z</ClusterCreateTime>
<PercentProgress>0</PercentProgress>
<AllocatedStorage>1</AllocatedStorage>
<MasterUsername>awsuser</MasterUsername>
</DBClusterSnapshot>
<DBClusterSnapshot>
  <Port>0</Port>
  <Status>creating</Status>
  <Engine>aurora</Engine>
  <SnapshotType>automated</SnapshotType>
  <LicenseModel>aurora</LicenseModel>
  <DBClusterSnapshotIdentifier>rds:sample-cluster-2014-10-22-08-27</
DBClusterSnapshotIdentifier>
  <SnapshotCreateTime>2014-10-22T08:27:08.435Z</SnapshotCreateTime>
  <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>
  <VpcId>vpc-3fabee54</VpcId>
  <ClusterCreateTime>2014-10-16T20:11:04.016Z</ClusterCreateTime>
  <PercentProgress>0</PercentProgress>
  <AllocatedStorage>1</AllocatedStorage>
  <MasterUsername>awsuser</MasterUsername>
</DBClusterSnapshot>
</DBClusterSnapshots>
</DescribeDBClusterSnapshotsResult>
<ResponseMetadata>
  <RequestId>3ff63be1-ceef-11e4-840b-459216ffcb55</RequestId>
</ResponseMetadata>
</DescribeDBClusterSnapshotsResponse>
```

DescribeDBEngineVersions

Returns a list of the available DB engines.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupFamily

The name of a specific DB parameter group family to return details for.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DefaultOnly

Indicates that only the default version of the specified engine or engine and major version combination is returned.

Type: Boolean

Required: No

Engine

The database engine to return.

Type: String

Required: No

EngineVersion

The database engine version to return.

Example: 5.1.49

Type: String

Required: No

Filters.Filter.N

Not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

ListSupportedCharacterSets

If this parameter is specified and the requested engine supports the `CharacterSetName` parameter for `CreateDBInstance`, the response includes a list of supported character sets for each engine version.

Type: Boolean

Required: No

ListSupportedTimezones

If this parameter is specified and the requested engine supports the `TimeZone` parameter for `CreateDBInstance`, the response includes a list of supported time zones for each engine version.

Type: Boolean

Required: No

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more than the `MaxRecords` value is available, a pagination token called a marker is included in the response so that the following results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBEngineVersions.DBEngineVersion.N

A list of `DBEngineVersion` elements.

Type: array of [DBEngineVersion](#) (p. 303) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=DescribeDBEngineVersions
&MaxRecords=100
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request
&X-Amz-Date=20140421T194732Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=4772d17a4c43bcd209ff42a0778dd23e73f8434253effd7ac53b89ade3dad45f
```

Sample Response

```
<DescribeDBEngineVersionsResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <DescribeDBEngineVersionsResult>
    <DBEngineVersions>
```

```
<DBEngineVersion>
  <Engine>mysql</Engine>
  <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>
  <DBEngineDescription>MySQL Community Edition</DBEngineDescription>
  <EngineVersion>5.1.57</EngineVersion>
  <DBEngineVersionDescription>MySQL 5.1.57</DBEngineVersionDescription>
</DBEngineVersion>
<DBEngineVersion>
  <Engine>mysql</Engine>
  <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>
  <DBEngineDescription>MySQL Community Edition</DBEngineDescription>
  <EngineVersion>5.1.61</EngineVersion>
  <DBEngineVersionDescription>MySQL 5.1.61</DBEngineVersionDescription>
</DBEngineVersion>
<DBEngineVersion>
  <Engine>mysql</Engine>
  <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>
  <DBEngineDescription>MySQL Community Edition</DBEngineDescription>
  <EngineVersion>5.1.62</EngineVersion>
  <DBEngineVersionDescription>MySQL 5.1.62</DBEngineVersionDescription>
</DBEngineVersion>
</DescribeDBEngineVersionsResult>
<ResponseMetadata>
  <RequestId>b74d2635-b98c-11d3-fbc7-5c0aad74da7c</RequestId>
</ResponseMetadata>
</DescribeDBEngineVersionsResponse>
```

DescribeDBInstances

Returns information about provisioned RDS instances. This API supports pagination.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceIdentifier

The user-supplied instance identifier. If this parameter is specified, information from only the specific DB instance is returned. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

Filters.Filter.N

A filter that specifies one or more DB instances to describe.

Supported filters:

- `db-instance-id` - Accepts DB instance identifiers and DB instance Amazon Resource Names (ARNs). The results list will only include information about the DB instances identified by these ARNs.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBInstances` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBInstances.DBInstance.N

A list of [DBInstance](#) (p. 304) instances.

Type: array of [DBInstance](#) (p. 304) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
  ?Action=DescribeDBInstances
  &MaxRecords=100
  &SignatureMethod=HmacSHA256
  &SignatureVersion=4
  &Version=2014-09-01
  &X-Amz-Algorithm=AWS4-HMAC-SHA256
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140420/us-west-2/rds/aws4_request
  &X-Amz-Date=20140420T171917Z
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
  &X-Amz-
Signature=caa44629fa60576c2c282d9b74d47647f9e9f229f6d0e52db1d3be0d095743b0
```

Sample Response

```
<DescribeDBInstancesResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <DescribeDBInstancesResult>
    <DBInstances>
      <DBInstance>
        <BackupRetentionPeriod>7</BackupRetentionPeriod>
        <MultiAZ>>false</MultiAZ>
        <DBInstanceStatus>available</DBInstanceStatus>
        <VpcSecurityGroups/>
        <DBInstanceIdentifier>mysqlsampledb</DBInstanceIdentifier>
        <PreferredBackupWindow>10:07-10:37</PreferredBackupWindow>
        <PreferredMaintenanceWindow>sun:06:13-sun:06:43</
PreferredMaintenanceWindow>
        <AvailabilityZone>us-west-2b</AvailabilityZone>
        <LatestRestorableTime>2014-04-21T17:15:00Z</LatestRestorableTime>
        <ReadReplicaDBInstanceIdentifiers/>
        <Engine>mysql</Engine>
        <PendingModifiedValues/>
        <LicenseModel>general-public-license</LicenseModel>
        <DBParameterGroups>
          <DBParameterGroup>
            <ParameterApplyStatus>in-sync</ParameterApplyStatus>
            <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
          </DBParameterGroup>
        </DBParameterGroups>
      </DBInstance>
    </DBInstances>
  </DescribeDBInstancesResult>
</DescribeDBInstancesResponse>
```

```

    <Endpoint>
      <Port>3306</Port>
      <Address>mysqlxampledb.c6c1rntzufv0.us-west-2.rds.amazonaws.com</
Address>
    </Endpoint>
    <EngineVersion>5.6.13</EngineVersion>
    <OptionGroupMemberships>
      <OptionGroupMembership>
        <OptionGroupName>default:mysql-5-6</OptionGroupName>
        <Status>in-sync</Status>
      </OptionGroupMembership>
    </OptionGroupMemberships>
    <DBSecurityGroups>
      <DBSecurityGroup>
        <Status>active</Status>
        <DBSecurityGroupName>my-db-secgroup</DBSecurityGroupName>
      </DBSecurityGroup>
    </DBSecurityGroups>
    <PubliclyAccessible>true</PubliclyAccessible>
    <DBName>mysampled</DBName>
    <AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
    <InstanceCreateTime>2014-01-29T22:58:24.231Z</InstanceCreateTime>
    <AllocatedStorage>5</AllocatedStorage>
    <MasterUsername>myawsuser</MasterUsername>
    <DBInstanceClass>db.t1.micro</DBInstanceClass>
  </DBInstance>
  <DBInstance>
    <BackupRetentionPeriod>7</BackupRetentionPeriod>
    <MultiAZ>>false</MultiAZ>
    <DBInstanceStatus>available</DBInstanceStatus>
    <VpcSecurityGroups/>
    <DBInstanceIdentifier>mysqlxampledb-restore</DBInstanceIdentifier>
    <PreferredBackupWindow>10:07-10:37</PreferredBackupWindow>
    <PreferredMaintenanceWindow>sun:06:13-sun:06:43</
PreferredMaintenanceWindow>
    <AvailabilityZone>us-west-2b</AvailabilityZone>
    <LatestRestorableTime>2014-04-21T17:15:00Z</LatestRestorableTime>
    <ReadReplicaDBInstanceIdentifiers/>
    <Engine>mysql</Engine>
    <PendingModifiedValues/>
    <LicenseModel>general-public-license</LicenseModel>
    <DBParameterGroups>
      <DBParameterGroup>
        <ParameterApplyStatus>in-sync</ParameterApplyStatus>
        <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
      </DBParameterGroup>
    </DBParameterGroups>
    <Endpoint>
      <Port>3306</Port>
      <Address>mysqlxampledb-restore.c6c2mntzugv0.us-
west-2.rds.amazonaws.com</Address>
    </Endpoint>
    <EngineVersion>5.6.13</EngineVersion>
    <OptionGroupMemberships>
      <OptionGroupMembership>
        <OptionGroupName>default:mysql-5-6</OptionGroupName>
        <Status>in-sync</Status>
      </OptionGroupMembership>
    </OptionGroupMemberships>

```

```
<DBSecurityGroups>
  <DBSecurityGroup>
    <Status>active</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
<PubliclyAccessible>true</PubliclyAccessible>
<DBName>mysampled</DBName>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<InstanceCreateTime>2014-03-28T20:14:17.296Z</InstanceCreateTime>
<AllocatedStorage>5</AllocatedStorage>
<MasterUsername>myawsuser</MasterUsername>
<DBInstanceClass>db.t1.micro</DBInstanceClass>
</DBInstance>
</DBInstances>
</DescribeDBInstancesResult>
<ResponseMetadata>
  <RequestId>01b2685a-b978-11d3-f272-7cd6cce12cc5</RequestId>
</ResponseMetadata>
</DescribeDBInstancesResponse>
```

DescribeDBLogFiles

Returns a list of DB log files for the DB instance.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceIdentifier

The customer-assigned name of the DB instance that contains the log files you want to list.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

FileLastWritten

Filters the available log files for files written since the specified date, in POSIX timestamp format with milliseconds.

Type: Long

Required: No

FilenameContains

Filters the available log files for log file names that contain the specified string.

Type: String

Required: No

FileSize

Filters the available log files for files larger than the specified size.

Type: Long

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

The pagination token provided in the previous request. If this parameter is specified the response includes only records beyond the marker, up to MaxRecords.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified MaxRecords value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DescribeDBLogFiles.DescribeDBLogFilesDetails.N

The DB log files returned.

Type: array of [DescribeDBLogFilesDetails](#) (p. 320) objects

Marker

A pagination token that can be used in a subsequent DescribeDBLogFiles request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=DescribeDBLogFiles  
  &DBInstanceIdentifier=mysqladb  
  &MaxRecords=100  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140421T225750Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=9020fd1bcd658614e058cd2eb8c58572cf6c11460b1e96380635ee428a52e8a1
```

Sample Response

```
<DescribeDBLogFilesResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <DescribeDBLogFilesResult>  
    <DescribeDBLogFiles>  
      <DescribeDBLogFilesDetails>  
        <LastWritten>1398119101000</LastWritten>  
        <LogFileName>error/mysql-error-running.log</LogFileName>  
        <Size>1599</Size>  
      </DescribeDBLogFilesDetails>  
      <DescribeDBLogFilesDetails>  
        <LastWritten>1398120900000</LastWritten>  
        <LogFileName>error/mysql-error.log</LogFileName>  
        <Size>0</Size>  
      </DescribeDBLogFilesDetails>  
    </DescribeDBLogFiles>  
  </DescribeDBLogFilesResult>  
  <ResponseMetadata>  
    <RequestId>4c6ed648-b9f7-11d3-97bd-7999dd5a8f72</RequestId>
```

```
</ResponseMetadata>  
</DescribeDBLogFilesResponse>
```

DescribeDBParameterGroups

Returns a list of `DBParameterGroup` descriptions. If a `DBParameterGroupName` is specified, the list will contain only the description of the specified DB parameter group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupName

The name of a specific DB parameter group to return details for.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBParameterGroups` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBParameterGroups.DBParameterGroup.N

A list of [DBParameterGroup](#) (p. 310) instances.

Type: array of [DBParameterGroup](#) (p. 310) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=DescribeDBParameterGroups
&DBInstanceIdentifier=db1-mysql
&MaxRecords=100
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request
&X-Amz-Date=20140421T194732Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=e2753df1cb019f212057b51e8a2ac16dae05b344063355b195b560ef6e76661a
```

Sample Response

```
<DescribeDBParameterGroupsResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <DescribeDBParameterGroupsResult>
    <DBParameterGroups>
      <DBParameterGroup>
        <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>
        <Description>Default parameter group for mysql5.1</Description>
        <DBParameterGroupName>default.mysql5.1</DBParameterGroupName>
      </DBParameterGroup>
      <DBParameterGroup>
        <DBParameterGroupFamily>mysql5.5</DBParameterGroupFamily>
        <Description>Default parameter group for mysql5.5</Description>
        <DBParameterGroupName>default.mysql5.5</DBParameterGroupName>
      </DBParameterGroup>
      <DBParameterGroup>
        <DBParameterGroupFamily>mysql5.6</DBParameterGroupFamily>
        <Description>Default parameter group for mysql5.6</Description>
        <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
      </DBParameterGroup>
    </DBParameterGroups>
  </DescribeDBParameterGroupsResult>
  <ResponseMetadata>
    <RequestId>b75d527a-b98c-11d3-f272-7cd6ccea12cc5</RequestId>
  </ResponseMetadata>
</DescribeDBParameterGroupsResponse>
```


DescribeDBParameters

Returns the detailed parameter list for a particular DB parameter group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupName

The name of a specific DB parameter group to return details for.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBParameters` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Source

The parameter types to return.

Default: All parameter types returned

Valid Values: `user` | `system` | `engine-default`

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Parameters.Parameter.N

A list of [Parameter](#) (p. 342) values.

Type: array of [Parameter](#) (p. 342) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DescribeDBParameters  
&DBParameterGroupName=oracle-logs  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-east-1/rds/aws4_request  
&X-Amz-Date=20140421T231357Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=ac9b18d6ae7cab4bf45ed2caa99cd8438101b293c0a84e80c3bab77f7369cc7
```

Sample Response

```
<DescribeDBParametersResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeDBParametersResult>  
    <Marker>bGlzdGVuZXJfbmV0d29ya3M=</Marker>  
    <Parameters>  
      <Parameter>  
        <DataType>integer</DataType>  
        <Source>engine-default</Source>  
        <IsModifiable>true</IsModifiable>  
        <Description>number of AQ Time Managers to start</Description>  
        <ApplyType>dynamic</ApplyType>  
        <AllowedValues>0-40</AllowedValues>  
        <ParameterName>aq_tm_processes</ParameterName>  
      </Parameter>  
      <Parameter>  
        <ParameterValue>300</ParameterValue>  
        <DataType>integer</DataType>  
        <Source>system</Source>  
        <IsModifiable>false</IsModifiable>  
        <Description>Maximum number of seconds of redos the standby could  
lose</Description>
```

```
<ApplyType>dynamic</ApplyType>
  <ParameterName>archive_lag_target</ParameterName>
</Parameter>
<Parameter>
  <ParameterValue>/rdsdbdata/admin/{dbName}/adump</ParameterValue>
  <DataType>string</DataType>
  <Source>system</Source>
  <IsModifiable>>false</IsModifiable>
  <Description>Directory in which auditing files are to reside</
Description>
  <ApplyType>dynamic</ApplyType>
  <ParameterName>audit_file_dest</ParameterName>
</Parameter>
<Parameter>
  <DataType>boolean</DataType>
  <Source>engine-default</Source>
  <IsModifiable>>false</IsModifiable>
  <Description>enable sys auditing</Description>
  <ApplyType>static</ApplyType>
  <AllowedValues>TRUE,FALSE</AllowedValues>
  <ParameterName>audit_sys_operations</ParameterName>
</Parameter>
<Parameter>
  <DataType>string</DataType>
  <Source>engine-default</Source>
  <IsModifiable>>false</IsModifiable>
  <Description>Syslog facility and level</Description>
  <ApplyType>static</ApplyType>
  <ParameterName>audit_syslog_level</ParameterName>
</Parameter>
<Parameter>
  <DataType>string</DataType>
  <Source>engine-default</Source>
  <IsModifiable>>true</IsModifiable>
  <Description>enable system auditing</Description>
  <ApplyType>static</ApplyType>
  <AllowedValues>DB,OS,NONE,TRUE,FALSE,DB_EXTENDED,XML</AllowedValues>
  <ParameterName>audit_trail</ParameterName>
</Parameter>
</Parameters>
</DescribeDBParametersResult>
<ResponseMetadata>
  <RequestId>8c40488f-b9ff-11d3-a15e-7ac49293f4fa</RequestId>
</ResponseMetadata>
</DescribeDBParametersResponse>
```

DescribeDBSecurityGroups

Returns a list of `DBSecurityGroup` descriptions. If a `DBSecurityGroupName` is specified, the list will contain only the descriptions of the specified DB security group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBSecurityGroupName

The name of the DB security group to return details for.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBSecurityGroups` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBSecurityGroups.DBSecurityGroup.N

A list of [DBSecurityGroup](#) (p. 312) instances.

Type: array of [DBSecurityGroup](#) (p. 312) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSecurityGroupNotFound

`DBSecurityGroupName` does not refer to an existing DB security group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeDBSecurityGroups  
  &MaxRecords=100  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194732Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=b14bcdedcf2fd7ffbbcc45ed2caa99cd848ee309a19070f946ad2a54f5331fe
```

Sample Response

```
<DescribeDBSecurityGroupsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeDBSecurityGroupsResult>  
    <DBSecurityGroups>  
      <DBSecurityGroup>  
        <EC2SecurityGroups/>  
        <DBSecurityGroupDescription>My security group</  
DBSecurityGroupDescription>  
        <IPRanges>  
          <IPRange>  
            <CIDRIP>192.0.0.0/24</CIDRIP>  
            <Status>authorized</Status>  
          </IPRange>  
          <IPRange>  
            <CIDRIP>190.0.1.0/29</CIDRIP>  
            <Status>authorized</Status>  
          </IPRange>  
          <IPRange>  
            <CIDRIP>190.0.2.0/29</CIDRIP>  
            <Status>authorized</Status>  
          </IPRange>  
          <IPRange>  
            <CIDRIP>10.0.0.0/8</CIDRIP>  
            <Status>authorized</Status>  
          </IPRange>  
        </IPRanges>  
        <OwnerId>803#####</OwnerId>  
        <DBSecurityGroupName>my-secgrp</DBSecurityGroupName>  
      </DBSecurityGroup>  
      <DBSecurityGroup>  
        <EC2SecurityGroups/>  
        <DBSecurityGroupDescription>default</DBSecurityGroupDescription>  
        <IPRanges/>  
        <OwnerId>803#####</OwnerId>
```

```
<DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
</DescribeDBSecurityGroupsResult>
<ResponseMetadata>
  <RequestId>b76e692c-b98c-11d3-a907-5a2c468b9cb0</RequestId>
</ResponseMetadata>
</DescribeDBSecurityGroupsResponse>
```

DescribeDBSnapshotAttributes

Returns a list of DB snapshot attribute names and values for a manual DB snapshot.

When sharing snapshots with other AWS accounts, `DescribeDBSnapshotAttributes` returns the `restore` attribute and a list of IDs for the AWS accounts that are authorized to copy or restore the manual DB snapshot. If `all` is included in the list of values for the `restore` attribute, then the manual DB snapshot is public and can be copied or restored by all AWS accounts.

To add or remove access for an AWS account to copy or restore a manual DB snapshot, or to make the manual DB snapshot public or private, use the [ModifyDBSnapshotAttribute \(p. 217\)](#) API action.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBSnapshotIdentifier

The identifier for the DB snapshot to describe the attributes for.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBSnapshotAttributes \(p. 139\)](#) API action.

Manual DB snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB snapshot. For more information, see the [ModifyDBSnapshotAttribute \(p. 217\)](#) API action.

Type: [DBSnapshotAttributesResult \(p. 318\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeDBSnapshotAttributes  
&DBSnapshotIdentifier=manual-snapshot1  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256
```

```
&X-Amz-Credential=AKIADQKE4SARGYLE/20151027/us-east-1/rds/aws4_request
&X-Amz-Date=20151027T210706Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=27413f450dfac3d68b2197453e52109bacd3863f9df1a02d6e40022165bb2e09
```

Sample Response

```
<DescribeDBSnapshotAttributesResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <DescribeDBSnapshotAttributesResult>
    <DBSnapshotAttributesResult>
      <DBSnapshotAttributes>
        <DBSnapshotAttribute>
          <AttributeName>restore</AttributeName>
          <AttributeValues>
            <AttributeValue>012345678901</AttributeValue>
          </AttributeValues>
        </DBSnapshotAttribute>
      </DBSnapshotAttributes>
      <DBSnapshotIdentifier>manual-snapshot1</DBSnapshotIdentifier>
    </DescribeDBSnapshotAttributesResult>
  </DescribeDBSnapshotAttributesResponse>
  <ResponseMetadata>
    <RequestId>ae5be4a2-7cee-11e5-a056-f1c189649a47</RequestId>
  </ResponseMetadata>
</DescribeDBSnapshotAttributesResponse>
```


DescribeDBSnapshots

Returns information about DB snapshots. This API action supports pagination.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceIdentifier

The ID of the DB instance to retrieve the list of DB snapshots for. This parameter cannot be used in conjunction with `DBSnapshotIdentifier`. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DBSnapshotIdentifier

A specific DB snapshot identifier to describe. This parameter cannot be used in conjunction with `DBInstanceIdentifier`. This value is stored as a lowercase string.

Constraints:

- Must be 1 to 255 alphanumeric characters.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.
- If this identifier is for an automated snapshot, the `SnapshotType` parameter must also be specified.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

IncludePublic

Set this value to `true` to include manual DB snapshots that are public and can be copied or restored by any AWS account, otherwise set this value to `false`. The default is `false`.

You can share a manual DB snapshot as public by using the [ModifyDBSnapshotAttribute](#) (p. 217) API.

Type: Boolean

Required: No

IncludeShared

Set this value to `true` to include shared manual DB snapshots from other AWS accounts that this AWS account has been given permission to copy or restore, otherwise set this value to `false`. The default is `false`.

You can give an AWS account permission to restore a manual DB snapshot from another AWS account by using the [ModifyDBSnapshotAttribute](#) (p. 217) API action.

Type: Boolean

Required: No

Marker

An optional pagination token provided by a previous `DescribeDBSnapshots` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String
Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

SnapshotType

The type of snapshots to be returned. You can specify one of the following values:

- `automated` - Return all DB snapshots that have been automatically taken by Amazon RDS for my AWS account.
- `manual` - Return all DB snapshots that have been taken by my AWS account.
- `shared` - Return all manual DB snapshots that have been shared to my AWS account.
- `public` - Return all DB snapshots that have been marked as public.

If you don't specify a `SnapshotType` value, then both `automated` and `manual` snapshots are returned. Shared and public DB snapshots are not included in the returned results by default. You can include shared snapshots with these results by setting the `IncludeShared` parameter to `true`. You can include public snapshots with these results by setting the `IncludePublic` parameter to `true`.

The `IncludeShared` and `IncludePublic` parameters don't apply for `SnapshotType` values of `manual` or `automated`. The `IncludePublic` parameter doesn't apply when `SnapshotType` is set to `shared`. The `IncludeShared` parameter doesn't apply when `SnapshotType` is set to `public`.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

DBSnapshots.DBSnapshot.N

A list of [DBSnapshot \(p. 314\)](#) instances.

Type: array of [DBSnapshot \(p. 314\)](#) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSnapshotNotFound

`DBSnapshotIdentifier` does not refer to an existing DB snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeDBSnapshots  
  &IncludePublic=false  
  &IncludeShared=true  
  &MaxRecords=100  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194732Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=4aa31bdcf7b5e0dadffbd6dc8448a31871e283ffe270e77890e15487354bcc
```

Sample Response

```
<DescribeDBSnapshotsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeDBSnapshotsResult>  
    <DBSnapshots>  
      <DBSnapshot>  
        <Port>3306</Port>  
        <OptionGroupName>default:mysql-5-6</OptionGroupName>  
        <Engine>mysql</Engine>  
        <Status>available</Status>  
        <SnapshotType>manual</SnapshotType>  
        <LicenseModel>general-public-license</LicenseModel>  
        <EngineVersion>5.6.13</EngineVersion>  
        <DBInstanceIdentifier>my-mysqlexampledb</DBInstanceIdentifier>  
        <DBSnapshotIdentifier>my-test-restore-snapshot</DBSnapshotIdentifier>  
        <SnapshotCreateTime>2014-03-28T19:57:16.707Z</SnapshotCreateTime>  
        <AvailabilityZone>us-west-2b</AvailabilityZone>  
        <InstanceCreateTime>2014-01-29T22:58:24.231Z</InstanceCreateTime>  
        <PercentProgress>100</PercentProgress>  
        <AllocatedStorage>5</AllocatedStorage>  
        <MasterUsername>awsmyuser</MasterUsername>  
      </DBSnapshot>  
      <DBSnapshot>  
        <Port>3306</Port>  
        <OptionGroupName>default:mysql-5-6</OptionGroupName>  
        <Engine>mysql</Engine>  
        <Status>available</Status>  
        <SnapshotType>automated</SnapshotType>  
        <LicenseModel>general-public-license</LicenseModel>  
        <EngineVersion>5.6.13</EngineVersion>  
        <DBInstanceIdentifier>my-mysqlexampledb</DBInstanceIdentifier>  
        <DBSnapshotIdentifier>rds:my-mysqlexampledb-2014-04-19-10-08</  
DBSnapshotIdentifier>
```

Amazon Relational Database Service API Reference
Example

```
<SnapshotCreateTime>2014-04-19T10:09:09.790Z</SnapshotCreateTime>
<AvailabilityZone>us-west-2b</AvailabilityZone>
<InstanceCreateTime>2014-01-29T22:58:24.231Z</InstanceCreateTime>
<PercentProgress>100</PercentProgress>
<AllocatedStorage>5</AllocatedStorage>
<MasterUsername>awsmyuser</MasterUsername>
</DBSnapshot>
<DBSnapshot>
  <Port>3306</Port>
  <OptionGroupName>default:mysql-5-6</OptionGroupName>
  <Engine>mysql</Engine>
  <Status>available</Status>
  <SnapshotType>automated</SnapshotType>
  <LicenseModel>general-public-license</LicenseModel>
  <EngineVersion>5.6.13</EngineVersion>
  <DBInstanceIdentifier>my-mysqlexampledb</DBInstanceIdentifier>
  <DBSnapshotIdentifier>rds:my-mysqlexampledb-2014-04-20-10-09</
DBSnapshotIdentifier>
  <SnapshotCreateTime>2014-04-20T10:09:15.446Z</SnapshotCreateTime>
  <AvailabilityZone>us-west-2b</AvailabilityZone>
  <InstanceCreateTime>2014-01-29T22:58:24.231Z</InstanceCreateTime>
  <PercentProgress>100</PercentProgress>
  <AllocatedStorage>5</AllocatedStorage>
  <MasterUsername>awsmyuser</MasterUsername>
</DBSnapshot>
</DBSnapshots>
</DescribeDBSnapshotsResult>
<ResponseMetadata>
  <RequestId>b7769930-b98c-11d3-f272-7cd6cce12cc5</RequestId>
</ResponseMetadata>
</DescribeDBSnapshotsResponse>
```

DescribeDBSubnetGroups

Returns a list of DBSubnetGroup descriptions. If a DBSubnetGroupName is specified, the list will contain only the descriptions of the specified DBSubnetGroup.

For an overview of CIDR ranges, go to the [Wikipedia Tutorial](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBSubnetGroupName

The name of the DB subnet group to return details for.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous DescribeDBSubnetGroups request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

DBSubnetGroups.DBSubnetGroup.N

A list of [DBSubnetGroup \(p. 319\)](#) instances.

Type: array of [DBSubnetGroup \(p. 319\)](#) objects

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeDBSubnetGroups  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
&X-Amz-Date=20140421T194732Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=6cc9b2825866148e1d6290b8aa2e9d75b1884b116d8665759942d87ebfbed426
```

Sample Response

```
<DescribeDBSubnetGroupsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeDBSubnetGroupsResult>  
    <DBSubnetGroups>  
      <DBSubnetGroup>  
        <VpcId>vpc-e7abbdce</VpcId>  
        <SubnetGroupStatus>Complete</SubnetGroupStatus>  
        <DBSubnetGroupDescription>DB subnet group 1</  
DBSubnetGroupDescription>  
        <DBSubnetGroupName>mydbsubnetgroup1</DBSubnetGroupName>  
        <Subnets>  
          <Subnet>  
            <SubnetStatus>Active</SubnetStatus>  
            <SubnetIdentifier>subnet-e8b3e5b1</SubnetIdentifier>  
            <SubnetAvailabilityZone>  
              <Name>us-west-2a</Name>  
              <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>  
            </SubnetAvailabilityZone>  
          </Subnet>  
          <Subnet>  
            <SubnetStatus>Active</SubnetStatus>  
            <SubnetIdentifier>subnet-44b2f22e</SubnetIdentifier>  
            <SubnetAvailabilityZone>  
              <Name>us-west-2b</Name>  
              <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>  
            </SubnetAvailabilityZone>  
          </Subnet>  
        </Subnets>  
      </DBSubnetGroup>  
      <DBSubnetGroup>  
        <VpcId>vpc-c1e17bb8</VpcId>
```

```
<SubnetGroupStatus>Complete</SubnetGroupStatus>
<DBSubnetGroupDescription>My DB Subnet Group 2</
DBSubnetGroupDescription>
<DBSubnetGroupName>sub-grp-2</DBSubnetGroupName>
<Subnets>
  <Subnet>
    <SubnetStatus>Active</SubnetStatus>
    <SubnetIdentifier>subnet-d281ef8a</SubnetIdentifier>
    <SubnetAvailabilityZone>
      <Name>us-west-2a</Name>
      <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
    </SubnetAvailabilityZone>
  </Subnet>
  <Subnet>
    <SubnetStatus>Active</SubnetStatus>
    <SubnetIdentifier>subnet-b381ef9f</SubnetIdentifier>
    <SubnetAvailabilityZone>
      <Name>us-west-2c</Name>
      <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
    </SubnetAvailabilityZone>
  </Subnet>
  <Subnet>
    <SubnetStatus>Active</SubnetStatus>
    <SubnetIdentifier>subnet-e1e17ebd</SubnetIdentifier>
    <SubnetAvailabilityZone>
      <Name>us-west-2b</Name>
      <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
    </SubnetAvailabilityZone>
  </Subnet>
</Subnets>
</DBSubnetGroup>
</DBSubnetGroups>
</DescribeDBSubnetGroupsResult>
<ResponseMetadata>
  <RequestId>b783db3b-b98c-11d3-fbc7-5c0aad74da7c</RequestId>
</ResponseMetadata>
</DescribeDBSubnetGroupsResponse>
```

DescribeEngineDefaultClusterParameters

Returns the default engine and system parameter information for the cluster database engine. For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupFamily

The name of the DB cluster parameter group family to return engine parameter information for.

Type: String

Required: Yes

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeEngineDefaultClusterParameters` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following element is returned by the service.

EngineDefaults

Contains the result of a successful invocation of the [DescribeEngineDefaultParameters](#) (p. 150) action.

Type: [EngineDefaults](#) (p. 324) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

Sample Response

DescribeEngineDefaultParameters

Returns the default engine and system parameter information for the specified database engine.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupFamily

The name of the DB parameter group family.

Type: String

Required: Yes

Filters.Filter.N

Not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribeEngineDefaultParameters` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following element is returned by the service.

EngineDefaults

Contains the result of a successful invocation of the [DescribeEngineDefaultParameters](#) (p. 150) action.

Type: [EngineDefaults](#) (p. 324) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
```

```
?Action=DescribeEngineDefaultParameters
&DBParameterGroupFamily=mysql5.1
&MaxRecords=100
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request
&X-Amz-Date=20140421T194732Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=747cc243a8a2385b0b06a9e2d145d08b905a39620b2782edd8382ea1712cf826
```

Sample Response

```
<DescribeEngineDefaultParametersResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/">
  <DescribeEngineDefaultParametersResult>
    <EngineDefaults>
      <DBParameterGroupFamily>mysql5.1</DBParameterGroupFamily>
      <Marker>bG9nX3FZXJpZ4Nfbm90X3VzaW5nX2luZGV4Z1M=</Marker>
      <Parameters>
        <Parameter>
          <DataType>boolean</DataType>
          <Source>engine-default</Source>
          <IsModifiable>>false</IsModifiable>
          <Description>Controls whether user-defined functions that have only
an xxx symbol for the main function can be loaded</Description>
          <ApplyType>static</ApplyType>
          <AllowedValues>0,1</AllowedValues>
          <ParameterName>allow-suspicious-udfs</ParameterName>
        </Parameter>
        <Parameter>
          <DataType>integer</DataType>
          <Source>engine-default</Source>
          <IsModifiable>>true</IsModifiable>
          <Description>Intended for use with master-to-master replication,
and can be used to control the operation of AUTO_INCREMENT columns</
Description>
          <ApplyType>dynamic</ApplyType>
          <AllowedValues>1-65535</AllowedValues>
          <ParameterName>auto_increment_increment</ParameterName>
        </Parameter>
        <Parameter>
          <DataType>integer</DataType>
          <Source>engine-default</Source>
          <IsModifiable>>true</IsModifiable>
          <Description>Determines the starting point for the AUTO_INCREMENT
column value</Description>
          <ApplyType>dynamic</ApplyType>
          <AllowedValues>1-65535</AllowedValues>
          <ParameterName>auto_increment_offset</ParameterName>
        </Parameter>
      </Parameters>
    </EngineDefaults>
  </DescribeEngineDefaultParametersResult>
```

```
<ResponseMetadata>  
  <RequestId>b789ce01-b98c-11d3-a907-5a2c468b9cb0</RequestId>  
</ResponseMetadata>  
</DescribeEngineDefaultParametersResponse>
```

DescribeEventCategories

Displays a list of categories for all event source types, or, if specified, for a specified source type. You can see a list of the event categories and source types in the [Events](#) topic in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

SourceType

The type of source that will be generating the events.

Valid values: db-instance | db-parameter-group | db-security-group | db-snapshot

Type: String

Required: No

Response Elements

The following element is returned by the service.

EventCategoriesMapList.EventCategoriesMap.N

A list of EventCategoriesMap data types.

Type: array of [EventCategoriesMap](#) (p. 326) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeEventCategories  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
&X-Amz-Date=20140421T194732Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=6e25c542bf96fe24b28c12976ec92d2f856ab1d2a158e21c35441a736e4fde2b
```

Sample Response

```
<DescribeEventCategoriesResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <DescribeEventCategoriesResult>
    <EventCategoriesMapList>
      <EventCategoriesMap>
        <SourceType>db-instance</SourceType>
        <EventCategories>
          <EventCategory>backup</EventCategory>
          <EventCategory>recovery</EventCategory>
          <EventCategory>restoration</EventCategory>
          <EventCategory>failover</EventCategory>
          <EventCategory>low storage</EventCategory>
          <EventCategory>maintenance</EventCategory>
          <EventCategory>deletion</EventCategory>
          <EventCategory>availability</EventCategory>
          <EventCategory>configuration change</EventCategory>
          <EventCategory>notification</EventCategory>
          <EventCategory>failure</EventCategory>
          <EventCategory>creation</EventCategory>
        </EventCategories>
      </EventCategoriesMap>
      <EventCategoriesMap>
        <SourceType>db-security-group</SourceType>
        <EventCategories>
          <EventCategory>configuration change</EventCategory>
          <EventCategory>failure</EventCategory>
        </EventCategories>
      </EventCategoriesMap>
      <EventCategoriesMap>
        <SourceType>db-parameter-group</SourceType>
        <EventCategories>
          <EventCategory>configuration change</EventCategory>
        </EventCategories>
      </EventCategoriesMap>
      <EventCategoriesMap>
        <SourceType>db-snapshot</SourceType>
        <EventCategories>
          <EventCategory>deletion</EventCategory>
          <EventCategory>restoration</EventCategory>
          <EventCategory>notification</EventCategory>
          <EventCategory>failure</EventCategory>
          <EventCategory>creation</EventCategory>
        </EventCategories>
      </EventCategoriesMap>
    </EventCategoriesMapList>
  </DescribeEventCategoriesResult>
  <ResponseMetadata>
    <RequestId>b79456f2-b98c-11d3-f272-7cd6cce12cc5</RequestId>
  </ResponseMetadata>
</DescribeEventCategoriesResponse>
```

DescribeEvents

Returns events related to DB instances, DB security groups, DB snapshots, and DB parameter groups for the past 14 days. Events specific to a particular DB instance, DB security group, database snapshot, or DB parameter group can be obtained by providing the name as a parameter. By default, the past hour of events are returned.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

Duration

The number of minutes to retrieve events for.

Default: 60

Type: Integer

Required: No

EndTime

The end of the time interval for which to retrieve events, specified in ISO 8601 format. For more information about ISO 8601, go to the [ISO8601 Wikipedia page](#).

Example: 2009-07-08T18:00Z

Type: Timestamp

Required: No

EventCategories.EventCategory.N

A list of event categories that trigger notifications for a event notification subscription.

Type: array of Strings

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous DescribeEvents request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

SourceIdentifier

The identifier of the event source for which events will be returned. If not specified, then all sources are included in the response.

Constraints:

- If `SourceIdentifier` is supplied, `SourceType` must also be provided.
- If the source type is `DBInstance`, then a `DBInstanceIdentifier` must be supplied.
- If the source type is `DBSecurityGroup`, a `DBSecurityGroupName` must be supplied.

- If the source type is `DBParameterGroup`, a `DBParameterGroupName` must be supplied.
- If the source type is `DBSnapshot`, a `DBSnapshotIdentifier` must be supplied.
- Cannot end with a hyphen or contain two consecutive hyphens.

Type: String

Required: No

SourceType

The event source to retrieve events for. If no value is specified, all events are returned.

Type: String

Valid Values: `db-instance` | `db-parameter-group` | `db-security-group` | `db-snapshot` | `db-cluster` | `db-cluster-snapshot`

Required: No

StartTime

The beginning of the time interval to retrieve events for, specified in ISO 8601 format. For more information about ISO 8601, go to the [ISO8601 Wikipedia page](#).

Example: `2009-07-08T18:00Z`

Type: Timestamp

Required: No

Response Elements

The following elements are returned by the service.

Events.Event.N

A list of [Event \(p. 325\)](#) instances.

Type: array of [Event \(p. 325\)](#) objects

Marker

An optional pagination token provided by a previous Events request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeEvents  
&Duration=1440  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
&X-Amz-Date=20140421T194733Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date
```



```
&X-Amz-  
Signature=8e313cabcd9766c56a2886b5b298fd944e0b7cfa248953c82705fdd0374f27
```

Sample Response

```
<DescribeEventsResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <DescribeEventsResult>  
    <Events>  
      <Event>  
        <Message>Backing up DB instance</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>  
          <EventCategory>backup</EventCategory>  
        </EventCategories>  
        <Date>2014-04-21T06:23:33.866Z</Date>  
        <SourceIdentifier>mypgdbinstance</SourceIdentifier>  
      </Event>  
      <Event>  
        <Message>Finished DB Instance backup</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>  
          <EventCategory>backup</EventCategory>  
        </EventCategories>  
        <Date>2014-04-21T06:25:03.928Z</Date>  
        <SourceIdentifier>mypgdbinstance</SourceIdentifier>  
      </Event>  
      <Event>  
        <Message>Backing up DB instance</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>  
          <EventCategory>backup</EventCategory>  
        </EventCategories>  
        <Date>2014-04-21T07:09:34.594Z</Date>  
        <SourceIdentifier>my-mysqlexampled4</SourceIdentifier>  
      </Event>  
      <Event>  
        <Message>Finished DB Instance backup</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>  
          <EventCategory>backup</EventCategory>  
        </EventCategories>  
        <Date>2014-04-21T07:11:05.640Z</Date>  
        <SourceIdentifier>my-mysqlexampled4</SourceIdentifier>  
      </Event>  
      <Event>  
        <Message>Backing up DB instance</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>  
          <EventCategory>backup</EventCategory>  
        </EventCategories>  
        <Date>2014-04-21T09:26:25.988Z</Date>  
        <SourceIdentifier>my-oracledb1</SourceIdentifier>  
      </Event>  
      <Event>  
        <Message>Finished DB Instance backup</Message>  
        <SourceType>db-instance</SourceType>  
        <EventCategories>
```

```
    <EventCategory>backup</EventCategory>
  </EventCategories>
  <Date>2014-04-21T09:28:38.048Z</Date>
  <SourceIdentifier>my-oracledb1</SourceIdentifier>
</Event>
</Events>
</DescribeEventsResult>
<ResponseMetadata>
  <RequestId>b7a8cd43-b98c-11d3-a907-5a2c468b9cb0</RequestId>
</ResponseMetadata>
</DescribeEventsResponse>
```

DescribeEventSubscriptions

Lists all the subscription descriptions for a customer account. The description for a subscription includes SubscriptionName, SNSTopicARN, CustomerID, SourceType, SourceID, CreationTime, and Status.

If you specify a SubscriptionName, lists the description for that subscription.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous DescribeOrderableDBInstanceOptions request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by MaxRecords .

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified MaxRecords value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

SubscriptionName

The name of the RDS event notification subscription you want to describe.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

EventSubscriptionsList.EventSubscription.N

A list of EventSubscriptions data types.

Type: array of [EventSubscription \(p. 327\)](#) objects

Marker

An optional pagination token provided by a previous DescribeOrderableDBInstanceOptions request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by MaxRecords.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

SubscriptionNotFound

The subscription name does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DescribeEventSubscriptions  
&MaxRecords=100  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
&X-Amz-Date=20140428T161907Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=4208679fe967783a1a149c826199080a066085d5a88227a80c6c0cadb3e8c0d4
```

Sample Response

```
<DescribeEventSubscriptionsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeEventSubscriptionsResult>  
    <EventSubscriptionsList>  
      <EventSubscription>  
        <Enabled>true</Enabled>  
        <CustomerAwsId>802#####</CustomerAwsId>  
        <SourceType>db-instance</SourceType>  
        <Status>active</Status>  
        <SourceIdsList>  
          <SourceId>mysqldb-rr</SourceId>  
          <SourceId>mysqldb</SourceId>  
        </SourceIdsList>  
        <SubscriptionCreationTime>2014-04-25 22:01:46.327</  
SubscriptionCreationTime>  
        <EventCategoriesList>  
          <EventCategory>creation</EventCategory>  
          <EventCategory>deletion</EventCategory>  
          <EventCategory>configuration change</EventCategory>  
          <EventCategory>low storage</EventCategory>  
        </EventCategoriesList>  
        <CustSubscriptionId>myawsuser-instance</CustSubscriptionId>  
        <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</  
SnsTopicArn>  
      </EventSubscription>  
      <EventSubscription>  
        <Enabled>true</Enabled>  
        <CustomerAwsId>802#####</CustomerAwsId>
```

```

        <SourceType>db-parameter-group</SourceType>
        <Status>active</Status>
        <SourceIdsList>
            <SourceId>mydbparametergroup00</SourceId>
        </SourceIdsList>
        <SubscriptionCreationTime>2014-04-25 21:44:44.68</
SubscriptionCreationTime>
        <EventCategoriesList>
            <EventCategory>configuration change</EventCategory>
        </EventCategoriesList>
        <CustSubscriptionId>myawsuser-paramgrp</CustSubscriptionId>
        <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</
SnsTopicArn>
    </EventSubscription>
    <EventSubscription>
        <Enabled>true</Enabled>
        <CustomerAwsId>802#####</CustomerAwsId>
        <SourceType>db-security-group</SourceType>
        <Status>active</Status>
        <SubscriptionCreationTime>2014-04-25 21:43:25.542</
SubscriptionCreationTime>
        <EventCategoriesList>
            <EventCategory>configuration change</EventCategory>
            <EventCategory>failure</EventCategory>
        </EventCategoriesList>
        <CustSubscriptionId>myawsuser-secgrp</CustSubscriptionId>
        <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</
SnsTopicArn>
    </EventSubscription>
    <EventSubscription>
        <Enabled>true</Enabled>
        <CustomerAwsId>802#####</CustomerAwsId>
        <SourceType>db-snapshot</SourceType>
        <Status>active</Status>
        <SubscriptionCreationTime>2014-04-25 21:41:24.405</
SubscriptionCreationTime>
        <EventCategoriesList>
            <EventCategory>creation</EventCategory>
            <EventCategory>failure</EventCategory>
            <EventCategory>deletion</EventCategory>
        </EventCategoriesList>
        <CustSubscriptionId>myawsuser-snapshot</CustSubscriptionId>
        <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</
SnsTopicArn>
    </EventSubscription>
</EventSubscriptionsList>
</DescribeEventSubscriptionsResult>
<ResponseMetadata>
    <RequestId>c2c6da4e-bde9-11d3-fe11-33d33a9bb7e3</RequestId>
</ResponseMetadata>
</DescribeEventSubscriptionsResponse>

```

DescribeOptionGroupOptions

Describes all available options.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

EngineName

A required parameter. Options available for the given engine name will be described.

Type: String

Required: Yes

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

MajorEngineVersion

If specified, filters the results to include only options for the specified major engine version.

Type: String

Required: No

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

OptionGroupOptions.OptionGroupOption.N

List of available option group options.

Type: array of [OptionGroupOption \(p. 335\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeOptionGroupOptions  
  &EngineName=oracle-sel  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194733Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=3792d1669ce65ba1ba6a85b2e4057235e46dd3d0072663c17f4b4439fd8af702
```

Sample Response

```
<DescribeOptionGroupOptionsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeOptionGroupOptionsResult>  
    <OptionGroupOptions>  
      <OptionGroupOption>  
        <MajorEngineVersion>11.2</MajorEngineVersion>  
        <PortRequired>>false</PortRequired>  
        <Persistent>>false</Persistent>  
        <OptionsDependedOn>  
          <OptionName>XMLDB</OptionName>  
        </OptionsDependedOn>  
        <OptionsConflictsWith/>  
        <Permanent>>false</Permanent>  
        <Description>Oracle Application Express Runtime Environment</  
Description>  
        <Name>APEX</Name>  
        <OptionGroupOptionSettings/>  
        <EngineName>oracle-sel</EngineName>  
        <MinimumRequiredMinorEngineVersion>0.2.v4</  
MinimumRequiredMinorEngineVersion>  
      </OptionGroupOption>  
      <OptionGroupOption>  
        <MajorEngineVersion>11.2</MajorEngineVersion>  
        <PortRequired>>false</PortRequired>  
        <Persistent>>false</Persistent>  
        <OptionsDependedOn>  
          <OptionName>APEX</OptionName>  
        </OptionsDependedOn>  
        <OptionsConflictsWith/>  
        <Permanent>>false</Permanent>  
        <Description>Oracle Application Express Development Environment</  
Description>  
        <Name>APEX-DEV</Name>  
        <OptionGroupOptionSettings/>
```

```
<EngineName>oracle-sel</EngineName>
  <MinimumRequiredMinorEngineVersion>0.2.v4</
MinimumRequiredMinorEngineVersion>
  </OptionGroupOption>
  <OptionGroupOption>
    <MajorEngineVersion>11.2</MajorEngineVersion>
    <PortRequired>true</PortRequired>
    <Persistent>false</Persistent>
    <OptionsDependedOn/>
    <OptionsConflictsWith/>
    <Permanent>false</Permanent>
    <Description>Oracle Enterprise Manager (Database Control only)</
Description>
    <DefaultPort>1158</DefaultPort>
    <Name>OEM</Name>
    <OptionGroupOptionSettings/>
    <EngineName>oracle-sel</EngineName>
    <MinimumRequiredMinorEngineVersion>0.2.v3</
MinimumRequiredMinorEngineVersion>
  </OptionGroupOption>
</OptionGroupOptions>
</DescribeOptionGroupOptionsResult>
<ResponseMetadata>
  <RequestId>b7b26a8f-b98c-11d3-f272-7cd6cce12cc5</RequestId>
</ResponseMetadata>
</DescribeOptionGroupOptionsResponse>
```


DescribeOptionGroups

Describes the available option groups.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

EngineName

Filters the list of option groups to only include groups associated with a specific database engine.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

MajorEngineVersion

Filters the list of option groups to only include groups associated with a specific database engine version. If specified, then EngineName must also be specified.

Type: String

Required: No

Marker

An optional pagination token provided by a previous DescribeOptionGroups request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

OptionGroupName

The name of the option group to describe. Cannot be supplied together with EngineName or MajorEngineVersion.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

OptionGroupsList.OptionGroup.N

List of option groups.

Type: array of [OptionGroup](#) (p. 333) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

OptionGroupNotFoundFault

The specified option group could not be found.
HTTP Status Code: 404

Examples

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=DescribeOptionGroups  
  &MaxRecords=100  
  &OptionGroupName=myawsuser-grp1  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140421T231357Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=fabfb85c44e3f151d44211790c5135a9074fdb8d85ec117788ac6cfab6c5bc
```

Sample Response

```
<DescribeOptionGroupsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeOptionGroupsResult>  
    <OptionGroupsList>  
      <OptionGroup>  
        <AllowsVpcAndNonVpcInstanceMemberships>true</  
AllowsVpcAndNonVpcInstanceMemberships>  
        <MajorEngineVersion>5.6</MajorEngineVersion>  
        <OptionGroupName>myawsuser-grp1</OptionGroupName>  
        <EngineName>mysql</EngineName>  
        <OptionGroupDescription>my test option group</OptionGroupDescription>  
        <Options/>  
      </OptionGroup>  
    </OptionGroupsList>  
  </DescribeOptionGroupsResult>  
  <ResponseMetadata>  
    <RequestId>8c6201fc-b9ff-11d3-f92b-31fa5e8dbc99</RequestId>  
  </ResponseMetadata>  
</DescribeOptionGroupsResponse>
```

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeOptionGroups  
  &MaxRecords=100  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140613/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140613T223341Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=5ae331adcd684c27d66e0b794a51933effe32a4c026eba2e994ae483ee47a0ba
```

Sample Response

```
<DescribeOptionGroupsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeOptionGroupsResult>  
    <OptionGroupsList>  
      <OptionGroup>  
        <OptionGroupName>default:mysql-5-5</OptionGroupName>  
        <AllowsVpcAndNonVpcInstanceMemberships>true</  
AllowsVpcAndNonVpcInstanceMemberships>  
        <MajorEngineVersion>5.5</MajorEngineVersion>  
        <EngineName>mysql</EngineName>  
        <OptionGroupDescription>Default option group for mysql 5.5</  
OptionGroupDescription>  
        <Options/>  
      </OptionGroup>  
      <OptionGroup>  
        <OptionGroupName>default:postgres-9-3</OptionGroupName>  
        <AllowsVpcAndNonVpcInstanceMemberships>true</  
AllowsVpcAndNonVpcInstanceMemberships>  
        <MajorEngineVersion>9.3</MajorEngineVersion>  
        <EngineName>postgres</EngineName>  
        <OptionGroupDescription>Default option group for postgres 9.3</  
OptionGroupDescription>  
        <Options/>  
      </OptionGroup>  
      <OptionGroup>  
        <OptionGroupName>default:sqlserver-ex-10-50</OptionGroupName>  
        <AllowsVpcAndNonVpcInstanceMemberships>true</  
AllowsVpcAndNonVpcInstanceMemberships>  
        <MajorEngineVersion>10.50</MajorEngineVersion>  
        <EngineName>sqlserver-ex</EngineName>  
        <OptionGroupDescription>Default option group for sqlserver-ex 10.50</  
OptionGroupDescription>  
        <Options/>  
      </OptionGroup>  
    </OptionGroupsList>  
  </DescribeOptionGroupsResult>  
</DescribeOptionGroupsResponse>
```

```

    <OptionGroupName>default:sqlserver-se-10-50-mirrored</
OptionGroupName>
    <AllowsVpcAndNonVpcInstanceMemberships>>true</
AllowsVpcAndNonVpcInstanceMemberships>
    <MajorEngineVersion>10.50</MajorEngineVersion>
    <EngineName>sqlserver-se</EngineName>
    <OptionGroupDescription>Default Mirroring-enabled option group for
sqlserver-se 10.50</OptionGroupDescription>
    <Options>
    <Option>
    <OptionName>Mirroring</OptionName>
    <OptionDescription>SQLServer Database Mirroring</
OptionDescription>
    <Persistent>>false</Persistent>
    <Permanent>>false</Permanent>
    <OptionSettings/>
    <VpcSecurityGroupMemberships/>
    <DBSecurityGroupMemberships/>
    </Option>
    </Options>
    </OptionGroup>
    <OptionGroup>
    <OptionGroupName>default:sqlserver-se-11-00</OptionGroupName>
    <AllowsVpcAndNonVpcInstanceMemberships>>true</
AllowsVpcAndNonVpcInstanceMemberships>
    <MajorEngineVersion>11.00</MajorEngineVersion>
    <EngineName>sqlserver-se</EngineName>
    <OptionGroupDescription>Default option group for sqlserver-se 11.00</
OptionGroupDescription>
    <Options/>
    </OptionGroup>
    <OptionGroup>
    <OptionGroupName>myawsuser-opt-grp</OptionGroupName>
    <AllowsVpcAndNonVpcInstanceMemberships>>false</
AllowsVpcAndNonVpcInstanceMemberships>
    <MajorEngineVersion>11.2</MajorEngineVersion>
    <EngineName>oracle-ee</EngineName>
    <OptionGroupDescription>test option group</OptionGroupDescription>
    <Options>
    <Option>
    <OptionName>NATIVE_NETWORK_ENCRYPTION</OptionName>
    <OptionDescription>Oracle Advanced Security - Native Network
Encryption</OptionDescription>
    <Persistent>>false</Persistent>
    <Permanent>>false</Permanent>
    <OptionSettings>
    <OptionSetting>
    <DataType>STRING</DataType>
    <IsModifiable>>true</IsModifiable>
    <IsCollection>>true</IsCollection>
    <Description>Specifies list of checksumming algorithms in
order of intended use</Description>
    <Name>SQLNET.CRYPTO_CHECKSUM_TYPES_SERVER</Name>
    <Value>SHA1,MD5</Value>
    <ApplyType>STATIC</ApplyType>
    <DefaultValue>SHA1,MD5</DefaultValue>
    <AllowedValues>SHA1,MD5</AllowedValues>
    </OptionSetting>
    <OptionSetting>

```

```

        <DataType>STRING</DataType>
        <IsModifiable>true</IsModifiable>
        <IsCollection>true</IsCollection>
        <Description>Specifies list of encryption algorithms in order
of intended use</Description>
        <Name>SQLNET.ENCRYPTION_TYPES_SERVER</Name>

    <Value>RC4_256,AES256,AES192,3DES168,RC4_128,AES128,3DES112,RC4_56,DES,RC4_40,DES40</
Value>

        <ApplyType>STATIC</ApplyType>

    <DefaultValue>RC4_256,AES256,AES192,3DES168,RC4_128,AES128,3DES112,RC4_56,DES,RC4_40,DES40
DefaultValue>

    <AllowedValues>RC4_256,AES256,AES192,3DES168,RC4_128,AES128,3DES112,RC4_56,DES,RC4_40,DES40
AllowedValues>
    </OptionSetting>
    <OptionSetting>
        <DataType>STRING</DataType>
        <IsModifiable>true</IsModifiable>
        <IsCollection>>false</IsCollection>
        <Description>Specifies the desired encryption behavior</
Description>
        <Name>SQLNET.ENCRYPTION_SERVER</Name>
        <Value>REQUESTED</Value>
        <ApplyType>STATIC</ApplyType>
        <DefaultValue>REQUESTED</DefaultValue>
        <AllowedValues>ACCEPTED,REJECTED,REQUESTED,REQUIRED</
AllowedValues>
    </OptionSetting>
    <OptionSetting>
        <DataType>STRING</DataType>
        <IsModifiable>true</IsModifiable>
        <IsCollection>>false</IsCollection>
        <Description>Specifies the desired data integrity behavior</
Description>
        <Name>SQLNET.CRYPTO_CHECKSUM_SERVER</Name>
        <Value>REQUESTED</Value>
        <ApplyType>STATIC</ApplyType>
        <DefaultValue>REQUESTED</DefaultValue>
        <AllowedValues>ACCEPTED,REJECTED,REQUESTED,REQUIRED</
AllowedValues>
    </OptionSetting>
    </OptionSettings>
    <VpcSecurityGroupMemberships/>
    <DBSecurityGroupMemberships/>
</Option>
<Option>
    <OptionName>XMLDB</OptionName>
    <OptionDescription>Oracle XMLDB Repository</OptionDescription>
    <Persistent>>false</Persistent>
    <Permanent>>false</Permanent>
    <OptionSettings/>
    <VpcSecurityGroupMemberships/>
    <DBSecurityGroupMemberships/>
</Option>
<Option>
    <Port>1158</Port>
    <OptionName>OEM</OptionName>

```

```
        <OptionDescription>Oracle Enterprise Manager (Database Control
only)</OptionDescription>
        <Persistent>>false</Persistent>
        <Permanent>>false</Permanent>
        <OptionSettings/>
        <VpcSecurityGroupMemberships/>
        <DBSecurityGroupMemberships>
            <DBSecurityGroup>
                <Status>authorized</Status>
                <DBSecurityGroupName>sg-db-sec-grp</DBSecurityGroupName>
            </DBSecurityGroup>
        </DBSecurityGroupMemberships>
    </Option>
</Options>
</OptionGroup>
    <Option>
        <OptionName>APEX</OptionName>
        <OptionDescription>Oracle Application Express Runtime
Environment</OptionDescription>
        <Persistent>>false</Persistent>
        <Permanent>>false</Permanent>
        <OptionSettings/>
        <VpcSecurityGroupMemberships/>
        <DBSecurityGroupMemberships/>
    </Option>
</Options>
</OptionGroup>
</OptionGroupsList>
</DescribeOptionGroupsResult>
<ResponseMetadata>
    <RequestId>b2ce0772-f55a-11e3-bd0f-bb88ac05a37c</RequestId>
</ResponseMetadata>
</DescribeOptionGroupsResponse>
```

DescribeOrderableDBInstanceOptions

Returns a list of orderable DB instance options for the specified engine.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBInstanceClass

The DB instance class filter value. Specify this parameter to show only the available offerings matching the specified DB instance class.

Type: String

Required: No

Engine

The name of the engine to retrieve DB instance options for.

Type: String

Required: Yes

EngineVersion

The engine version filter value. Specify this parameter to show only the available offerings matching the specified engine version.

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

LicenseModel

The license model filter value. Specify this parameter to show only the available offerings matching the specified license model.

Type: String

Required: No

Marker

An optional pagination token provided by a previous DescribeOrderableDBInstanceOptions request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

Vpc

The VPC filter value. Specify this parameter to show only the available VPC or non-VPC offerings.

Type: Boolean

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous `OrderableDBInstanceOptions` request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

OrderableDBInstanceOptions.OrderableDBInstanceOption.N

An `OrderableDBInstanceOption` (p. 340) structure containing information about orderable options for the DB instance.

Type: array of `OrderableDBInstanceOption` (p. 340) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribeOrderableDBInstanceOptions  
  &Engine=mysql  
  &MaxRecords=100  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140421/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194733Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=b49545dd3c933bdded80655d433d84bf743261ea1bebb33a7922c5c2c5240cd8
```

Sample Response

```
<DescribeOrderableDBInstanceOptionsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DescribeOrderableDBInstanceOptionsResult>  
    <Marker>ZGIubTEuc21hbGwKZ2VuZXJhbC1wdWJsaWMtbGljZW5zZQo1LjEuNjkKTg==</  
Marker>  
    <OrderableDBInstanceOptions>  
      <OrderableDBInstanceOption>  
        <MultiAZCapable>>true</MultiAZCapable>  
        <Engine>mysql</Engine>  
        <LicenseModel>general-public-license</LicenseModel>  
        <ReadReplicaCapable>>true</ReadReplicaCapable>  
        <Vpc>>false</Vpc>  
        <EngineVersion>5.1.57</EngineVersion>
```



```
<AvailabilityZones>
  <AvailabilityZone>
    <Name>us-west-2a</Name>
    <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
  </AvailabilityZone>
  <AvailabilityZone>
    <Name>us-west-2b</Name>
    <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
  </AvailabilityZone>
  <AvailabilityZone>
    <Name>us-west-2c</Name>
    <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
  </AvailabilityZone>
</AvailabilityZones>
<DBInstanceClass>db.m1.large</DBInstanceClass>
</OrderableDBInstanceOption>
<OrderableDBInstanceOption>
  <MultiAZCapable>true</MultiAZCapable>
  <Engine>mysql</Engine>
  <LicenseModel>general-public-license</LicenseModel>
  <ReadReplicaCapable>true</ReadReplicaCapable>
  <Vpc>true</Vpc>
  <EngineVersion>5.1.57</EngineVersion>
  <AvailabilityZones>
    <AvailabilityZone>
      <Name>us-west-2a</Name>
      <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
    </AvailabilityZone>
    <AvailabilityZone>
      <Name>us-west-2b</Name>
      <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
    </AvailabilityZone>
    <AvailabilityZone>
      <Name>us-west-2c</Name>
      <ProvisionedIopsCapable>true</ProvisionedIopsCapable>
    </AvailabilityZone>
  </AvailabilityZones>
  <DBInstanceClass>db.m1.large</DBInstanceClass>
</OrderableDBInstanceOption>
</OrderableDBInstanceOptions>
</DescribeOrderableDBInstanceOptionsResult>
<ResponseMetadata>
  <RequestId>b7ceb73e-b98c-11d3-a907-5a2c468b9cb0</RequestId>
</ResponseMetadata>
</DescribeOrderableDBInstanceOptionsResponse>
```

DescribePendingMaintenanceActions

Returns a list of resources (for example, DB instances) that have at least one pending maintenance action.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

Filters.Filter.N

A filter that specifies one or more resources to return pending maintenance actions for.

Supported filters:

- `db-cluster-id` - Accepts DB cluster identifiers and DB cluster Amazon Resource Names (ARNs). The results list will only include pending maintenance actions for the DB clusters identified by these ARNs.
- `db-instance-id` - Accepts DB instance identifiers and DB instance ARNs. The results list will only include pending maintenance actions for the DB instances identified by these ARNs.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous `DescribePendingMaintenanceActions` request. If this parameter is specified, the response includes only records beyond the marker, up to a number of records specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

ResourceIdentifier

The ARN of a resource to return pending maintenance actions for.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous `DescribePendingMaintenanceActions` request. If this parameter is specified, the response includes only records beyond the marker, up to a number of records specified by `MaxRecords`.

Type: String

PendingMaintenanceActions.ResourcePendingMaintenanceActions.N

A list of the pending maintenance actions for the resource.

Type: array of [ResourcePendingMaintenanceActions \(p. 351\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

ResourceNotFoundFault

The specified resource ID was not found.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
  ?Action=DescribePendingMaintenanceActions  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20141216/us-west-2/rds/aws4_request  
  &X-Amz-Date=20140421T194732Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=6e25c542bf96fe24b28c12976ec92d2f856ab1d2a158e21c35441a736e4fde2b
```

Sample Response

```
<DescribePendingMaintenanceActionsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribePendingMaintenanceActionsResult>  
    <PendingMaintenanceActions>  
      <ResourcePendingMaintenanceActions>  
        <ResourceIdentifier>arn:aws:rds:us-east-1:123456781234:db:my-  
instance</ResourceIdentifier>  
        <PendingMaintenanceActionDetails>  
          <PendingMaintenanceAction>  
            <Action>os-upgrade</Action>  
          </PendingMaintenanceAction>  
        </PendingMaintenanceActionDetails>  
      </ResourcePendingMaintenanceActions>  
      <ResourcePendingMaintenanceActions>  
        <ResourceIdentifier>arn:aws:rds:us-east-1:123456781234:db:another-  
instance</ResourceIdentifier>  
        <PendingMaintenanceActionDetails>  
          <PendingMaintenanceAction>  
            <Action>os-upgrade</Action>  
          </PendingMaintenanceAction>  
        </PendingMaintenanceActionDetails>  
      </ResourcePendingMaintenanceActions>  
    </PendingMaintenanceActions>  
  </DescribePendingMaintenanceActionsResult>  
</ResponseMetadata>
```

```
<RequestId>dcfe0682-870c-11e4-9833-b3ad657ea9da</RequestId>  
</ResponseMetadata>  
</DescribePendingMaintenanceActionsResponse>
```

DescribeReservedDBInstances

Returns information about reserved DB instances for this account, or about a specified reserved DB instance.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceClass

The DB instance class filter value. Specify this parameter to show only those reservations matching the specified DB instances class.

Type: String

Required: No

Duration

The duration filter value, specified in years or seconds. Specify this parameter to show only reservations for this duration.

Valid Values: 1 | 3 | 31536000 | 94608000

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter](#) (p. 329) objects

Required: No

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more than the `MaxRecords` value is available, a pagination token called a marker is included in the response so that the following results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

MultiAZ

The Multi-AZ filter value. Specify this parameter to show only those reservations matching the specified Multi-AZ parameter.

Type: Boolean

Required: No

OfferingType

The offering type filter value. Specify this parameter to show only the available offerings matching the specified offering type.

Valid Values: "Partial Upfront" | "All Upfront" | "No Upfront"

Type: String

Required: No

ProductDescription

The product description filter value. Specify this parameter to show only those reservations matching the specified product description.

Type: String

Required: No

ReservedDBInstanceId

The reserved DB instance identifier filter value. Specify this parameter to show only the reservation that matches the specified reservation ID.

Type: String

Required: No

ReservedDBInstancesOfferingId

The offering identifier filter value. Specify this parameter to show only purchased reservations matching the specified offering identifier.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

ReservedDBInstances.ReservedDBInstance.N

A list of reserved DB instances.

Type: array of [ReservedDBInstance](#) (p. 348) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

ReservedDBInstanceNotFound

The specified reserved DB Instance not found.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DescribeReservedDBInstances  
&ReservedDBInstanceId=customerSpecifiedID  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140420/us-west-2/rds/aws4_request  
&X-Amz-Date=20140420T162211Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=3312d17a4c43bcd209bc22a0778dd23e73f8434254abbd7ac53b89ade3dae88e
```

Sample Response

```
<DescribeReservedDBInstancesResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <DescribeReservedDBInstancesResult>
    <ReservedDBInstances>
      <ReservedDBInstance>
        <OfferingType>Partial Upfront</OfferingType>
        <CurrencyCode>USD</CurrencyCode>
        <RecurringCharges/>
        <ProductDescription>mysql</ProductDescription>
        <ReservedDBInstancesOfferingId>649fd0c8-cf6d-47a0-bfa6-060f8e75e95f</ReservedDBInstancesOfferingId>
        <MultiAZ>>false</MultiAZ>
        <State>active</State>
        <ReservedDBInstanceId>myreservationid</ReservedDBInstanceId>
        <DBInstanceCount>1</DBInstanceCount>
        <StartTime>2014-05-15T00:25:14.131Z</StartTime>
        <Duration>31536000</Duration>
        <FixedPrice>227.5</FixedPrice>
        <UsagePrice>0.046</UsagePrice>
        <DBInstanceClass>db.m1.small</DBInstanceClass>
      </ReservedDBInstance>
    </DescribeReservedDBInstancesResult>
    <ResponseMetadata>
      <RequestId>c695119b-2961-11e1-bd06-6fe008f046c3</RequestId>
    </ResponseMetadata>
  </DescribeReservedDBInstancesResponse>
```

DescribeReservedDBInstancesOfferings

Lists available reserved DB instance offerings.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBInstanceClass

The DB instance class filter value. Specify this parameter to show only the available offerings matching the specified DB instance class.

Type: String

Required: No

Duration

Duration filter value, specified in years or seconds. Specify this parameter to show only reservations for this duration.

Valid Values: 1 | 3 | 31536000 | 94608000

Type: String

Required: No

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more than the `MaxRecords` value is available, a pagination token called a marker is included in the response so that the following results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

MultiAZ

The Multi-AZ filter value. Specify this parameter to show only the available offerings matching the specified Multi-AZ parameter.

Type: Boolean

Required: No

OfferingType

The offering type filter value. Specify this parameter to show only the available offerings matching the specified offering type.

Valid Values: "Partial Upfront" | "All Upfront" | "No Upfront"

Type: String

Required: No

ProductDescription

Product description filter value. Specify this parameter to show only the available offerings matching the specified product description.

Type: String

Required: No

ReservedDBInstancesOfferingId

The offering identifier filter value. Specify this parameter to show only the available offering that matches the specified reservation identifier.

Example: 438012d3-4052-4cc7-b2e3-8d3372e0e706

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

ReservedDBInstancesOfferings.ReservedDBInstancesOffering.N

A list of reserved DB instance offerings.

Type: array of [ReservedDBInstancesOffering](#) (p. 350) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

ReservedDBInstancesOfferingNotFound

Specified offering does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=DescribeReservedDBInstancesOfferings  
&ReservedDBInstancesOfferingId=438012d3-4052-4cc7-b2e3-8d3372e0e706  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140411/us-east-1/rds/aws4_request  
&X-Amz-Date=20140411T203327Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=545f04acffeb4b80d2e778526b1c9da79d0b3097151c24f28e83e851d65422e2
```

Sample Response

```
<DescribeReservedDBInstancesOfferingsResponse xmlns="http://
rds.amazonaws.com/doc/2014-09-01/">
  <DescribeReservedDBInstancesOfferingsResult>
    <ReservedDBInstancesOfferings>
      <ReservedDBInstancesOffering>
        <Duration>31536000</Duration>
        <OfferingType>Partial Upfront</OfferingType>
        <CurrencyCode>USD</CurrencyCode>
        <RecurringCharges>
          <RecurringCharge>
            <RecurringChargeFrequency>Hourly</RecurringChargeFrequency>
            <RecurringChargeAmount>0.123</RecurringChargeAmount>
          </RecurringCharge>
        </RecurringCharges>
        <FixedPrice>162.0</FixedPrice>
        <ProductDescription>mysql</ProductDescription>
        <UsagePrice>0.0</UsagePrice>
        <MultiAZ>>false</MultiAZ>
        <ReservedDBInstancesOfferingId>SampleOfferingId</
ReservedDBInstancesOfferingId>
        <DBInstanceClass>db.m1.small</DBInstanceClass>
      </ReservedDBInstancesOffering>
    </ReservedDBInstancesOfferings>
  </DescribeReservedDBInstancesOfferingsResult>
  <ResponseMetadata>
    <RequestId>521b420a-2961-11e1-bd06-6fe008f046c3</RequestId>
  </ResponseMetadata>
</DescribeReservedDBInstancesOfferingsResponse>
```

DescribeSourceRegions

Returns a list of the source AWS regions where the current AWS region can create a Read Replica or copy a DB snapshot from. This API action supports pagination.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

Marker

An optional pagination token provided by a previous [DescribeSourceRegions \(p. 183\)](#) request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

MaxRecords

The maximum number of records to include in the response. If more records exist than the specified `MaxRecords` value, a pagination token called a marker is included in the response so that the remaining results can be retrieved.

Default: 100

Constraints: Minimum 20, maximum 100.

Type: Integer

Required: No

RegionName

The source region name. For example, `us-east-1`.

Constraints:

- Must specify a valid AWS Region name.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

Marker

An optional pagination token provided by a previous request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

SourceRegions.SourceRegion.N

A list of `SourceRegion` instances that contains each source AWS Region that the current region can get a Read Replica or a DB snapshot from.

Type: array of [SourceRegion \(p. 352\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=DescribeSourceRegions  
  &MaxRecords=10  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140429/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140429T175351Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=9164337efa99caf850e874a1cb7ef62f3cea29d0b448b9e0e7c53b288ddffed2
```

Sample Response

```
<DescribeSourceRegionsResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <DescribeSourceRegionsResult>  
    <SourceRegions>  
      <SourceRegion>  
        <RegionName>ap-northeast-1</RegionName>  
        <EndPoint>https://rds.ap-northeast-1.amazonaws.com</EndPoint>  
        <Status>available</Status>  
      </SourceRegion>  
      <SourceRegion>  
        <RegionName>ap-southeast-2</RegionName>  
        <EndPoint>https://rds.ap-southeast-2.amazonaws.com</EndPoint>  
        <Status>available</Status>  
      </SourceRegion>  
    </SourceRegions>  
  </DescribeSourceRegionsResult>  
  <ResponseMetadata>  
    <RequestId>01b2685a-b978-11d3-f272-7cd6cce12cc5</RequestId>  
  </ResponseMetadata>  
</DescribeSourceRegionsResponse>
```

DownloadDBLogFilePortion

Downloads all or a portion of the specified log file, up to 1 MB in size.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceIdentifier

The customer-assigned name of the DB instance that contains the log files you want to list.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

LogFileName

The name of the log file to be downloaded.

Type: String

Required: Yes

Marker

The pagination token provided in the previous request or "0". If the Marker parameter is specified the response includes only records beyond the marker until the end of the file or up to NumberOfLines.

Type: String

Required: No

NumberOfLines

The number of lines to download. If the number of lines specified results in a file over 1 MB in size, the file will be truncated at 1 MB in size.

If the NumberOfLines parameter is specified, then the block of lines returned can be from the beginning or the end of the log file, depending on the value of the Marker parameter.

- If neither Marker or NumberOfLines are specified, the entire log file is returned up to a maximum of 10000 lines, starting with the most recent log entries first.
- If NumberOfLines is specified and Marker is not specified, then the most recent lines from the end of the log file are returned.
- If Marker is specified as "0", then the specified number of lines from the beginning of the log file are returned.
- You can download the log file in blocks of lines by specifying the size of the block using the NumberOfLines parameter, and by specifying a value of "0" for the Marker parameter in your first request. Include the Marker value returned in the response as the Marker value for the next request, continuing until the AdditionalDataPending response element returns false.

Type: Integer

Required: No

Response Elements

The following elements are returned by the service.

AdditionalDataPending

Boolean value that if true, indicates there is more data to be downloaded.

Type: Boolean

LogFileData

Entries from the specified log file.

Type: String

Marker

A pagination token that can be used in a subsequent DownloadDBLogFilePortion request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBLogFileNotFoundFault

LogFileName does not refer to an existing DB log file.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=DownloadDBLogFilePortion  
&DBInstanceIdentifier=myexampledb  
&LogFileName=log%2FERROR  
&Marker=0  
&NumberOfLines=50  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140127/us-west-2/rds/aws4_request  
&X-Amz-Date=20140127T235259Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=2171c5a8e91a70202e77de7e81df75787f3bbd6b4ea97f7a426205474fcc446f
```

Sample Response

```
<DownloadDBLogFilePortionResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <DownloadDBLogFilePortionResult>  
    <Marker>0:4485</Marker>  
    <LogFileData>??2014-01-26 23:59:00.01 spid54      Microsoft SQL Server  
2012 - 11.0.2100.60 (X64)  
  
Feb 10 2012 19:39:15  
  
Copyright (c) Microsoft Corporation
```

```
Web Edition (64-bit) on Windows NT 6.1 &lt;X64&gt; (Build 7601: Service Pack
1) (Hypervisor)

2014-01-26 23:59:00.01 spid54      (c) Microsoft Corporation.

2014-01-26 23:59:00.01 spid54      All rights reserved.

2014-01-26 23:59:00.01 spid54      Server process ID is 2976.

2014-01-26 23:59:00.01 spid54      System Manufacturer: 'Xen', System Model:
'HVM domU'.

2014-01-26 23:59:00.01 spid54      Authentication mode is MIXED.

2014-01-26 23:59:00.01 spid54      Logging SQL Server messages in file 'D:
\RDSBDDATA\Log\ERROR'.

2014-01-26 23:59:00.01 spid54      The service account is 'WORKGROUP\AMAZONA-
NUQUUMV$'. This is an informational message; no user action is required.

2014-01-26 23:59:00.01 spid54      The error log has been reinitialized. See
the previous log for older entries.

2014-01-27 00:00:56.42 spid25s     This instance of SQL Server has been using
a process ID of 2976 since 10/21/2013 2:16:50 AM (local) 10/21/2013 2:16:50
AM (UTC). This is an informational message only; no user action is required.

2014-01-27 09:35:15.43 spid71      I/O is frozen on database model. No user
action is required. However, if I/O is not resumed promptly, you could
cancel the backup.

2014-01-27 09:35:15.44 spid72      I/O is frozen on database msdb. No user
action is required. However, if I/O is not resumed promptly, you could
cancel the backup.

2014-01-27 09:35:15.44 spid74      I/O is frozen on database rdsadmin. No
user action is required. However, if I/O is not resumed promptly, you could
cancel the backup.

2014-01-27 09:35:15.44 spid73      I/O is frozen on database master. No user
action is required. However, if I/O is not resumed promptly, you could
cancel the backup.

2014-01-27 09:35:25.57 spid73      I/O was resumed on database master. No
user action is required.

2014-01-27 09:35:25.57 spid74      I/O was resumed on database rdsadmin. No
user action is required.

2014-01-27 09:35:25.57 spid71      I/O was resumed on database model. No user
action is required.

2014-01-27 09:35:25.57 spid72      I/O was resumed on database msdb. No user
action is required.

</LogFileData>
```

```
<AdditionalDataPending>>false</AdditionalDataPending>
</DownloadDBLogFilePortionResult>
<ResponseMetadata>
  <RequestId>27143425-87ae-11e3-acc9-fb64b157268e</RequestId>
</ResponseMetadata>
</DownloadDBLogFilePortionResponse>
```


FailoverDBCluster

Forces a failover for a DB cluster.

A failover for a DB cluster promotes one of the Aurora Replicas (read-only instances) in the DB cluster to be the primary instance (the cluster writer).

Amazon Aurora will automatically fail over to an Aurora Replica, if one exists, when the primary instance fails. You can force a failover when you want to simulate a failure of a primary instance for testing. Because each instance in a DB cluster has its own endpoint address, you will need to clean up and re-establish any existing connections that use those endpoint addresses when the failover is complete.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

A DB cluster identifier to force a failover for. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

TargetDBInstanceIdentifier

The name of the instance to promote to the primary instance.

You must specify the instance identifier for an Aurora Replica in the DB cluster. For example, `mydbcluster-replica1`.

Type: String

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)
- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=FailoverDBCluster  
  &DBClusterIdentifier=sample-cluster  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-10-31  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20150323/us-east-1/rds/aws4_request  
  &X-Amz-Date=20150323T170232Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=9be705fa28a68244d5072722463a29a322f9ef8eb58a63c40a6f6547174dec44
```

Sample Response

```
<FailoverDBClusterResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">  
  <FailoverDBClusterResult>  
    <DBCluster>  
      <Port>3306</Port>  
      <LatestRestorableTime>2015-03-23T17:00:54.893Z</LatestRestorableTime>  
      <Engine>aurora</Engine>  
      <Status>available</Status>  
      <BackupRetentionPeriod>7</BackupRetentionPeriod>  
      <VpcSecurityGroups>  
        <VpcSecurityGroupMembership>  
          <Status>active</Status>  
          <VpcSecurityGroupId>sg-922dc2fd</VpcSecurityGroupId>  
        </VpcSecurityGroupMembership>  
      </VpcSecurityGroups>  
      <DBSubnetGroup>sample-group</DBSubnetGroup>  
      <EngineVersion>5.6.10a</EngineVersion>  
      <Endpoint>sample-cluster.cluster-claxbpgwvdf0.us-  
east-1.rds.amazonaws.com</Endpoint>  
      <DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>  
      <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>
```

```
<PreferredBackupWindow>05:47-06:17</PreferredBackupWindow>
<PreferredMaintenanceWindow>mon:10:16-mon:10:46</
PreferredMaintenanceWindow>
<EarliestRestorableTime>2015-03-04T23:08:59.159Z</
EarliestRestorableTime>
<DBClusterMembers>
  <DBClusterMember>
    <IsClusterWriter>>false</IsClusterWriter>
    <DBInstanceIdentifier>sample-replica1</DBInstanceIdentifier>
    <DBClusterParameterGroupStatus>in-sync</
DBClusterParameterGroupStatus>
  </DBClusterMember>
  <DBClusterMember>
    <IsClusterWriter>>true</IsClusterWriter>
    <DBInstanceIdentifier>sample-primary</DBInstanceIdentifier>
    <DBClusterParameterGroupStatus>in-sync</
DBClusterParameterGroupStatus>
  </DBClusterMember>
</DBClusterMembers>
<AllocatedStorage>1</AllocatedStorage>
<MasterUsername>awsuser</MasterUsername>
</DBCluster>
</FailoverDBClusterResult>
<ResponseMetadata>
  <RequestId>659c3dba-d17e-11e4-9fd0-35e9d88e2515</RequestId>
</ResponseMetadata>
</FailoverDBClusterResponse>
```

ListTagsForResource

Lists all tags on an Amazon RDS resource.

For an overview on tagging an Amazon RDS resource, see [Tagging Amazon RDS Resources](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

Filters.Filter.N

This parameter is not currently supported.

Type: array of [Filter \(p. 329\)](#) objects

Required: No

ResourceName

The Amazon RDS resource with tags to be listed. This value is an Amazon Resource Name (ARN). For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

TagList.Tag.N

List of tags returned by the ListTagsForResource operation.

Type: array of [Tag \(p. 354\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=ListTagsForResource  
&ResourceName=arn%3Aaws%3Ards%3Aus-west-2%3A12345678910%3Adb%3Asample-sql
```

```
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20160304/us-west-2/rds/aws4_request
&X-Amz-Date=20160304T205529Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=ad333e422a92110b6340a28a684f0ed78606cc48b29b25682df0173e04b93b85
```

Sample Response

```
<ListTagsForResourceResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <ListTagsForResourceResult>
    <TagList>
      <Tag>
        <Value>development-team</Value>
        <Key>owner</Key>
      </Tag>
      <Tag>
        <Value>test</Value>
        <Key>environment</Key>
      </Tag>
    </TagList>
  </ListTagsForResourceResult>
  <ResponseMetadata>
    <RequestId>71217a3c-e24b-11e5-a5e9-cad172f9e6c1</RequestId>
  </ResponseMetadata>
</ListTagsForResourceResponse>
```

ModifyDBCluster

Modify a setting for an Amazon Aurora DB cluster. You can change one or more database configuration parameters by specifying these parameters and the new values in the request. For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

ApplyImmediately

A value that specifies whether the modifications in this request and any pending modifications are asynchronously applied as soon as possible, regardless of the `PreferredMaintenanceWindow` setting for the DB cluster. If this parameter is set to `false`, changes to the DB cluster are applied during the next maintenance window.

The `ApplyImmediately` parameter only affects the `NewDBClusterIdentifier` and `MasterUserPassword` values. If you set the `ApplyImmediately` parameter value to `false`, then changes to the `NewDBClusterIdentifier` and `MasterUserPassword` values are applied during the next maintenance window. All other changes are applied immediately, regardless of the value of the `ApplyImmediately` parameter.

Default: `false`

Type: Boolean

Required: No

BackupRetentionPeriod

The number of days for which automated backups are retained. You must specify a minimum value of 1.

Default: 1

Constraints:

- Must be a value from 1 to 35

Type: Integer

Required: No

DBClusterIdentifier

The DB cluster identifier for the cluster being modified. This parameter is not case-sensitive.

Constraints:

- Must be the identifier for an existing DB cluster.
- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Type: String

Required: Yes

DBClusterParameterGroupName

The name of the DB cluster parameter group to use for the DB cluster.

Type: String

Required: No

MasterUserPassword

The new password for the master database user. This password can contain any printable ASCII character except `/`, `""`, or `@`.

Constraints: Must contain from 8 to 41 characters.

Type: String

Required: No

NewDBClusterIdentifier

The new DB cluster identifier for the DB cluster when renaming a DB cluster. This value is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-cluster2`

Type: String

Required: No

OptionGroupName

A value that indicates that the DB cluster should be associated with the specified option group. Changing this parameter does not result in an outage except in the following case, and the change is applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request. If the parameter change results in an option group that enables OEM, this change can cause a brief (sub-second) period during which new connections are rejected but existing connections are not interrupted.

Permanent options cannot be removed from an option group. The option group cannot be removed from a DB cluster once it is associated with a DB cluster.

Type: String

Required: No

Port

The port number on which the DB cluster accepts connections.

Constraints: Value must be 1150–65535

Default: The same port as the original DB cluster.

Type: Integer

Required: No

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled, using the `BackupRetentionPeriod` parameter.

Default: A 30-minute window selected at random from an 8-hour block of time per region. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Constraints:

- Must be in the format `hh24:mi-hh24:mi`.
- Times should be in Universal Coordinated Time (UTC).
- Must not conflict with the preferred maintenance window.
- Must be at least 30 minutes.

Type: String

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Format: `ddd:hh24:mi-ddd:hh24:mi`

Default: A 30-minute window selected at random from an 8-hour block of time per region, occurring on a random day of the week. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Valid Days: Mon, Tue, Wed, Thu, Fri, Sat, Sun

Constraints: Minimum 30-minute window.

Type: String

Required: No

VpcSecurityGroupIds.VpcSecurityGroupId.N

A list of VPC security groups that the DB cluster will belong to.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)
- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterAlreadyExistsFault

User already has a DB cluster with the given identifier.

HTTP Status Code: 400

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterParameterGroupNotFound

DBClusterParameterGroupName does not refer to an existing DB Cluster parameter group.

HTTP Status Code: 404

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

InvalidDBSecurityGroupState

The state of the DB security group does not allow deletion.

HTTP Status Code: 400

InvalidDBSubnetGroupStateFault

The DB subnet group cannot be deleted because it is in use.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=ModifyDBCluster  
&DBClusterIdentifier=sample-cluster3  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140725/us-east-1/rds/aws4_request  
&X-Amz-Date=20140725T161457Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=d6d1c65c2e94f5800ab411a3f7336625820b103713b6c063430900514e21d784
```

Sample Response

```
<ModifyDBClusterResponse xmlns="http://rds.amazonaws.com/doc/2014-10-31/">  
  <ModifyDBClusterResult>  
    <DBCluster>  
      <Engine>aurora5.6</Engine>  
      <Status>available</Status>  
      <BackupRetentionPeriod>0</BackupRetentionPeriod>  
      <DBSubnetGroup>my-subgroup</DBSubnetGroup>  
      <EngineVersion>5.6.10a</EngineVersion>  
      <Endpoint>sample-cluster3.cluster-cefgqfx9y5fy.us-  
east-1.rds.amazonaws.com</Endpoint>  
      <DBClusterIdentifier>sample-cluster3</DBClusterIdentifier>  
      <PreferredBackupWindow>07:06-07:36</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>tue:10:18-tue:10:48</  
PreferredMaintenanceWindow>  
      <DBClusterMembers>  
        <DBClusterMember>  
          <IsClusterWriter>>true</IsClusterWriter>  
          <DBInstanceIdentifier>sample-cluster3-master</DBInstanceIdentifier>
```

```
</DBClusterMember>
<DBClusterMember>
  <IsClusterWriter>>false</IsClusterWriter>
  <DBInstanceIdentifier>sample-cluster3-read1</DBInstanceIdentifier>
</DBClusterMember>
</DBClusterMembers>
<AllocatedStorage>15</AllocatedStorage>
<MasterUsername>awsuser</MasterUsername>
</DBCluster>
</ModifyDBClusterResult>
<ResponseMetadata>
  <RequestId>d2cd0e2f-1416-11e4-9210-cf99df4125d0</RequestId>
</ResponseMetadata>
</ModifyDBClusterResponse>
```

ModifyDBClusterParameterGroup

Modifies the parameters of a DB cluster parameter group. To modify more than one parameter, submit a list of the following: `ParameterName`, `ParameterValue`, and `ApplyMethod`. A maximum of 20 parameters can be modified in a single request.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Note

Changes to dynamic parameters are applied immediately. Changes to static parameters require a reboot without failover to the DB cluster associated with the parameter group before the change can take effect.

Important

After you create a DB cluster parameter group, you should wait at least 5 minutes before creating your first DB cluster that uses that DB cluster parameter group as the default parameter group. This allows Amazon RDS to fully complete the create action before the parameter group is used as the default for a new DB cluster. This is especially important for parameters that are critical when creating the default database for a DB cluster, such as the character set for the default database defined by the `character_set_database` parameter. You can use the *Parameter Groups* option of the [Amazon RDS console](#) or the [DescribeDBClusterParameters](#) (p. 109) command to verify that your DB cluster parameter group has been created or modified.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterParameterGroupName

The name of the DB cluster parameter group to modify.

Type: String

Required: Yes

Parameters.Parameter.N

A list of parameters in the DB cluster parameter group to modify.

Type: array of [Parameter](#) (p. 342) objects

Required: Yes

Response Elements

The following element is returned by the service.

DBClusterParameterGroupName

The name of the DB cluster parameter group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Note

This value is stored as a lowercase string.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=ModifyDBClusterParameterGroup
&DBClusterParameterGroupName=sample-cluster-pg
&Parameters.member.1.ApplyMethod=pending-reboot
&Parameters.member.1.ParameterName=binlog_format
&Parameters.member.1.ParameterValue=MIXED
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request
&X-Amz-Date=20160913T173245Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=cfb4f35de32455f77405636315dd431f2e236a1a997f94e0f6e00183d1f5156e
```

Sample Response

```
<ModifyDBClusterParameterGroupResponse xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <ModifyDBClusterParameterGroupResult>
    <DBClusterParameterGroupName>sample-cluster-pg</
DBClusterParameterGroupName>
  </ModifyDBClusterParameterGroupResult>
  <ResponseMetadata>
    <RequestId>1534d6a1-79d8-11e6-9b94-838991bd50c6</RequestId>
  </ResponseMetadata>
</ModifyDBClusterParameterGroupResponse>
```

ModifyDBClusterSnapshotAttribute

Adds an attribute and values to, or removes an attribute and values from, a manual DB cluster snapshot.

To share a manual DB cluster snapshot with other AWS accounts, specify `restore` as the `AttributeName` and use the `ValuesToAdd` parameter to add a list of IDs of the AWS accounts that are authorized to restore the manual DB cluster snapshot. Use the value `all` to make the manual DB cluster snapshot public, which means that it can be copied or restored by all AWS accounts. Do not add the `all` value for any manual DB cluster snapshots that contain private information that you don't want available to all AWS accounts.

To view which AWS accounts have access to copy or restore a manual DB cluster snapshot, or whether a manual DB cluster snapshot public or private, use the [DescribeDBClusterSnapshotAttributes \(p. 115\)](#) API action.

If a manual DB cluster snapshot is encrypted, it cannot be shared.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

AttributeName

The name of the DB cluster snapshot attribute to modify.

To manage authorization for other AWS accounts to copy or restore a manual DB cluster snapshot, set this value to `restore`.

Type: String

Required: Yes

DBClusterSnapshotIdentifier

The identifier for the DB cluster snapshot to modify the attributes for.

Type: String

Required: Yes

ValuesToAdd.AttributeValue.N

A list of DB cluster snapshot attributes to add to the attribute specified by `AttributeName`.

To authorize other AWS accounts to copy or restore a manual DB cluster snapshot, set this list to include one or more AWS account IDs, or `all` to make the manual DB cluster snapshot restorable by any AWS account. Do not add the `all` value for any manual DB cluster snapshots that contain private information that you don't want available to all AWS accounts.

Type: array of Strings

Required: No

ValuesToRemove.AttributeValue.N

A list of DB cluster snapshot attributes to remove from the attribute specified by `AttributeName`.

To remove authorization for other AWS accounts to copy or restore a manual DB cluster snapshot, set this list to include one or more AWS account identifiers, or `all` to remove authorization for any AWS account to copy or restore the DB cluster snapshot. If you specify `all`, an AWS account whose account ID is explicitly added to the `restore` attribute can still copy or restore a manual DB cluster snapshot.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBClusterSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBClusterSnapshotAttributes](#) (p. 115) API action.

Manual DB cluster snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB cluster snapshot. For more information, see the [ModifyDBClusterSnapshotAttribute](#) (p. 201) API action.

Type: [DBClusterSnapshotAttributesResult](#) (p. 302) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

SharedSnapshotQuotaExceeded

You have exceeded the maximum number of accounts that you can share a manual DB snapshot with.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=ModifyDBClusterSnapshotAttribute  
&AttributeName=restore  
&DBClusterSnapshotIdentifier>manual-cluster-snapshot1  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&ValuesToAdd.member.1=123451234512  
&ValuesToAdd.member.2=123456789012  
&ValuesToRemove.member.1=all  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20150922/us-west-2/rds/aws4_request  
&X-Amz-Date=20150922T220515Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=ef38f1ce3dab4e1dbf113d8d2a265c67d17ece1999ffd36be85714ed36dddbb3
```

Sample Response

```
<ModifyDBClusterSnapshotAttributeResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ModifyDBClusterSnapshotAttributeResult>
```

```
<DBClusterSnapshotAttributesResult>
  <DBClusterSnapshotAttributes>
    <DBClusterSnapshotAttribute>
      <AttributeName>restore</AttributeName>
      <AttributeValues>
        <AttributeValue>123451234512</AttributeValue>
        <AttributeValue>123456789012</AttributeValue>
      </AttributeValues>
    </DBClusterSnapshotAttribute>
  </DBClusterSnapshotAttributes>
  <DBClusterSnapshotIdentifier>manual-cluster-snapshot1</
DBSnapshotIdentifier>
</DBClusterSnapshotAttributesResult>
</ModifyDBClusterSnapshotAttributeResult>
<ResponseMetadata>
  <RequestId>0122a108-2276-11e5-9cc3-0f535cff56aa</RequestId>
</ResponseMetadata>
</ModifyDBClusterSnapshotAttributeResponse>
```

ModifyDBInstance

Modifies settings for a DB instance. You can change one or more database configuration parameters by specifying these parameters and the new values in the request.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

AllocatedStorage

The new storage capacity of the RDS instance. Changing this setting does not result in an outage and the change is applied during the next maintenance window unless `ApplyImmediately` is set to `true` for this request.

MySQL

Default: Uses existing setting

Valid Values: 5-6144

Constraints: Value supplied must be at least 10% greater than the current value. Values that are not at least 10% greater than the existing value are rounded up so that they are 10% greater than the current value.

Type: Integer

MariaDB

Default: Uses existing setting

Valid Values: 5-6144

Constraints: Value supplied must be at least 10% greater than the current value. Values that are not at least 10% greater than the existing value are rounded up so that they are 10% greater than the current value.

Type: Integer

PostgreSQL

Default: Uses existing setting

Valid Values: 5-6144

Constraints: Value supplied must be at least 10% greater than the current value. Values that are not at least 10% greater than the existing value are rounded up so that they are 10% greater than the current value.

Type: Integer

Oracle

Default: Uses existing setting

Valid Values: 10-6144

Constraints: Value supplied must be at least 10% greater than the current value. Values that are not at least 10% greater than the existing value are rounded up so that they are 10% greater than the current value.

SQL Server

Cannot be modified.

If you choose to migrate your DB instance from using standard storage to using Provisioned IOPS, or from using Provisioned IOPS to using standard storage, the process can take time. The duration of the migration depends on several factors such as database load, storage size, storage type (standard or Provisioned IOPS), amount of IOPS provisioned (if any), and the number of prior scale storage operations. Typical migration times are under 24 hours, but the process can take up to several days in some cases. During the migration, the DB instance will be available for use, but might experience performance degradation. While the migration takes place, nightly backups for the instance will be suspended. No other Amazon RDS operations can take place for the instance, including modifying the instance, rebooting the instance, deleting the instance, creating a Read Replica for the instance, and creating a DB snapshot of the instance.

Type: Integer

Required: No

AllowMajorVersionUpgrade

Indicates that major version upgrades are allowed. Changing this parameter does not result in an outage and the change is asynchronously applied as soon as possible.

Constraints: This parameter must be set to `true` when specifying a value for the `EngineVersion` parameter that is a different major version than the DB instance's current version.

Type: Boolean

Required: No

ApplyImmediately

Specifies whether the modifications in this request and any pending modifications are asynchronously applied as soon as possible, regardless of the `PreferredMaintenanceWindow` setting for the DB instance.

If this parameter is set to `false`, changes to the DB instance are applied during the next maintenance window. Some parameter changes can cause an outage and will be applied on the next call to [RebootDBInstance](#) (p. 238), or the next failure reboot. Review the table of parameters in [Modifying a DB Instance and Using the Apply Immediately Parameter](#) to see the impact that setting `ApplyImmediately` to `true` or `false` has for each modified parameter and to determine when the changes will be applied.

Default: `false`

Type: Boolean

Required: No

AutoMinorVersionUpgrade

Indicates that minor version upgrades will be applied automatically to the DB instance during the maintenance window. Changing this parameter does not result in an outage except in the following case and the change is asynchronously applied as soon as possible. An outage will result if this parameter is set to `true` during the maintenance window, and a newer minor version is available, and RDS has enabled auto patching for that engine version.

Type: Boolean

Required: No

BackupRetentionPeriod

The number of days to retain automated backups. Setting this parameter to a positive number enables backups. Setting this parameter to 0 disables automated backups.

Changing this parameter can result in an outage if you change from 0 to a non-zero value or from a non-zero value to 0. These changes are applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request. If you change the parameter from one non-zero value to another non-zero value, the change is asynchronously applied as soon as possible.

Default: Uses existing setting

Constraints:

- Must be a value from 0 to 35
- Can be specified for a MySQL Read Replica only if the source is running MySQL 5.6
- Can be specified for a PostgreSQL Read Replica only if the source is running PostgreSQL 9.3.5
- Cannot be set to 0 if the DB instance is a source to Read Replicas

Type: Integer

Required: No

CACertificateIdentifier

Indicates the certificate that needs to be associated with the instance.

Type: String

Required: No

CopyTagsToSnapshot

True to copy all tags from the DB instance to snapshots of the DB instance; otherwise false. The default is false.

Type: Boolean

Required: No

DBInstanceClass

The new compute and memory capacity of the DB instance. To determine the instance classes that are available for a particular DB engine, use the [DescribeOrderableDBInstanceOptions](#) (p. 171) action.

Passing a value for this setting causes an outage during the change and is applied during the next maintenance window, unless `ApplyImmediately` is specified as `true` for this request.

Default: Uses existing setting

Valid Values: `db.t1.micro` | `db.m1.small` | `db.m1.medium` | `db.m1.large` | `db.m1.xlarge` | `db.m2.xlarge` | `db.m2.2xlarge` | `db.m2.4xlarge` | `db.m3.medium` | `db.m3.large` | `db.m3.xlarge` | `db.m3.2xlarge` | `db.m4.large` | `db.m4.xlarge` | `db.m4.2xlarge` | `db.m4.4xlarge` | `db.m4.10xlarge` | `db.r3.large` | `db.r3.xlarge` | `db.r3.2xlarge` | `db.r3.4xlarge` | `db.r3.8xlarge` | `db.t2.micro` | `db.t2.small` | `db.t2.medium` | `db.t2.large`

Type: String

Required: No

DBInstanceIdentifier

The DB instance identifier. This value is stored as a lowercase string.

Constraints:

- Must be the identifier for an existing DB instance
- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

DBParameterGroupName

The name of the DB parameter group to apply to the DB instance. Changing this setting does not result in an outage. The parameter group name itself is changed immediately, but the actual parameter changes are not applied until you reboot the instance without failover. The db instance will NOT be rebooted automatically and the parameter changes will NOT be applied during the next maintenance window.

Default: Uses existing setting

Constraints: The DB parameter group must be in the same DB parameter group family as this DB instance.

Type: String

Required: No

DBPortNumber

The port number on which the database accepts connections.

The value of the `DBPortNumber` parameter must not match any of the port values specified for options in the option group for the DB instance.

Your database will restart when you change the `DBPortNumber` value regardless of the value of the `ApplyImmediately` parameter.

MySQL

Default: 3306

Valid Values: 1150-65535

MariaDB

Default: 3306

Valid Values: 1150-65535

PostgreSQL

Default: 5432

Valid Values: 1150-65535

Type: Integer

Oracle

Default: 1521

Valid Values: 1150-65535

SQL Server

Default: 1433

Valid Values: 1150-65535 except for 1434, 3389, 47001, 49152, and 49152 through 49156.

Amazon Aurora

Default: 3306

Valid Values: 1150-65535

Type: Integer

Required: No

DBSecurityGroups.DBSecurityGroupName.N

A list of DB security groups to authorize on this DB instance. Changing this setting does not result in an outage and the change is asynchronously applied as soon as possible.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: array of Strings

Required: No

DBSubnetGroupName

The new DB subnet group for the DB instance. You can use this parameter to move your DB instance to a different VPC. If your DB instance is not in a VPC, you can also use this parameter to move your DB instance into a VPC. For more information, see [Updating the VPC for a DB Instance](#).

Changing the subnet group causes an outage during the change. The change is applied during the next maintenance window, unless you specify `true` for the `ApplyImmediately` parameter.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens.

Example: `mySubnetGroup`

Type: String

Required: No

Domain

The Active Directory Domain to move the instance to. Specify `none` to remove the instance from its current domain. The domain must be created prior to this operation. Currently only a Microsoft SQL Server instance can be created in a Active Directory Domain.

Type: String

Required: No

DomainIAMRoleName

The name of the IAM role to use when making API calls to the Directory Service.

Type: String

Required: No

EngineVersion

The version number of the database engine to upgrade to. Changing this parameter results in an outage and the change is applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request.

For major version upgrades, if a non-default DB parameter group is currently in use, a new DB parameter group in the DB parameter group family for the new engine version must be specified. The new DB parameter group can be the default for that DB parameter group family.

For a list of valid engine versions, see [CreateDBInstance \(p. 42\)](#).

Type: String

Required: No

IOPS

The new Provisioned IOPS (I/O operations per second) value for the RDS instance. Changing this setting does not result in an outage and the change is applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request.

Default: Uses existing setting

Constraints: Value supplied must be at least 10% greater than the current value. Values that are not at least 10% greater than the existing value are rounded up so that they are 10% greater than the current value. If you are migrating from Provisioned IOPS to standard storage, set this value to 0. The DB instance will require a reboot for the change in storage type to take effect.

SQL Server

Setting the IOPS value for the SQL Server database engine is not supported.

Type: Integer

If you choose to migrate your DB instance from using standard storage to using Provisioned IOPS, or from using Provisioned IOPS to using standard storage, the process can take time. The duration of the migration depends on several factors such as database load, storage size, storage type (standard or Provisioned IOPS), amount of IOPS provisioned (if any), and the number of prior scale storage operations. Typical migration times are under 24 hours, but the process can take up to several days in some cases. During the migration, the DB instance will be available for use, but might experience performance degradation. While the migration takes place, nightly backups for the instance will be suspended. No other Amazon RDS operations can take place for the instance, including modifying the instance, rebooting the instance, deleting the instance, creating a Read Replica for the instance, and creating a DB snapshot of the instance.

Type: Integer

Required: No

LicenseModel

The license model for the DB instance.

Valid values: `license-included` | `bring-your-own-license` | `general-public-license`

Type: String

Required: No

MasterUserPassword

The new password for the DB instance master user. Can be any printable ASCII character except `/`, `""`, or `@`.

Changing this parameter does not result in an outage and the change is asynchronously applied as soon as possible. Between the time of the request and the completion of the request, the `MasterUserPassword` element exists in the `PendingModifiedValues` element of the operation response.

Default: Uses existing setting

Constraints: Must be 8 to 41 alphanumeric characters (MySQL, MariaDB, and Amazon Aurora), 8 to 30 alphanumeric characters (Oracle), or 8 to 128 alphanumeric characters (SQL Server).

Note

Amazon RDS API actions never return the password, so this action provides a way to regain access to a primary instance user if the password is lost. This includes restoring privileges that might have been accidentally revoked.

Type: String

Required: No

MonitoringInterval

The interval, in seconds, between points when Enhanced Monitoring metrics are collected for the DB instance. To disable collecting Enhanced Monitoring metrics, specify 0. The default is 0.

If `MonitoringRoleArn` is specified, then you must also set `MonitoringInterval` to a value other than 0.

Valid Values: 0, 1, 5, 10, 15, 30, 60

Type: Integer

Required: No

MonitoringRoleArn

The ARN for the IAM role that permits RDS to send enhanced monitoring metrics to CloudWatch Logs. For example, `arn:aws:iam:123456789012:role/emaccess`. For information on creating a monitoring role, go to [To create an IAM role for Amazon RDS Enhanced Monitoring](#).

If `MonitoringInterval` is set to a value other than 0, then you must supply a `MonitoringRoleArn` value.

Type: String

Required: No

MultiAZ

Specifies if the DB instance is a Multi-AZ deployment. Changing this parameter does not result in an outage and the change is applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request.

Constraints: Cannot be specified if the DB instance is a Read Replica.

Type: Boolean

Required: No

NewDBInstanceIdentifier

The new DB instance identifier for the DB instance when renaming a DB instance. When you change the DB instance identifier, an instance reboot will occur immediately if you set `ApplyImmediately` to `true`, or will occur during the next maintenance window if `ApplyImmediately` to `false`. This value is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

OptionGroupName

Indicates that the DB instance should be associated with the specified option group. Changing this parameter does not result in an outage except in the following case and the change is applied during the next maintenance window unless the `ApplyImmediately` parameter is set to `true` for this request. If the parameter change results in an option group that enables OEM, this change can cause a brief (sub-second) period during which new connections are rejected but existing connections are not interrupted.

Permanent options, such as the TDE option for Oracle Advanced Security TDE, cannot be removed from an option group, and that option group cannot be removed from a DB instance once it is associated with a DB instance

Type: String

Required: No

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled, as determined by the `BackupRetentionPeriod` parameter. Changing this parameter does not result in an outage and the change is asynchronously applied as soon as possible.

Constraints:

- Must be in the format hh24:mi-hh24:mi
- Times should be in Universal Time Coordinated (UTC)
- Must not conflict with the preferred maintenance window
- Must be at least 30 minutes

Type: String

Required: No

PreferredMaintenanceWindow

The weekly time range (in UTC) during which system maintenance can occur, which might result in an outage. Changing this parameter does not result in an outage, except in the following situation, and the change is asynchronously applied as soon as possible. If there are pending actions that cause a reboot, and the maintenance window is changed to include the current time, then changing this parameter will cause a reboot of the DB instance. If moving this window to the current time, there must be at least 30 minutes between the current time and end of the window to ensure pending changes are applied.

Default: Uses existing setting

Format: ddd:hh24:mi-ddd:hh24:mi

Valid Days: Mon | Tue | Wed | Thu | Fri | Sat | Sun

Constraints: Must be at least 30 minutes

Type: String

Required: No

PromotionTier

A value that specifies the order in which an Aurora Replica is promoted to the primary instance after a failure of the existing primary instance. For more information, see [Fault Tolerance for an Aurora DB Cluster](#).

Default: 1

Valid Values: 0 - 15

Type: Integer

Required: No

PubliclyAccessible

Boolean value that indicates if the DB instance has a publicly resolvable DNS name. Set to `True` to make the DB instance Internet-facing with a publicly resolvable DNS name, which resolves to a public IP address. Set to `False` to make the DB instance internal with a DNS name that resolves to a private IP address.

`PubliclyAccessible` only applies to DB instances in a VPC. The DB instance must be part of a public subnet and `PubliclyAccessible` must be true in order for it to be publicly accessible.

Changes to the `PubliclyAccessible` parameter are applied immediately regardless of the value of the `ApplyImmediately` parameter.

Default: false

Type: Boolean

Required: No

StorageType

Specifies the storage type to be associated with the DB instance.

Valid values: `standard` | `gp2` | `io1`

If you specify `io1`, you must also include a value for the `Iops` parameter.

Default: `io1` if the `Iops` parameter is specified; otherwise `standard`

Type: String

Required: No

TdeCredentialArn

The ARN from the Key Store with which to associate the instance for TDE encryption.

Type: String

Required: No

TdeCredentialPassword

The password for the given ARN from the Key Store in order to access the device.

Type: String

Required: No

VpcSecurityGroupIds.VpcSecurityGroupIds.N

A list of EC2 VPC security groups to authorize on this DB instance. This change is asynchronously applied as soon as possible.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance](#) (p. 42)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)

This data type is used as a response element in the [DescribeDBInstances](#) (p. 124) action.

Type: [DBInstance](#) (p. 304) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

AuthorizationNotFound

Specified CIDRIP or EC2 security group is not authorized for the specified DB security group. RDS may not also be authorized via IAM to perform necessary actions on your behalf.

HTTP Status Code: 404

CertificateNotFound

CertificateIdentifier does not refer to an existing certificate.

HTTP Status Code: 404

DBInstanceAlreadyExists

User already has a DB instance with the given identifier.

HTTP Status Code: 400

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

DBUpgradeDependencyFailure

The DB upgrade failed because a resource the DB depends on could not be modified.

HTTP Status Code: 400

DomainNotFoundFault

Domain does not refer to an existing Active Directory Domain.

HTTP Status Code: 404

InsufficientDBInstanceCapacity

Specified DB instance class is not available in the specified Availability Zone.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

InvalidDBSecurityGroupState

The state of the DB security group does not allow deletion.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

ProvisionedIopsNotAvailableInAZFault

Provisioned IOPS not available in the specified Availability Zone.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageTypeNotSupported

StorageType specified cannot be associated with the DB Instance.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=ModifyDBInstance  
&AllocatedStorage=20  
&DBInstanceIdentifier=myawsuser-dbi04  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
&X-Amz-Date=20140425T192732Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date
```



```
&X-Amz-  
Signature=1dc9dd716f4855e9bdf188c70f1cf9f6251b070b68b81103b59ec70c3e7854b3
```

Sample Response

```
<ModifyDBInstanceResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <ModifyDBInstanceResult>  
    <DBInstance>  
      <BackupRetentionPeriod>7</BackupRetentionPeriod>  
      <DBInstanceStatus>available</DBInstanceStatus>  
      <MultiAZ>true</MultiAZ>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>myawsuser-dbi04</DBInstanceIdentifier>  
      <PreferredBackupWindow>10:03-10:33</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>wed:03:32-wed:04:02</  
PreferredMaintenanceWindow>  
      <AvailabilityZone>us-east-1a</AvailabilityZone>  
      <ReadReplicaDBInstanceIdentifiers/>  
      <LatestRestorableTime>2014-04-25T19:25:00Z</LatestRestorableTime>  
      <Engine>mysql</Engine>  
      <PendingModifiedValues>  
        <AllocatedStorage>20</AllocatedStorage>  
      </PendingModifiedValues>  
      <LicenseModel>general-public-license</LicenseModel>  
      <DBParameterGroups>  
        <DBParameterGroup>  
          <ParameterApplyStatus>in-sync</ParameterApplyStatus>  
          <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>  
        </DBParameterGroup>  
      </DBParameterGroups>  
      <Endpoint>  
        <Port>3306</Port>  
        <Address>myawsuser-dbi04.cg037hpkuyjt.us-east-1.rds.amazonaws.com</  
Address>  
      </Endpoint>  
      <EngineVersion>5.6.13</EngineVersion>  
      <SecondaryAvailabilityZone>us-east-1b</SecondaryAvailabilityZone>  
      <OptionGroupMemberships>  
        <OptionGroupMembership>  
          <OptionGroupName>default:mysql-5-6</OptionGroupName>  
          <Status>in-sync</Status>  
        </OptionGroupMembership>  
      </OptionGroupMemberships>  
      <PubliclyAccessible>true</PubliclyAccessible>  
      <DBSecurityGroups>  
        <DBSecurityGroup>  
          <Status>active</Status>  
          <DBSecurityGroupName>default</DBSecurityGroupName>  
        </DBSecurityGroup>  
      </DBSecurityGroups>  
      <DBName>myawsuser_db04</DBName>  
      <AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>  
      <InstanceCreateTime>2014-04-25T18:07:51.508Z</InstanceCreateTime>  
      <AllocatedStorage>15</AllocatedStorage>  
      <MasterUsername>myawsuser</MasterUsername>  
      <DBInstanceClass>db.m1.small</DBInstanceClass>
```

```
</DBInstance>  
</ModifyDBInstanceResult>  
<ResponseMetadata>  
  <RequestId>f643f1ac-bbfe-11d3-f4c6-37db295f7674</RequestId>  
</ResponseMetadata>  
</ModifyDBInstanceResponse>
```

ModifyDBParameterGroup

Modifies the parameters of a DB parameter group. To modify more than one parameter, submit a list of the following: `ParameterName`, `ParameterValue`, and `ApplyMethod`. A maximum of 20 parameters can be modified in a single request.

Note

Changes to dynamic parameters are applied immediately. Changes to static parameters require a reboot without failover to the DB instance associated with the parameter group before the change can take effect.

Important

After you modify a DB parameter group, you should wait at least 5 minutes before creating your first DB instance that uses that DB parameter group as the default parameter group. This allows Amazon RDS to fully complete the modify action before the parameter group is used as the default for a new DB instance. This is especially important for parameters that are critical when creating the default database for a DB instance, such as the character set for the default database defined by the `character_set_database` parameter. You can use the *Parameter Groups* option of the [Amazon RDS console](#) or the `DescribeDBParameters` command to verify that your DB parameter group has been created or modified.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupName

The name of the DB parameter group.

Constraints:

- Must be the name of an existing DB parameter group
- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Parameters.Parameter.N

An array of parameter names, values, and the apply method for the parameter update. At least one parameter name, value, and apply method must be supplied; subsequent arguments are optional. A maximum of 20 parameters can be modified in a single request.

Valid Values (for the application method): `immediate` | `pending-reboot`

Note

You can use the `immediate` value with dynamic parameters only. You can use the `pending-reboot` value for both dynamic and static parameters, and changes are applied when you reboot the DB instance without failover.

Type: array of [Parameter](#) (p. 342) objects

Required: Yes

Response Elements

The following element is returned by the service.

DBParameterGroupName

Provides the name of the DB parameter group.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=ModifyDBParameterGroup  
  &DBParameterGroupName=mydbparametergroup01  
  &Parameters.member.1.ApplyMethod=immediate  
  &Parameters.member.1.ParameterName=binlog_cache_size  
  &Parameters.member.1.ParameterValue=65536  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140425T193811Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=afd9acfee876360dd294189465aca26502343d405292dc6e43b1961ad4d1d7e2
```

Sample Response

```
<ModifyDBParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ModifyDBParameterGroupResult>  
    <DBParameterGroupName>mydbparametergroup01</DBParameterGroupName>  
  </ModifyDBParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>12d7435e-bba0-11d3-fe11-33d33a9bb7e3</RequestId>  
  </ResponseMetadata>  
</ModifyDBParameterGroupResponse>
```

ModifyDBSnapshotAttribute

Adds an attribute and values to, or removes an attribute and values from, a manual DB snapshot.

To share a manual DB snapshot with other AWS accounts, specify `restore` as the `AttributeName` and use the `ValuesToAdd` parameter to add a list of IDs of the AWS accounts that are authorized to restore the manual DB snapshot. Uses the value `all` to make the manual DB snapshot public, which means it can be copied or restored by all AWS accounts. Do not add the `all` value for any manual DB snapshots that contain private information that you don't want available to all AWS accounts.

To view which AWS accounts have access to copy or restore a manual DB snapshot, or whether a manual DB snapshot public or private, use the [DescribeDBSnapshotAttributes \(p. 139\)](#) API action.

If the manual DB snapshot is encrypted, it cannot be shared.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

AttributeName

The name of the DB snapshot attribute to modify.

To manage authorization for other AWS accounts to copy or restore a manual DB snapshot, set this value to `restore`.

Type: String

Required: Yes

DBSnapshotIdentifier

The identifier for the DB snapshot to modify the attributes for.

Type: String

Required: Yes

ValuesToAdd.AttributeValue.N

A list of DB snapshot attributes to add to the attribute specified by `AttributeName`.

To authorize other AWS accounts to copy or restore a manual snapshot, set this list to include one or more AWS account IDs, or `all` to make the manual DB snapshot restorable by any AWS account. Do not add the `all` value for any manual DB snapshots that contain private information that you don't want available to all AWS accounts.

Type: array of Strings

Required: No

ValuesToRemove.AttributeValue.N

A list of DB snapshot attributes to remove from the attribute specified by `AttributeName`.

To remove authorization for other AWS accounts to copy or restore a manual snapshot, set this list to include one or more AWS account identifiers, or `all` to remove authorization for any AWS account to copy or restore the DB snapshot. If you specify `all`, an AWS account whose account ID is explicitly added to the `restore` attribute can still copy or restore the manual DB snapshot.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBSnapshotAttributes \(p. 139\)](#) API action.

Manual DB snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB snapshot. For more information, see the [ModifyDBSnapshotAttribute \(p. 217\)](#) API action.

Type: [DBSnapshotAttributesResult](#) (p. 318) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

SharedSnapshotQuotaExceeded

You have exceeded the maximum number of accounts that you can share a manual DB snapshot with.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=ModifyDBSnapshotAttribute  
&AttributeName=restore  
&DBSnapshotIdentifier>manual-snapshot1  
&SignatureMethod=HmacSHA256&SignatureVersion=4  
&ValuesToAdd.member.1=123451234512  
&ValuesToAdd.member.2=123456789012  
&ValuesToRemove.member.1=all  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20150922/us-west-2/rds/aws4_request  
&X-Amz-Date=20150922T220515Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=ef38f1ce3dab4e1dbf113d8d2a265c67d17ece1999ffd36be85714ed36dddbb3
```

Sample Response

```
<ModifyDBSnapshotAttributeResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ModifyDBSnapshotAttributeResult>  
    <DBSnapshotAttributesResult>  
      <DBSnapshotAttributes>  
        <DBSnapshotAttribute>  
          <AttributeName>restore</AttributeName>  
          <AttributeValues>  
            <AttributeValue>123451234512</AttributeValue>  
            <AttributeValue>123456789012</AttributeValue>
```

```
        </AttributeValues>
      </DBSnapshotAttribute>
    </DBSnapshotAttributes>
    <DBSnapshotIdentifier>manual-snapshot1</DBSnapshotIdentifier>
  </DBSnapshotAttributesResult>
</ModifyDBSnapshotAttributeResult>
<ResponseMetadata>
  <RequestId>0122a108-2276-11e5-9cc3-0f535cff56aa</RequestId>
</ResponseMetadata>
</ModifyDBSnapshotAttributeResponse>
```

ModifyDBSubnetGroup

Modifies an existing DB subnet group. DB subnet groups must contain at least one subnet in at least two AZs in the region.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBSubnetGroupDescription

The description for the DB subnet group.

Type: String

Required: No

DBSubnetGroupName

The name for the DB subnet group. This value is stored as a lowercase string.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: Yes

SubnetIds.SubnetIdentifier.N

The EC2 subnet IDs for the DB subnet group.

Type: array of Strings

Required: Yes

Response Elements

The following element is returned by the service.

DBSubnetGroup

Contains the result of a successful invocation of the following actions:

- [CreateDBSubnetGroup](#) (p. 69)
- [ModifyDBSubnetGroup](#) (p. 220)
- [DescribeDBSubnetGroups](#) (p. 145)
- [DeleteDBSubnetGroup](#) (p. 95)

This data type is used as a response element in the [DescribeDBSubnetGroups](#) (p. 145) action.

Type: [DBSubnetGroup](#) (p. 319) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DBSubnetQuotaExceededFault

Request would result in user exceeding the allowed number of subnets in a DB subnet groups.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

SubnetAlreadyInUse

The DB subnet is already in use in the Availability Zone.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=ModifyDBSubnetGroup  
&DBSubnetGroupDescription=A%20new%20Description  
&DBSubnetGroupName=myawsuser-sngrp  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SubnetIds.member.1=subnet-e4d398a1  
&SubnetIds.member.2=subnet-c2bdb6ba  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140425/us-east-1/rds/aws4_request  
&X-Amz-Date=20140425T200214Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=213c429d925cb1608fc13a1dde48715bcac3b0794536ee90beac34203265f9af
```

Sample Response

```
<ModifyDBSubnetGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ModifyDBSubnetGroupResult>  
    <DBSubnetGroup>  
      <VpcId>vpc-33ac97ea</VpcId>  
      <SubnetGroupStatus>Complete</SubnetGroupStatus>  
      <DBSubnetGroupDescription>A new Description</DBSubnetGroupDescription>  
      <DBSubnetGroupName>myawsuser-sngrp</DBSubnetGroupName>  
      <Subnets>  
        <Subnet>  
          <SubnetStatus>Active</SubnetStatus>  
          <SubnetIdentifier>subnet-e4d398a1</SubnetIdentifier>  
          <SubnetAvailabilityZone>  
            <Name>us-east-1b</Name>  
            <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>  
          </SubnetAvailabilityZone>  
        </Subnet>  
        <Subnet>  
          <SubnetStatus>Active</SubnetStatus>  
          <SubnetIdentifier>subnet-c2bdb6ba</SubnetIdentifier>
```

```
<SubnetAvailabilityZone>
  <Name>us-east-1c</Name>
  <ProvisionedIopsCapable>>false</ProvisionedIopsCapable>
</SubnetAvailabilityZone>
</Subnet>
</Subnets>
</DBSubnetGroup>
</ModifyDBSubnetGroupResult>
<ResponseMetadata>
  <RequestId>6dd028be-bba3-11d3-f4c6-37db295f7674</RequestId>
</ResponseMetadata>
</ModifyDBSubnetGroupResponse>
```

ModifyEventSubscription

Modifies an existing RDS event notification subscription. Note that you cannot modify the source identifiers using this call; to change source identifiers for a subscription, use the [AddSourceIdentifierToSubscription \(p. 7\)](#) and [RemoveSourceIdentifierFromSubscription \(p. 243\)](#) calls.

You can see a list of the event categories for a given SourceType in the [Events](#) topic in the Amazon RDS User Guide or by using the **DescribeEventCategories** action.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

Enabled

A Boolean value; set to **true** to activate the subscription.

Type: Boolean

Required: No

EventCategories.EventCategory.N

A list of event categories for a SourceType that you want to subscribe to. You can see a list of the categories for a given SourceType in the [Events](#) topic in the Amazon RDS User Guide or by using the **DescribeEventCategories** action.

Type: array of Strings

Required: No

SnsTopicArn

The Amazon Resource Name (ARN) of the SNS topic created for event notification. The ARN is created by Amazon SNS when you create a topic and subscribe to it.

Type: String

Required: No

SourceType

The type of source that will be generating the events. For example, if you want to be notified of events generated by a DB instance, you would set this parameter to db-instance. If this value is not specified, all events are returned.

Valid values: db-instance | db-parameter-group | db-security-group | db-snapshot

Type: String

Required: No

SubscriptionName

The name of the RDS event notification subscription.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions \(p. 159\)](#) action.

Type: [EventSubscription \(p. 327\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

EventSubscriptionQuotaExceeded

You have reached the maximum number of event subscriptions.

HTTP Status Code: 400

SNSInvalidTopic

SNS has responded that there is a problem with the SNS topic specified.

HTTP Status Code: 400

SNSNoAuthorization

You do not have permission to publish to the SNS topic ARN.

HTTP Status Code: 400

SNSTopicArnNotFound

The SNS topic ARN does not exist.

HTTP Status Code: 404

SubscriptionCategoryNotFound

The supplied category does not exist.

HTTP Status Code: 404

SubscriptionNotFound

The subscription name does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=ModifyEventSubscription  
&Enabled=true  
&EventCategories.member.1=creation  
&EventCategories.member.2=deletion  
&EventCategories.member.3=failover  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SnsTopicArn=arn%3Aaws%3Asns%3Aus-west-2%3A802#####%3Amy-rds-events  
&SourceIds.member.1=myexampledb&SourceType=db-instance  
&SubscriptionName=ES-myuser01  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-west-2/rds/aws4_request  
&X-Amz-Date=20140428T183020Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=3d85bdfaf13861e93a9528824d9876ed87e6e01aaf43a962ce6f2a39247cf33a
```

Sample Response

```
<ModifyEventSubscriptionResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ModifyEventSubscriptionResult>  
    <EventSubscription>
```

```
<CustomerAwsId>802#####</CustomerAwsId>
<Enabled>>true</Enabled>
<SourceType>db-instance</SourceType>
<Status>modifying</Status>
<SourceIdsList>
  <SourceId>myexampldb</SourceId>
</SourceIdsList>
<SubscriptionCreationTime>2014-04-28 18:24:52.735</
SubscriptionCreationTime>
<EventCategoriesList>
  <EventCategory>creation</EventCategory>
  <EventCategory>deletion</EventCategory>
  <EventCategory>failover</EventCategory>
</EventCategoriesList>
<CustSubscriptionId>ES-myuser01</CustSubscriptionId>
<SnsTopicArn>arn:aws:sns:us-west-2:802#####:my-rds-events</
SnsTopicArn>
</EventSubscription>
</ModifyEventSubscriptionResult>
<ResponseMetadata>
  <RequestId>1798605b-be02-11d3-f73c-899ec2766c3b</RequestId>
</ResponseMetadata>
</ModifyEventSubscriptionResponse>
```

ModifyOptionGroup

Modifies an existing option group.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

ApplyImmediately

Indicates whether the changes should be applied immediately, or during the next maintenance window for each instance associated with the option group.

Type: Boolean

Required: No

OptionGroupName

The name of the option group to be modified.

Permanent options, such as the TDE option for Oracle Advanced Security TDE, cannot be removed from an option group, and that option group cannot be removed from a DB instance once it is associated with a DB instance

Type: String

Required: Yes

OptionsToInclude.OptionConfiguration.N

Options in this list are added to the option group or, if already present, the specified configuration is used to update the existing configuration.

Type: array of [OptionConfiguration \(p. 332\)](#) objects

Required: No

OptionsToRemove.member.N

Options in this list are removed from the option group.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

OptionGroup

Type: [OptionGroup \(p. 333\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

InvalidOptionGroupStateFault

The option group is not in the *available* state.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

Examples

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=ModifyOptionGroup  
&ApplyImmediately=true  
&OptionGroupName=myawsuser-og02  
&OptionsToInclude.member.1.DBSecurityGroupMemberships.member.1=default  
&OptionsToInclude.member.1.OptionName=MEMCACHED  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140501/us-east-1/rds/aws4_request  
&X-Amz-Date=20140501T230529Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=4b278baae6294738704a9948e355af0e9bd4fa0913d5b35b0a9a3c916925aced
```

Sample Response

```
<ModifyOptionGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <ModifyOptionGroupResult>  
    <OptionGroup>  
      <OptionGroupName>myawsuser-og02</OptionGroupName>  
      <MajorEngineVersion>5.6</MajorEngineVersion>  
      <AllowsVpcAndNonVpcInstanceMemberships>>false</  
AllowsVpcAndNonVpcInstanceMemberships>  
      <EngineName>mysql</EngineName>  
      <OptionGroupDescription>my second og</OptionGroupDescription>  
      <Options>  
        <Option>  
          <Port>11211</Port>  
          <OptionName>MEMCACHED</OptionName>  
          <OptionDescription>InnoDB Memcached for MySQL</OptionDescription>  
          <Persistent>>false</Persistent>  
          <OptionSettings>  
            <OptionSetting>  
              <DataType>BOOLEAN</DataType>  
              <IsModifiable>>true</IsModifiable>  
              <IsCollection>>false</IsCollection>  
              <Description>If enabled when there is no more memory to  
store items, memcached will return an error rather than evicting items.</  
Description>  
              <Name>ERROR_ON_MEMORY_EXHAUSTED</Name>  
              <Value>0</Value>  
              <ApplyType>STATIC</ApplyType>  
              <AllowedValues>0,1</AllowedValues>  
              <DefaultValue>0</DefaultValue>  
            </OptionSetting>  
          </Option>  
        </Options>  
      </OptionGroup>  
    </ModifyOptionGroupResult>  
  </ModifyOptionGroupResponse>
```

```
<OptionSetting>
  <DataType>INTEGER</DataType>
  <IsModifiable>true</IsModifiable>
  <IsCollection>false</IsCollection>
  <Description>The backlog queue configures how many network
connections can be waiting to be processed by memcached</Description>
  <Name>BACKLOG_QUEUE_LIMIT</Name>
  <Value>1024</Value>
  <ApplyType>STATIC</ApplyType>
  <AllowedValues>1-2048</AllowedValues>
  <DefaultValue>1024</DefaultValue>
</OptionSetting>
</OptionSettings>
<VpcSecurityGroupMemberships/>
<Permanent>false</Permanent>
<DBSecurityGroupMemberships>
  <DBSecurityGroup>
    <Status>authorized</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroupMemberships>
</Option>
</Options>
</OptionGroup>
</ModifyOptionGroupResult>
<ResponseMetadata>
  <RequestId>073cfb45-c184-11d3-a537-cef97546330c</RequestId>
</ResponseMetadata>
</ModifyOptionGroupResponse>
```

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
?Action=ModifyOptionGroup
&ApplyImmediately=true
&OptionGroupName=myawsuser-og02
&OptionsToRemove.OptionName=MEMCACHED
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140501/us-east-1/rds/aws4_request
&X-Amz-Date=20140501T231731Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=fd7ee924d39f1014488eb3444a8dfdb028e958b97703f95845a5addc435c1399
```

Sample Response

```
<ModifyOptionGroupResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">
  <ModifyOptionGroupResult>
```



```
<OptionGroup>
  <OptionGroupName>myawsuser-og02</OptionGroupName>
  <AllowsVpcAndNonVpcInstanceMemberships>true</
AllowsVpcAndNonVpcInstanceMemberships>
  <MajorEngineVersion>5.6</MajorEngineVersion>
  <EngineName>mysql</EngineName>
  <OptionGroupDescription>my second og</OptionGroupDescription>
  <Options/>
</OptionGroup>
</ModifyOptionGroupResult>
<ResponseMetadata>
  <RequestId>b5f134f3-c185-11d3-f4c6-37db295f7674</RequestId>
</ResponseMetadata>
</ModifyOptionGroupResponse>
```

PromoteReadReplica

Promotes a Read Replica DB instance to a standalone DB instance.

Note

We recommend that you enable automated backups on your Read Replica before promoting the Read Replica. This ensures that no backup is taken during the promotion process. Once the instance is promoted to a primary instance, backups are taken based on your backup settings.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

BackupRetentionPeriod

The number of days to retain automated backups. Setting this parameter to a positive number enables backups. Setting this parameter to 0 disables automated backups.

Default: 1

Constraints:

- Must be a value from 0 to 8

Type: Integer

Required: No

DBInstanceIdentifier

The DB instance identifier. This value is stored as a lowercase string.

Constraints:

- Must be the identifier for an existing Read Replica DB instance
- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `mydbinstance`

Type: String

Required: Yes

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled, using the `BackupRetentionPeriod` parameter.

Default: A 30-minute window selected at random from an 8-hour block of time per region. To see the time blocks available, see [Adjusting the Preferred Maintenance Window](#) in the *Amazon RDS User Guide*.

Constraints:

- Must be in the format `hh24:mi-hh24:mi`.
- Times should be in Universal Coordinated Time (UTC).
- Must not conflict with the preferred maintenance window.
- Must be at least 30 minutes.

Type: String

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance](#) (p. 42)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)

This data type is used as a response element in the [DescribeDBInstances](#) (p. 124) action.

Type: [DBInstance](#) (p. 304) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=PromoteReadReplica  
&BackupRetentionPeriod=7  
&DBInstanceIdentifier=mysqlldb-rr  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
&X-Amz-Date=20140428T221536Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=c0b2cfc3db8334b6ef86922f664e05ab306754e30e408d9fd3c8e58069a9b386
```

Sample Response

```
<PromoteReadReplicaResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <PromoteReadReplicaResult>  
    <DBInstance>  
      <BackupRetentionPeriod>0</BackupRetentionPeriod>  
      <DBInstanceStatus>modifying</DBInstanceStatus>  
      <MultiAZ>>false</MultiAZ>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>mysqlldb-rr</DBInstanceIdentifier>  
      <PreferredBackupWindow>08:25-08:55</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</  
PreferredMaintenanceWindow>  
      <StatusInfos>
```

```
<DBInstanceStatusInfo>
  <Status>replicating</Status>
  <StatusType>read replication</StatusType>
  <Normal>>true</Normal>
</DBInstanceStatusInfo>
</StatusInfos>
<AvailabilityZone>us-east-1a</AvailabilityZone>
<ReadReplicaDBInstanceIdentifiers/>
<Engine>mysql</Engine>
<PendingModifiedValues>
  <BackupRetentionPeriod>7</BackupRetentionPeriod>
</PendingModifiedValues>
<LicenseModel>general-public-license</LicenseModel>
<DBParameterGroups>
  <DBParameterGroup>
    <ParameterApplyStatus>in-sync</ParameterApplyStatus>
    <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
  </DBParameterGroup>
</DBParameterGroups>
<Endpoint>
  <Port>3306</Port>
  <Address>mysqldb-rr.cg029hpkcjt.us-east-1.rds.amazonaws.com</
Address>
  </Endpoint>
  <EngineVersion>5.6.13</EngineVersion>
  <ReadReplicaSourceDBInstanceIdentifier>mysqldb</
ReadReplicaSourceDBInstanceIdentifier>
  <OptionGroupMemberships>
    <OptionGroupMembership>
      <OptionGroupName>default:mysql-5-6</OptionGroupName>
      <Status>in-sync</Status>
    </OptionGroupMembership>
  </OptionGroupMemberships>
  <PubliclyAccessible>true</PubliclyAccessible>
  <DBSecurityGroups>
    <DBSecurityGroup>
      <Status>active</Status>
      <DBSecurityGroupName>default</DBSecurityGroupName>
    </DBSecurityGroup>
  </DBSecurityGroups>
  <AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
  <DBName>mysqldb</DBName>
  <InstanceCreateTime>2014-04-25T17:12:34.460Z</InstanceCreateTime>
  <AllocatedStorage>100</AllocatedStorage>
  <DBInstanceClass>db.m1.medium</DBInstanceClass>
  <MasterUsername>myawsuser</MasterUsername>
</DBInstance>
</PromoteReadReplicaResult>
<ResponseMetadata>
  <RequestId>8e8c0d64-be21-11d3-a71c-13dc2f771e41</RequestId>
</ResponseMetadata>
</PromoteReadReplicaResponse>
```

PromoteReadReplicaDBCluster

Promotes a Read Replica DB cluster to a standalone DB cluster.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The identifier of the DB cluster Read Replica to promote. This parameter is not case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster-replica1`

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)
- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=PromoteReadReplicaDBCluster  
&DBClusterIdentifier=my-cluster-replicat  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20160328/us-east-1/rds/aws4_request  
&X-Amz-Date=20160328T221226Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=e2b2cfc3db7766b6ef86922f664e05ab306754e30e408d9fd3c8e58069a9b386
```

Sample Response

```
<PromoteReadReplicaDBClusterResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <PromoteReadReplicaDBClusterResult>  
    <DBCluster>  
      <Port>3306</Port>  
      <Engine>aurora</Engine>  
      <Status>creating</Status>  
      <BackupRetentionPeriod>1</BackupRetentionPeriod>  
      <VpcSecurityGroups>  
        <VpcSecurityGroupMembership>  
          <Status>active</Status>  
          <VpcSecurityGroupId>sg-2103dc23</VpcSecurityGroupId>  
        </VpcSecurityGroupMembership>  
      </VpcSecurityGroups>  
      <DBSubnetGroup>default</DBSubnetGroup>  
      <EngineVersion>5.6.10a</EngineVersion>  
      <Endpoint>sample-cluster.cluster-ctrayan0rynq.us-  
east-1.rds.amazonaws.com</Endpoint>  
      <DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>  
      <AvailabilityZones>  
        <AvailabilityZone>us-east-1a</AvailabilityZone>  
        <AvailabilityZone>us-east-1c</AvailabilityZone>  
        <AvailabilityZone>us-east-1e</AvailabilityZone>  
      </AvailabilityZones>  
      <DBClusterIdentifier>my-cluster-replicat</DBClusterIdentifier>  
      <PreferredBackupWindow>04:22-04:52</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>fri:06:44-fri:07:14</  
PreferredMaintenanceWindow>  
      <DBClusterMembers>  
        <DBClusterMember>  
          <IsClusterWriter>true</IsClusterWriter>  
          <DBInstanceIdentifier>my-cluster1-master</DBInstanceIdentifier>  
        </DBClusterMember>  
        <DBClusterMember>  
          <IsClusterWriter>>false</IsClusterWriter>  
          <DBInstanceIdentifier>my-cluster1-read1</DBInstanceIdentifier>  
        </DBClusterMember>  
      </DBClusterMembers>  
      <AllocatedStorage>1</AllocatedStorage>  
      <MasterUsername>myawsuser</MasterUsername>
```

```
</DBCluster>  
</PromoteReadReplicaDBClusterResult>  
<ResponseMetadata>  
  <RequestId>8e8c0d64-be21-11d3-a71c-13dc2f771e41</RequestId>  
</ResponseMetadata>  
</PromoteReadReplicaDBClusterResponse>
```

PurchaseReservedDBInstancesOffering

Purchases a reserved DB instance offering.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBInstanceCount

The number of instances to reserve.

Default: 1

Type: Integer

Required: No

ReservedDBInstanceid

Customer-specified identifier to track this reservation.

Example: myreservationID

Type: String

Required: No

ReservedDBInstancesOfferingId

The ID of the Reserved DB instance offering to purchase.

Example: 438012d3-4052-4cc7-b2e3-8d3372e0e706

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag](#) (p. 354) objects

Required: No

Response Elements

The following element is returned by the service.

ReservedDBInstance

This data type is used as a response element in the [DescribeReservedDBInstances](#) (p. 177) and [PurchaseReservedDBInstancesOffering](#) (p. 236) actions.

Type: [ReservedDBInstance](#) (p. 348) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

ReservedDBInstanceAlreadyExists

User already has a reservation with the given identifier.

HTTP Status Code: 404

ReservedDBInstanceQuotaExceeded

Request would exceed the user's DB Instance quota.

HTTP Status Code: 400

ReservedDBInstancesOfferingNotFound

Specified offering does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=PurchaseReservedDBInstancesOffering  
  &ReservedDBInstanceId=myreservationID  
  &ReservedDBInstancesOfferingId=438012d3-4052-4cc7-b2e3-8d3372e0e706  
  &DBInstanceCount=10  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140415/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140415T232655Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=c2ac761e8c8f54a8c0727f5a87ad0a766fbb0024510b9aa34ea6d1f7df52fb11
```

Sample Response

```
<PurchaseReservedDBInstancesOfferingResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <PurchaseReservedDBInstancesOfferingResult>  
    <ReservedDBInstance>  
      <OfferingType>Partial Upfront</OfferingType>  
      <CurrencyCode>USD</CurrencyCode>  
      <RecurringCharges/>  
      <ProductDescription>mysql</ProductDescription>  
      <ReservedDBInstancesOfferingId>438012d3-4052-4cc7-b2e3-8d3372e0e706</  
ReservedDBInstancesOfferingId>  
      <MultiAZ>>true</MultiAZ>  
      <State>payment-pending</State>  
      <ReservedDBInstanceId>myreservationID</ReservedDBInstanceId>  
      <DBInstanceCount>10</DBInstanceCount>  
      <StartTime>2014-05-18T23:24:56.577Z</StartTime>  
      <Duration>31536000</Duration>  
      <FixedPrice>123.0</FixedPrice>  
      <UsagePrice>0.123</UsagePrice>  
      <DBInstanceClass>db.m1.small</DBInstanceClass>  
    </ReservedDBInstance>  
  </PurchaseReservedDBInstancesOfferingResult>  
  <ResponseMetadata>  
    <RequestId>7f099901-29cf-11e1-bd06-6fe008f046c3</RequestId>  
  </ResponseMetadata>  
</PurchaseReservedDBInstancesOfferingResponse>
```

RebootDBInstance

Rebooting a DB instance restarts the database engine service. A reboot also applies to the DB instance any modifications to the associated DB parameter group that were pending. Rebooting a DB instance results in a momentary outage of the instance, during which the DB instance status is set to `rebooting`. If the RDS instance is configured for MultiAZ, it is possible that the reboot will be conducted through a failover. An Amazon RDS event is created when the reboot is completed.

If your DB instance is deployed in multiple Availability Zones, you can force a failover from one AZ to the other during the reboot. You might force a failover to test the availability of your DB instance deployment or to restore operations to the original AZ after a failover occurs.

The time required to reboot is a function of the specific database engine's crash recovery process. To improve the reboot time, we recommend that you reduce database activities as much as possible during the reboot process to reduce rollback activity for in-transit transactions.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBInstanceIdentifier

The DB instance identifier. This parameter is stored as a lowercase string.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

ForceFailover

When `true`, the reboot will be conducted through a MultiAZ failover.

Constraint: You cannot specify `true` if the instance is not configured for MultiAZ.

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance \(p. 42\)](#)
- [DeleteDBInstance \(p. 85\)](#)
- [ModifyDBInstance \(p. 204\)](#)

This data type is used as a response element in the [DescribeDBInstances \(p. 124\)](#) action.

Type: [DBInstance \(p. 304\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=RebootDBInstance  
&DBInstanceIdentifier=mysqlldb  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
&X-Amz-Date=20140428T222011Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=1c48f44c14183cff26fde7d912946f87f3bb9d715f66448f457a8f9e99602af5
```

Sample Response

```
<RebootDBInstanceResponse xmlns="http://rds.amazonaws.com/doc/2014-09-01/">  
  <RebootDBInstanceResult>  
    <DBInstance>  
      <BackupRetentionPeriod>7</BackupRetentionPeriod>  
      <DBInstanceStatus>rebooting</DBInstanceStatus>  
      <MultiAZ>>false</MultiAZ>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>mysqlldb</DBInstanceIdentifier>  
      <PreferredBackupWindow>08:14-08:44</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</  
PreferredMaintenanceWindow>  
      <AvailabilityZone>us-east-1a</AvailabilityZone>  
      <ReadReplicaDBInstanceIdentifiers/>  
      <LatestRestorableTime>2014-04-28T22:15:00Z</LatestRestorableTime>  
      <Engine>mysql</Engine>  
      <PendingModifiedValues/>  
      <LicenseModel>general-public-license</LicenseModel>  
      <EngineVersion>5.6.13</EngineVersion>  
      <Endpoint>  
        <Port>3306</Port>  
        <Address>mysqlldb.cb036hpkmopt.us-east-1.rds.amazonaws.com</Address>  
      </Endpoint>  
      <DBParameterGroups>  
        <DBParameterGroup>  
          <ParameterApplyStatus>in-sync</ParameterApplyStatus>  
          <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>  
        </DBParameterGroup>  
      </DBParameterGroups>  
      <OptionGroupMemberships>
```

```
<OptionGroupMembership>
  <OptionGroupName>default:mysql-5-6</OptionGroupName>
  <Status>in-sync</Status>
</OptionGroupMembership>
</OptionGroupMemberships>
<PubliclyAccessible>true</PubliclyAccessible>
<DBSecurityGroups>
  <DBSecurityGroup>
    <Status>active</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
<DBName>mysqldb</DBName>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<InstanceCreateTime>2014-04-21T22:24:26.573Z</InstanceCreateTime>
<AllocatedStorage>100</AllocatedStorage>
<MasterUsername>myawsuser</MasterUsername>
<DBInstanceClass>db.m1.medium</DBInstanceClass>
</DBInstance>
</RebootDBInstanceResult>
<ResponseMetadata>
  <RequestId>33c99cd2-be22-11d3-abdb-7cb19376fb1c</RequestId>
</ResponseMetadata>
</RebootDBInstanceResponse>
```

RemoveRoleFromDBCluster

Disassociates an Identity and Access Management (IAM) role from an Aurora DB cluster. For more information, see [Authorizing Amazon Aurora to Access Other AWS Services On Your Behalf](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 358\)](#).

DBClusterIdentifier

The name of the DB cluster to disassociate the IAM role from.

Type: String

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of the IAM role to disassociate from the Aurora DB cluster, for example `arn:aws:iam::123456789012:role/AuroraAccessRole`.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterRoleNotFound

The specified IAM role Amazon Resource Name (ARN) is not associated with the specified DB cluster.

HTTP Status Code: 404

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=RemoveRoleFromDBCluster  
&DBClusterIdentifier=sample-cluster  
&RoleArn=arn%3Aaws%3Aiam%3A%3A123456789012%3Arole%2Fsample-role  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20161012/us-east-1/rds/aws4_request  
&X-Amz-Date=20161012T204525Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date
```

```
&X-Amz-  
Signature=cd7d5005d56a505b4e2a878c297e6f8a3cc26b19a335ede018ba41f3185c92a2
```

Sample Response

```
<RemoveRoleFromDBClusterResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ResponseMetadata>  
    <RequestId>ccfca75a-90bc-11e6-8533-cd6377e421f8</RequestId>  
  </ResponseMetadata>  
</RemoveRoleFromDBClusterResponse>
```

RemoveSourceIdentifierFromSubscription

Removes a source identifier from an existing RDS event notification subscription.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

SourceIdentifier

The source identifier to be removed from the subscription, such as the **DB instance identifier** for a DB instance or the name of a security group.

Type: String

Required: Yes

SubscriptionName

The name of the RDS event notification subscription you want to remove a source identifier from.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions](#) (p. 159) action.

Type: [EventSubscription](#) (p. 327) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

SourceNotFound

The requested source could not be found.

HTTP Status Code: 404

SubscriptionNotFound

The subscription name does not exist.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=RemoveSourceIdentifierFromSubscription  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SourceIdentifier=si-sample  
&SubscriptionName=myawsuser-secgrp  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request
```

```
&X-Amz-Date=20140428T222718Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=4419f0015657ee120d781849ffdc6642eeafeee42bf1d18c4b2ed8eb732f7bf8
```

Sample Response

```
<RemoveSourceIdentifierFromSubscriptionResponse xmlns="http://
rds.amazonaws.com/doc/2014-09-01/">
  <RemoveSourceIdentifierFromSubscriptionResult>
    <EventSubscription>
      <Enabled>true</Enabled>
      <CustomerAwsId>802#####</CustomerAwsId>
      <SourceType>db-security-group</SourceType>
      <Status>active</Status>
      <SubscriptionCreationTime>2014-04-25 21:43:25.542</
SubscriptionCreationTime>
      <EventCategoriesList>
        <EventCategory>configuration change</EventCategory>
        <EventCategory>failure</EventCategory>
      </EventCategoriesList>
      <CustSubscriptionId>myawsuser-secgrp</CustSubscriptionId>
      <SnsTopicArn>arn:aws:sns:us-east-1:802#####:myawsuser-RDS</
SnsTopicArn>
    </EventSubscription>
  </RemoveSourceIdentifierFromSubscriptionResult>
  <ResponseMetadata>
    <RequestId>326cdeb9-be23-11d3-91a5-a90441261bc4</RequestId>
  </ResponseMetadata>
</RemoveSourceIdentifierFromSubscriptionResponse>
```


RemoveTagsFromResource

Removes metadata tags from an Amazon RDS resource.

For an overview on tagging an Amazon RDS resource, see [Tagging Amazon RDS Resources](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

ResourceName

The Amazon RDS resource the tags will be removed from. This value is an Amazon Resource Name (ARN). For information about creating an ARN, see [Constructing an RDS Amazon Resource Name \(ARN\)](#).

Type: String

Required: Yes

TagKeys.member.N

The tag key (name) of the tag to be removed.

Type: array of Strings

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/
?Action=RemoveTagsFromResource
&ResourceName=arn%3Aaws%3Ards%3Aus-west-2%3A123456789012%3Adb%3Asample
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&TagKeys.member.1=InstanceType
&TagKeys.member.2=Owner
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request
&X-Amz-Date=20160913T174918Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
```

```
&X-Amz-  
Signature=4c72f307a75444461bd9b9ccb7de361fec75b8adad66a52824226320d0a33ca8
```

Sample Response

```
<RemoveTagsFromResourceResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ResponseMetadata>  
    <RequestId>126d40cc-79da-11e6-b8e4-29f0c684be5d</RequestId>  
  </ResponseMetadata>  
</RemoveTagsFromResourceResponse>
```

ResetDBClusterParameterGroup

Modifies the parameters of a DB cluster parameter group to the default value. To reset specific parameters submit a list of the following: `ParameterName` and `ApplyMethod`. To reset the entire DB cluster parameter group, specify the `DBClusterParameterGroupName` and `ResetAllParameters` parameters.

When resetting the entire group, dynamic parameters are updated immediately and static parameters are set to `pending-reboot` to take effect on the next DB instance restart or [RebootDBInstance](#) (p. 238) request. You must call [RebootDBInstance](#) (p. 238) for every DB instance in your DB cluster that you want the updated static parameter to apply to.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterParameterGroupName

The name of the DB cluster parameter group to reset.

Type: String

Required: Yes

Parameters.Parameter.N

A list of parameter names in the DB cluster parameter group to reset to the default values. You cannot use this parameter if the `ResetAllParameters` parameter is set to `true`.

Type: array of [Parameter](#) (p. 342) objects

Required: No

ResetAllParameters

A value that is set to `true` to reset all parameters in the DB cluster parameter group to their default values, and `false` otherwise. You cannot use this parameter if there is a list of parameter names specified for the `Parameters` parameter.

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBClusterParameterGroupName

The name of the DB cluster parameter group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Note

This value is stored as a lowercase string.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=ResetDBClusterParameterGroup  
&DBClusterParameterGroupName=sample-cluster-pg  
&Parameters.member.1.ApplyMethod=pending-reboot  
&Parameters.member.1.ParameterName=binlog_format  
&Parameters.member.2.ApplyMethod=pending-reboot  
&Parameters.member.2.ParameterName=innodb_support_xa  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request  
&X-Amz-Date=20160913T230026Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=7cca4504082065e227696f2dd904fab2f39633bc7d120258c4bedd35da3ade7f
```

Sample Response

```
<ResetDBClusterParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <ResetDBClusterParameterGroupResult>  
    <DBClusterParameterGroupName>sample-cluster-pg</  
DBClusterParameterGroupName>  
  </ResetDBClusterParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>dc2c61eb-7a05-11e6-b83b-cd70a540d79f</RequestId>  
  </ResponseMetadata>  
</ResetDBClusterParameterGroupResponse>
```

ResetDBParameterGroup

Modifies the parameters of a DB parameter group to the engine/system default value. To reset specific parameters submit a list of the following: `ParameterName` and `ApplyMethod`. To reset the entire DB parameter group, specify the `DBParameterGroup` name and `ResetAllParameters` parameters. When resetting the entire group, dynamic parameters are updated immediately and static parameters are set to `pending-reboot` to take effect on the next DB instance restart or `RebootDBInstance` request.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBParameterGroupName

The name of the DB parameter group.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Parameters.Parameter.N

An array of parameter names, values, and the apply method for the parameter update. At least one parameter name, value, and apply method must be supplied; subsequent arguments are optional. A maximum of 20 parameters can be modified in a single request.

MySQL

Valid Values (for Apply method): `immediate` | `pending-reboot`

You can use the `immediate` value with dynamic parameters only. You can use the `pending-reboot` value for both dynamic and static parameters, and changes are applied when DB instance reboots.

MariaDB

Valid Values (for Apply method): `immediate` | `pending-reboot`

You can use the `immediate` value with dynamic parameters only. You can use the `pending-reboot` value for both dynamic and static parameters, and changes are applied when DB instance reboots.

Oracle

Valid Values (for Apply method): `pending-reboot`

Type: array of [Parameter](#) (p. 342) objects

Required: No

ResetAllParameters

Specifies whether (`true`) or not (`false`) to reset all parameters in the DB parameter group to default values.

Default: `true`

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBParameterGroupName

Provides the name of the DB parameter group.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBParameterGroupNotFound

DBParameterGroupName does not refer to an existing DB parameter group.

HTTP Status Code: 404

InvalidDBParameterGroupState

The DB parameter group cannot be deleted because it is in use.

HTTP Status Code: 400

Examples

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=ResetDBParameterGroup  
  &DBParameterGroupName=mydbparametergroup01  
  &ResetAllParameters=true  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140428T225714Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=709d1418c91c5ef4129d4665e5c2820002a9665699acf4204683c778f03c3573
```

Sample Response

```
<ResetDBParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ResetDBParameterGroupResult>  
    <DBParameterGroupName>mydbparametergroup01</DBParameterGroupName>  
  </ResetDBParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>610909c6-be27-11d3-a71c-13dc2f771e41</RequestId>  
  </ResponseMetadata>  
</ResetDBParameterGroupResponse>
```

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=ResetDBParameterGroup  
&DBParameterGroupName=mydbparametergroup01  
&Parameters.member.1.ApplyMethod=immediate  
&Parameters.member.1.ParameterName=bulk_insert_buffer_size  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
&X-Amz-Date=20140428T230509Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=d343dd7fcc3789d30295b5e3fc67262f28af15d71fc978921f0e8846b2d1e6
```

Sample Response

```
<ResetDBParameterGroupResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <ResetDBParameterGroupResult>  
    <DBParameterGroupName>mydbparametergroup01</DBParameterGroupName>  
  </ResetDBParameterGroupResult>  
  <ResponseMetadata>  
    <RequestId>7acb72cf-be28-11d3-a4fc-e3b7f6c20c5f</RequestId>  
  </ResponseMetadata>  
</ResetDBParameterGroupResponse>
```

RestoreDBClusterFromS3

Creates an Amazon Aurora DB cluster from data stored in an Amazon S3 bucket. Amazon RDS must be authorized to access the Amazon S3 bucket and the data must be created using the Percona XtraBackup utility as described in [Migrating Data from MySQL by Using an Amazon S3 Bucket](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

AvailabilityZones.AvailabilityZone.N

A list of EC2 Availability Zones that instances in the restored DB cluster can be created in.

Type: array of Strings

Required: No

BackupRetentionPeriod

The number of days for which automated backups of the restored DB cluster are retained. You must specify a minimum value of 1.

Default: 1

Constraints:

- Must be a value from 1 to 35

Type: Integer

Required: No

CharacterSetName

A value that indicates that the restored DB cluster should be associated with the specified CharacterSet.

Type: String

Required: No

DatabaseName

The database name for the restored DB cluster.

Type: String

Required: No

DBClusterIdentifier

The name of the DB cluster to create from the source data in the S3 bucket. This parameter is isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens.
- First character must be a letter.
- Cannot end with a hyphen or contain two consecutive hyphens.

Example: `my-cluster1`

Type: String

Required: Yes

DBClusterParameterGroupName

The name of the DB cluster parameter group to associate with the restored DB cluster. If this argument is omitted, `default.aurora5.6` will be used.

Constraints:

- Must be 1 to 255 alphanumeric characters
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: No

DBSubnetGroupName

A DB subnet group to associate with the restored DB cluster.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Engine

The name of the database engine to be used for the restored DB cluster.

Valid Values: `aurora`

Type: String

Required: Yes

EngineVersion

The version number of the database engine to use.

Aurora

Example: `5.6.10a`

Type: String

Required: No

KmsKeyId

The KMS key identifier for an encrypted DB cluster.

The KMS key identifier is the Amazon Resource Name (ARN) for the KMS encryption key. If you are creating a DB cluster with the same AWS account that owns the KMS encryption key used to encrypt the new DB cluster, then you can use the KMS key alias instead of the ARN for the KMS encryption key.

If the `StorageEncrypted` parameter is true, and you do not specify a value for the `KmsKeyId` parameter, then Amazon RDS will use your default encryption key. AWS KMS creates the default encryption key for your AWS account. Your AWS account has a different default encryption key for each AWS region.

Type: String

Required: No

MasterUsername

The name of the master user for the restored DB cluster.

Constraints:

- Must be 1 to 16 alphanumeric characters.
- First character must be a letter.
- Cannot be a reserved word for the chosen database engine.

Type: String

Required: Yes

MasterUserPassword

The password for the master database user. This password can contain any printable ASCII character except `/`, `""`, or `@`.

Constraints: Must contain from 8 to 41 characters.

Type: String

Required: Yes

OptionGroupName

A value that indicates that the restored DB cluster should be associated with the specified option group.

Permanent options cannot be removed from an option group. An option group cannot be removed from a DB cluster once it is associated with a DB cluster.

Type: String

Required: No

Port

The port number on which the instances in the restored DB cluster accept connections.

Default: 3306

Type: Integer

Required: No

PreferredBackupWindow

The daily time range during which automated backups are created if automated backups are enabled using the `BackupRetentionPeriod` parameter.

Default: A 30-minute window selected at random from an 8-hour block of time per region. To see the time blocks available, see [Adjusting the Preferred Maintenance Window in the Amazon RDS User Guide](#).

Constraints:

- Must be in the format `hh24:mi-hh24:mi`.
- Times should be in Universal Coordinated Time (UTC).
- Must not conflict with the preferred maintenance window.
- Must be at least 30 minutes.

Type: String

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Format: `ddd:hh24:mi-ddd:hh24:mi`

Default: A 30-minute window selected at random from an 8-hour block of time per region, occurring on a random day of the week. To see the time blocks available, see [Adjusting the Preferred Maintenance Window in the Amazon RDS User Guide](#).

Valid Days: Mon, Tue, Wed, Thu, Fri, Sat, Sun

Constraints: Minimum 30-minute window.

Type: String

Required: No

S3BucketName

The name of the Amazon S3 bucket that contains the data used to create the Amazon Aurora DB cluster.

Type: String

Required: Yes

S3IngestionRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) role that authorizes Amazon RDS to access the Amazon S3 bucket on your behalf.

Type: String

Required: Yes

S3Prefix

The prefix for all of the file names that contain the data used to create the Amazon Aurora DB cluster. If you do not specify a **SourceS3Prefix** value, then the Amazon Aurora DB cluster is created by using all of the files in the Amazon S3 bucket.

Type: String

Required: No

SourceEngine

The identifier for the database engine that was backed up to create the files stored in the Amazon S3 bucket.

Valid values: `mysql`

Type: String

Required: Yes

SourceEngineVersion

The version of the database that the backup files were created from.

MySQL version 5.5 and 5.6 are supported.

Example: 5 . 6 . 22

Type: String

Required: Yes

StorageEncrypted

Specifies whether the restored DB cluster is encrypted.

Type: Boolean

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

VpcSecurityGroupIds.VpcSecurityGroupId.N

A list of EC2 VPC security groups to associate with the restored DB cluster.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster \(p. 30\)](#)
- [DeleteDBCluster \(p. 78\)](#)
- [FailoverDBCluster \(p. 189\)](#)
- [ModifyDBCluster \(p. 194\)](#)
- [RestoreDBClusterFromSnapshot \(p. 258\)](#)
- [RestoreDBClusterToPointInTime \(p. 263\)](#)

This data type is used as a response element in the [DescribeDBClusters \(p. 112\)](#) action.

Type: [DBCluster \(p. 291\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

DBClusterAlreadyExistsFault

User already has a DB cluster with the given identifier.

HTTP Status Code: 400

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterParameterGroupNotFound

DBClusterParameterGroupName does not refer to an existing DB Cluster parameter group.

HTTP Status Code: 404

DBClusterQuotaExceededFault

User attempted to create a new DB cluster and the user has already reached the maximum allowed DB cluster quota.

HTTP Status Code: 403

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InsufficientStorageClusterCapacity

There is insufficient storage available for the current action. You may be able to resolve this error by updating your subnet group to use different Availability Zones that have more storage available.

HTTP Status Code: 400

InvalidDBClusterStateFault

The DB cluster is not in a valid state.

HTTP Status Code: 400

InvalidDBSubnetGroupStateFault

The DB subnet group cannot be deleted because it is in use.

HTTP Status Code: 400

InvalidS3BucketFault

The specified Amazon S3 bucket name could not be found or Amazon RDS is not authorized to access the specified Amazon S3 bucket. Verify the **SourceS3BucketName** and **S3IngestionRoleArn** values and try again.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=RestoreDBClusterFromS3  
&DBClusterIdentifier=sample-cluster  
&Engine=aurora  
&S3BucketName=s3-ingestion-sample  
&SourceEngine=mysql  
&SourceEngineVersion=5.6.22  
&MasterUsername=myawsuser  
&MasterUserPassword=<password>
```

```
&S3IngestionRoleArn=arn:aws:iam:123456789012:role/sample-role
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&SnapshotIdentifier=sample-snapshot
&Version=2014-10-31
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20150323/us-east-1/rds/aws4_request
&X-Amz-Date=20150323T165638Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=c59effef9b7b96f6a8dfed7873611df555364594f7f9acf9cd14d353114771fd
```

Sample Response

```
<RestoreDBClusterFromS3Response xmlns="http://rds.amazonaws.com/
doc/2014-10-31/">
  <RestoreDBClusterFromS3Result>
    <DBCluster>
      <Port>3306</Port>
      <Engine>aurora</Engine>
      <Status>creating</Status>
      <BackupRetentionPeriod>1</BackupRetentionPeriod>
      <VpcSecurityGroups>
        <VpcSecurityGroupMembership>
          <Status>active</Status>
          <VpcSecurityGroupId>sg-2103dc23</VpcSecurityGroupId>
        </VpcSecurityGroupMembership>
      </VpcSecurityGroups>
      <DBSubnetGroup>default</DBSubnetGroup>
      <EngineVersion>5.6.10a</EngineVersion>
      <Endpoint>sample-cluster.cluster-ctrayan0rynq.us-
east-1.rds.amazonaws.com</Endpoint>
      <DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>
      <AvailabilityZones>
        <AvailabilityZone>us-east-1a</AvailabilityZone>
        <AvailabilityZone>us-east-1c</AvailabilityZone>
        <AvailabilityZone>us-east-1e</AvailabilityZone>
      </AvailabilityZones>
      <DBClusterIdentifier>sample-cluster</DBClusterIdentifier>
      <PreferredBackupWindow>04:22-04:52</PreferredBackupWindow>
      <PreferredMaintenanceWindow>fri:06:44-fri:07:14</
PreferredMaintenanceWindow>
      <DBClusterMembers/>
      <AllocatedStorage>1</AllocatedStorage>
      <MasterUsername>myawsuser</MasterUsername>
    </DBCluster>
  </RestoreDBClusterFromS3Result>
  <ResponseMetadata>
    <RequestId>46d2b228-7681-11e5-3e8b-9b2c0d5d51a9</RequestId>
  </ResponseMetadata>
</RestoreDBClusterFromS3Response>
```

RestoreDBClusterFromSnapshot

Creates a new DB cluster from a DB cluster snapshot. The target DB cluster is created from the source DB cluster restore point with the same configuration as the original source DB cluster, except that the new DB cluster is created with the default security group.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

AvailabilityZones.AvailabilityZone.N

Provides the list of EC2 Availability Zones that instances in the restored DB cluster can be created in.

Type: array of Strings

Required: No

DatabaseName

The database name for the restored DB cluster.

Type: String

Required: No

DBClusterIdentifier

The name of the DB cluster to create from the DB cluster snapshot. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-snapshot-id`

Type: String

Required: Yes

DBSubnetGroupName

The name of the DB subnet group to use for the new DB cluster.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Engine

The database engine to use for the new DB cluster.

Default: The same as source

Constraint: Must be compatible with the engine of the source

Type: String

Required: Yes

EngineVersion

The version of the database engine to use for the new DB cluster.

Type: String

Required: No

KmsKeyId

The KMS key identifier to use when restoring an encrypted DB cluster from a DB cluster snapshot.

The KMS key identifier is the Amazon Resource Name (ARN) for the KMS encryption key. If you are restoring a DB cluster with the same AWS account that owns the KMS encryption key used to encrypt the new DB cluster, then you can use the KMS key alias instead of the ARN for the KMS encryption key.

If you do not specify a value for the `KmsKeyId` parameter, then the following will occur:

- If the DB cluster snapshot is encrypted, then the restored DB cluster is encrypted using the KMS key that was used to encrypt the DB cluster snapshot.
- If the DB cluster snapshot is not encrypted, then the restored DB cluster is encrypted using the specified encryption key.

Type: String

Required: No

OptionGroupName

The name of the option group to use for the restored DB cluster.

Type: String

Required: No

Port

The port number on which the new DB cluster accepts connections.

Constraints: Value must be 1150–65535

Default: The same port as the original DB cluster.

Type: Integer

Required: No

SnapshotIdentifier

The identifier for the DB cluster snapshot to restore from.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Tags.Tag.N

The tags to be assigned to the restored DB cluster.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

VpcSecurityGroupIds.VpcSecurityGroupId.N

A list of VPC security groups that the new DB cluster will belong to.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster \(p. 30\)](#)
- [DeleteDBCluster \(p. 78\)](#)
- [FailoverDBCluster \(p. 189\)](#)
- [ModifyDBCluster \(p. 194\)](#)
- [RestoreDBClusterFromSnapshot \(p. 258\)](#)

- [RestoreDBClusterToPointInTime](#) (p. 263)
This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.
Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterAlreadyExistsFault

User already has a DB cluster with the given identifier.

HTTP Status Code: 400

DBClusterQuotaExceededFault

User attempted to create a new DB cluster and the user has already reached the maximum allowed DB cluster quota.

HTTP Status Code: 403

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InsufficientDBClusterCapacityFault

The DB cluster does not have enough capacity for the current operation.

HTTP Status Code: 403

InsufficientStorageClusterCapacity

There is insufficient storage available for the current action. You may be able to resolve this error by updating your subnet group to use different Availability Zones that have more storage available.

HTTP Status Code: 400

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

InvalidRestoreFault

Cannot restore from vpc backup to non-vpc DB instance.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.
HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.
HTTP Status Code: 404

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=RestoreDBClusterFromSnapshot  
&DBClusterIdentifier=sample-restored  
&Engine=aurora  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SnapshotIdentifier=sample-snapshot-1  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request  
&X-Amz-Date=20160913T223701Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=65d0d03242d99a16ef3712142bfcd52ac63fd2f68fbb5efd7edfble89138da57
```

Sample Response

```
<RestoreDBClusterFromSnapshotResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <RestoreDBClusterFromSnapshotResult>  
    <DBCluster>  
      <AllocatedStorage>1</AllocatedStorage>  
      <DatabaseName>sample</DatabaseName>  
      <AvailabilityZones>  
        <AvailabilityZone>us-west-2a</AvailabilityZone>  
        <AvailabilityZone>us-west-2b</AvailabilityZone>  
        <AvailabilityZone>us-west-2c</AvailabilityZone>  
      </AvailabilityZones>  
      <PreferredBackupWindow>10:37-11:07</PreferredBackupWindow>  
      <Endpoint>sample-restored.cluster-cnubrrevfka6.us-  
west-2.rds.amazonaws.com</Endpoint>  
      <Engine>aurora</Engine>
```

```
<ReaderEndpoint>sample-restored.cluster-ro-cnubrevfka6.us-  
west-2.rds.amazonaws.com</ReaderEndpoint>  
<ReadReplicaIdentifiers/>  
<EngineVersion>5.6.10a</EngineVersion>  
<MasterUsername>mymasteruser</MasterUsername>  
<DBClusterMembers/>  
<StorageEncrypted>>false</StorageEncrypted>  
<DBSubnetGroup>default</DBSubnetGroup>  
<VpcSecurityGroups>  
  <VpcSecurityGroupMembership>  
    <VpcSecurityGroupId>sg-178c1671</VpcSecurityGroupId>  
    <Status>active</Status>  
  </VpcSecurityGroupMembership>  
</VpcSecurityGroups>  
<HostedZoneId>Z1PVI0B346C1W</HostedZoneId>  
<Port>3306</Port>  
<PreferredMaintenanceWindow>tue:11:51-tue:12:21</  
PreferredMaintenanceWindow>  
<DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>  
<BackupRetentionPeriod>1</BackupRetentionPeriod>  
<DBClusterIdentifier>sample-restored</DBClusterIdentifier>  
<DbClusterResourceId>cluster-BOCABDT6N5UVQW273AOXAX234Y</  
DbClusterResourceId>  
<DBClusterArn>arn:aws:rds:us-west-2:123456789012:cluster:sample-  
restored</DBClusterArn>  
<Status>creating</Status>  
</DBCluster>  
</RestoreDBClusterFromSnapshotResult>  
<ResponseMetadata>  
  <RequestId>955ebc45-7a02-11e6-a5e1-0785f9b8437a</RequestId>  
</ResponseMetadata>  
</RestoreDBClusterFromSnapshotResponse>
```

RestoreDBClusterToPointInTime

Restores a DB cluster to an arbitrary point in time. Users can restore to any point in time before `LatestRestorableTime` for up to `BackupRetentionPeriod` days. The target DB cluster is created from the source DB cluster with the same configuration as the original DB cluster, except that the new DB cluster is created with the default DB security group.

For more information on Amazon Aurora, see [Aurora on Amazon RDS](#) in the *Amazon RDS User Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

DBClusterIdentifier

The name of the new DB cluster to be created.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

DBSubnetGroupName

The DB subnet group name to use for the new DB cluster.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

KmsKeyId

The KMS key identifier to use when restoring an encrypted DB cluster from an encrypted DB cluster.

The KMS key identifier is the Amazon Resource Name (ARN) for the KMS encryption key. If you are restoring a DB cluster with the same AWS account that owns the KMS encryption key used to encrypt the new DB cluster, then you can use the KMS key alias instead of the ARN for the KMS encryption key.

You can restore to a new DB cluster and encrypt the new DB cluster with a KMS key that is different than the KMS key used to encrypt the source DB cluster. The new DB cluster will be encrypted with the KMS key identified by the `KmsKeyId` parameter.

If you do not specify a value for the `KmsKeyId` parameter, then the following will occur:

- If the DB cluster is encrypted, then the restored DB cluster is encrypted using the KMS key that was used to encrypt the source DB cluster.
- If the DB cluster is not encrypted, then the restored DB cluster is not encrypted.

If `DBClusterIdentifier` refers to a DB cluster that is not encrypted, then the restore request is rejected.

Type: String

Required: No

OptionGroupName

The name of the option group for the new DB cluster.

Type: String

Required: No

Port

The port number on which the new DB cluster accepts connections.

Constraints: Value must be 1150–65535

Default: The same port as the original DB cluster.

Type: Integer

Required: No

RestoreToTime

The date and time to restore the DB cluster to.

Valid Values: Value must be a time in Universal Coordinated Time (UTC) format

Constraints:

- Must be before the latest restorable time for the DB instance
- Cannot be specified if `UseLatestRestorableTime` parameter is true

Example: 2015-03-07T23:45:00Z

Type: Timestamp

Required: No

SourceDBClusterIdentifier

The identifier of the source DB cluster from which to restore.

Constraints:

- Must be the identifier of an existing database instance
- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

UseLatestRestorableTime

A value that is set to `true` to restore the DB cluster to the latest restorable backup time, and `false` otherwise.

Default: `false`

Constraints: Cannot be specified if `RestoreToTime` parameter is provided.

Type: Boolean

Required: No

VpcSecurityGroupIds.VpcSecurityGroupid.N

A list of VPC security groups that the new DB cluster belongs to.

Type: array of Strings

Required: No

Response Elements

The following element is returned by the service.

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster \(p. 30\)](#)
- [DeleteDBCluster \(p. 78\)](#)
- [FailoverDBCluster \(p. 189\)](#)

- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Type: [DBCluster](#) (p. 291) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

DBClusterAlreadyExistsFault

User already has a DB cluster with the given identifier.

HTTP Status Code: 400

DBClusterNotFoundFault

DBClusterIdentifier does not refer to an existing DB cluster.

HTTP Status Code: 404

DBClusterQuotaExceededFault

User attempted to create a new DB cluster and the user has already reached the maximum allowed DB cluster quota.

HTTP Status Code: 403

DBClusterSnapshotNotFoundFault

DBClusterSnapshotIdentifier does not refer to an existing DB cluster snapshot.

HTTP Status Code: 404

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

InsufficientDBClusterCapacityFault

The DB cluster does not have enough capacity for the current operation.

HTTP Status Code: 403

InsufficientStorageClusterCapacity

There is insufficient storage available for the current action. You may be able to resolve this error by updating your subnet group to use different Availability Zones that have more storage available.

HTTP Status Code: 400

InvalidDBClusterSnapshotStateFault

The supplied value is not a valid DB cluster snapshot state.

HTTP Status Code: 400

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

InvalidRestoreFault

Cannot restore from vpc backup to non-vpc DB instance.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.
HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.
HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.
HTTP Status Code: 404

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.
HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.
HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-west-2.amazonaws.com/  
?Action=RestoreDBClusterToPointInTime  
&DBClusterIdentifier=sample-restored-1  
&RestoreToTime=2016-09-13T18%3A45%3A00Z  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&SourceDBClusterIdentifier=sample-cluster  
&Version=2014-10-31  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20160913/us-west-2/rds/aws4_request  
&X-Amz-Date=20160913T224930Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=e3b88945052247e82eaeaca6e269e7f6e18a36147b45c3b077bc600472e70de6
```

Sample Response

```
<RestoreDBClusterToPointInTimeResponse xmlns="http://rds.amazonaws.com/  
doc/2014-10-31/">  
  <RestoreDBClusterToPointInTimeResult>  
    <DBCluster>  
      <AllocatedStorage>1</AllocatedStorage>  
      <DatabaseName>sample</DatabaseName>  
      <AvailabilityZones>  
        <AvailabilityZone>us-west-2a</AvailabilityZone>  
        <AvailabilityZone>us-west-2b</AvailabilityZone>  
        <AvailabilityZone>us-west-2c</AvailabilityZone>  
      </AvailabilityZones>  
      <PreferredBackupWindow>10:37-11:07</PreferredBackupWindow>
```

```
<Endpoint>sample-restored-1.cluster-cnubrrfwfkg6.us-  
west-2.rds.amazonaws.com</Endpoint>  
<Engine>aurora</Engine>  
<ReaderEndpoint>sample-restored-1.cluster-ro-cnubrrfwfkg6.us-  
west-2.rds.amazonaws.com</ReaderEndpoint>  
<ReadReplicaIdentifiers/>  
<EngineVersion>5.6.10a</EngineVersion>  
<MasterUsername>mymasteruser</MasterUsername>  
<DBClusterMembers/>  
<StorageEncrypted>>false</StorageEncrypted>  
<DBSubnetGroup>default</DBSubnetGroup>  
<HostedZoneId>Z1PVI0B622C1W</HostedZoneId>  
<VpcSecurityGroups>  
  <VpcSecurityGroupMembership>  
    <VpcSecurityGroupId>sg-187c1671</VpcSecurityGroupId>  
    <Status>active</Status>  
  </VpcSecurityGroupMembership>  
</VpcSecurityGroups>  
<Port>3306</Port>  
<PreferredMaintenanceWindow>tue:11:51-tue:12:21</  
PreferredMaintenanceWindow>  
<DBClusterParameterGroup>default.aurora5.6</DBClusterParameterGroup>  
<BackupRetentionPeriod>1</BackupRetentionPeriod>  
<DBClusterIdentifier>sample-restored-1</DBClusterIdentifier>  
<DbClusterResourceId>cluster-U5ZXU3237H7YVCVKISDIXSQKUQ</  
DbClusterResourceId>  
<DBClusterArn>arn:aws:rds:us-west-2:123456789012:cluster:sample-  
restored-1</DBClusterArn>  
<Status>creating</Status>  
</DBCluster>  
</RestoreDBClusterToPointInTimeResult>  
<ResponseMetadata>  
  <RequestId>54b75eef-7a04-15b6-aaa0-75ef834084a0</RequestId>  
</ResponseMetadata>  
</RestoreDBClusterToPointInTimeResponse>
```

RestoreDBInstanceFromDBSnapshot

Creates a new DB instance from a DB snapshot. The target database is created from the source database restore point with the most of original configuration with the default security group and the default DB parameter group. By default, the new DB instance is created as a single-AZ deployment except when the instance is a SQL Server instance that has an option group that is associated with mirroring; in this case, the instance becomes a mirrored AZ deployment and not a single-AZ deployment.

If your intent is to replace your original DB instance with the new, restored DB instance, then rename your original DB instance before you call the `RestoreDBInstanceFromDBSnapshot` action. RDS does not allow two DB instances with the same name. Once you have renamed your original DB instance with a different identifier, then you can pass the original name of the DB instance as the `DBInstanceIdentifier` in the call to the `RestoreDBInstanceFromDBSnapshot` action. The result is that you will replace the original DB instance with the DB instance created from the snapshot.

If you are restoring from a shared manual DB snapshot, the `DBSnapshotIdentifier` must be the ARN of the shared DB snapshot.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

AutoMinorVersionUpgrade

Indicates that minor version upgrades will be applied automatically to the DB instance during the maintenance window.

Type: Boolean

Required: No

AvailabilityZone

The EC2 Availability Zone that the database instance will be created in.

Default: A random, system-chosen Availability Zone.

Constraint: You cannot specify the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to `true`.

Example: `us-east-1a`

Type: String

Required: No

CopyTagsToSnapshot

True to copy all tags from the restored DB instance to snapshots of the DB instance; otherwise false. The default is false.

Type: Boolean

Required: No

DBInstanceClass

The compute and memory capacity of the Amazon RDS DB instance.

Valid Values: `db.t1.micro` | `db.m1.small` | `db.m1.medium` | `db.m1.large` | `db.m1.xlarge` | `db.m2.2xlarge` | `db.m2.4xlarge` | `db.m3.medium` | `db.m3.large` | `db.m3.xlarge` | `db.m3.2xlarge` | `db.m4.large` | `db.m4.xlarge` | `db.m4.2xlarge` | `db.m4.4xlarge` | `db.m4.10xlarge` | `db.r3.large` | `db.r3.xlarge` | `db.r3.2xlarge` | `db.r3.4xlarge` | `db.r3.8xlarge` | `db.t2.micro` | `db.t2.small` | `db.t2.medium` | `db.t2.large`

Type: String

Required: No

DBInstanceIdentifier

Name of the DB instance to create from the DB snapshot. This parameter isn't case-sensitive.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens (1 to 15 for SQL Server)
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Example: `my-snapshot-id`

Type: String

Required: Yes

DBName

The database name for the restored DB instance.

Note

This parameter doesn't apply to the MySQL, PostgreSQL, or MariaDB engines.

Type: String

Required: No

DBSnapshotIdentifier

The identifier for the DB snapshot to restore from.

Constraints:

- Must contain from 1 to 255 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

If you are restoring from a shared manual DB snapshot, the `DBSnapshotIdentifier` must be the ARN of the shared DB snapshot.

Type: String

Required: Yes

DBSubnetGroupName

The DB subnet group name to use for the new instance.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Domain

Specify the Active Directory Domain to restore the instance in.

Type: String

Required: No

DomainIAMRoleName

Specify the name of the IAM role to be used when making API calls to the Directory Service.

Type: String

Required: No

Engine

The database engine to use for the new instance.

Default: The same as source

Constraint: Must be compatible with the engine of the source

Valid Values: `MySQL` | `mariadb` | `oracle-se1` | `oracle-se` | `oracle-ee` | `sqlserver-ee` | `sqlserver-se` | `sqlserver-ex` | `sqlserver-web` | `postgres` | `aurora`

Type: String

Required: No

IOPS

Specifies the amount of provisioned IOPS for the DB instance, expressed in I/O operations per second. If this parameter is not specified, the IOPS value will be taken from the backup. If this parameter is set to 0, the new instance will be converted to a non-PIOPS instance, which will take

additional time, though your DB instance will be available for connections before the conversion starts.

Constraints: Must be an integer greater than 1000.

SQL Server

Setting the IOPS value for the SQL Server database engine is not supported.

Type: Integer

Required: No

LicenseModel

License model information for the restored DB instance.

Default: Same as source.

Valid values: `license-included` | `bring-your-own-license` | `general-public-license`

Type: String

Required: No

MultiAZ

Specifies if the DB instance is a Multi-AZ deployment.

Constraint: You cannot specify the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to `true`.

Type: Boolean

Required: No

OptionGroupName

The name of the option group to be used for the restored DB instance.

Permanent options, such as the TDE option for Oracle Advanced Security TDE, cannot be removed from an option group, and that option group cannot be removed from a DB instance once it is associated with a DB instance

Type: String

Required: No

Port

The port number on which the database accepts connections.

Default: The same port as the original DB instance

Constraints: Value must be 1150–65535

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance. A value of `true` specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address. A value of `false` specifies an internal instance with a DNS name that resolves to a private IP address.

Default: The default behavior varies depending on whether a VPC has been requested or not. The following list shows the default behavior in each case.

- **Default VPC:** `true`
- **VPC:** `false`

If no DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be publicly accessible. If a specific DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be private.

Type: Boolean

Required: No

StorageType

Specifies the storage type to be associated with the DB instance.

Valid values: `standard` | `gp2` | `io1`

If you specify `io1`, you must also include a value for the `Iops` parameter.

Default: `iol` if the `Iops` parameter is specified; otherwise `standard`

Type: String

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TdeCredentialArn

The ARN from the Key Store with which to associate the instance for TDE encryption.

Type: String

Required: No

TdeCredentialPassword

The password for the given ARN from the Key Store in order to access the device.

Type: String

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance \(p. 42\)](#)
- [DeleteDBInstance \(p. 85\)](#)
- [ModifyDBInstance \(p. 204\)](#)

This data type is used as a response element in the [DescribeDBInstances \(p. 124\)](#) action.

Type: [DBInstance \(p. 304\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 360\)](#).

AuthorizationNotFound

Specified CIDRIP or EC2 security group is not authorized for the specified DB security group.

RDS may not also be authorized via IAM to perform necessary actions on your behalf.

HTTP Status Code: 404

DBInstanceAlreadyExists

User already has a DB instance with the given identifier.

HTTP Status Code: 400

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

DBSnapshotNotFound

DBSnapshotIdentifier does not refer to an existing DB snapshot.

HTTP Status Code: 404

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DomainNotFoundFault

Domain does not refer to an existing Active Directory Domain.

HTTP Status Code: 404

InstanceQuotaExceeded

Request would result in user exceeding the allowed number of DB instances.

HTTP Status Code: 400

InsufficientDBInstanceCapacity

Specified DB instance class is not available in the specified Availability Zone.

HTTP Status Code: 400

InvalidDBSnapshotState

The state of the DB snapshot does not allow deletion.

HTTP Status Code: 400

InvalidRestoreFault

Cannot restore from vpc backup to non-vpc DB instance.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

ProvisionedIopsNotAvailableInAZFault

Provisioned IOPS not available in the specified Availability Zone.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageTypeNotSupported

StorageType specified cannot be associated with the DB Instance.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/
```

```
?Action=RestoreDBInstanceFromDBSnapshot
&DBInstanceIdentifier=mysqlldb-restored
&DBSnapshotIdentifier=rds%3Amysqldb-2014-04-22-08-15
&SignatureMethod=HmacSHA256
&SignatureVersion=4
&Version=2014-09-01
&X-Amz-Algorithm=AWS4-HMAC-SHA256
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request
&X-Amz-Date=20140428T232655Z
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-
amz-date
&X-Amz-
Signature=78ac761e8c8f54a8c0727f4e67ad0a766fbb0024510b9aa34ea6d1f7df52fe92
```

Sample Response

```
<RestoreDBInstanceFromDBSnapshotResponse xmlns="http://rds.amazonaws.com/
doc/2014-09-01/" >
  <RestoreDBInstanceFromDBSnapshotResult>
    <DBInstance>
      <BackupRetentionPeriod>7</BackupRetentionPeriod>
      <MultiAZ>>false</MultiAZ>
      <DBInstanceStatus>creating</DBInstanceStatus>
      <VpcSecurityGroups/>
      <DBInstanceIdentifier>mysqldb-restored</DBInstanceIdentifier>
      <PreferredBackupWindow>08:14-08:44</PreferredBackupWindow>
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</
PreferredMaintenanceWindow>
      <ReadReplicaDBInstanceIdentifiers/>
      <Engine>mysql</Engine>
      <PendingModifiedValues/>
      <LicenseModel>general-public-license</LicenseModel>
      <EngineVersion>5.6.13</EngineVersion>
      <DBParameterGroups>
        <DBParameterGroup>
          <ParameterApplyStatus>in-sync</ParameterApplyStatus>
          <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>
        </DBParameterGroup>
      </DBParameterGroups>
      <OptionGroupMemberships>
        <OptionGroupMembership>
          <OptionGroupName>default:mysql-5-6</OptionGroupName>
          <Status>pending-apply</Status>
        </OptionGroupMembership>
      </OptionGroupMemberships>
      <PubliclyAccessible>>true</PubliclyAccessible>
      <DBSecurityGroups>
        <DBSecurityGroup>
          <Status>active</Status>
          <DBSecurityGroupName>default</DBSecurityGroupName>
        </DBSecurityGroup>
      </DBSecurityGroups>
      <DBName>mysqldb</DBName>
      <AutoMinorVersionUpgrade>>true</AutoMinorVersionUpgrade>
      <AllocatedStorage>100</AllocatedStorage>
      <MasterUsername>myawsuser</MasterUsername>
      <DBInstanceClass>db.m1.medium</DBInstanceClass>
```

```
</DBInstance>  
</RestoreDBInstanceFromDBSnapshotResult>  
<ResponseMetadata>  
  <RequestId>863fd73e-be2b-11d3-855b-576787000e19</RequestId>  
</ResponseMetadata>  
</RestoreDBInstanceFromDBSnapshotResponse>
```

RestoreDBInstanceToPointInTime

Restores a DB instance to an arbitrary point in time. You can restore to any point in time before the time identified by the `LatestRestorableTime` property. You can restore to a point up to the number of days specified by the `BackupRetentionPeriod` property.

The target database is created with most of the original configuration, but in a system-selected availability zone, with the default security group, the default subnet group, and the default DB parameter group. By default, the new DB instance is created as a single-AZ deployment except when the instance is a SQL Server instance that has an option group that is associated with mirroring; in this case, the instance becomes a mirrored deployment and not a single-AZ deployment.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

AutoMinorVersionUpgrade

Indicates that minor version upgrades will be applied automatically to the DB instance during the maintenance window.

Type: Boolean

Required: No

AvailabilityZone

The EC2 Availability Zone that the database instance will be created in.

Default: A random, system-chosen Availability Zone.

Constraint: You cannot specify the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to true.

Example: `us-east-1a`

Type: String

Required: No

CopyTagsToSnapshot

True to copy all tags from the restored DB instance to snapshots of the DB instance; otherwise false. The default is false.

Type: Boolean

Required: No

DBInstanceClass

The compute and memory capacity of the Amazon RDS DB instance.

Valid Values: `db.t1.micro` | `db.m1.small` | `db.m1.medium` | `db.m1.large` | `db.m1.xlarge` | `db.m2.2xlarge` | `db.m2.4xlarge` | `db.m3.medium` | `db.m3.large` | `db.m3.xlarge` | `db.m3.2xlarge` | `db.m4.large` | `db.m4.xlarge` | `db.m4.2xlarge` | `db.m4.4xlarge` | `db.m4.10xlarge` | `db.r3.large` | `db.r3.xlarge` | `db.r3.2xlarge` | `db.r3.4xlarge` | `db.r3.8xlarge` | `db.t2.micro` | `db.t2.small` | `db.t2.medium` | `db.t2.large`

Default: The same `DBInstanceClass` as the original DB instance.

Type: String

Required: No

DBName

The database name for the restored DB instance.

Note

This parameter is not used for the MySQL or MariaDB engines.

Type: String

Required: No

DBSubnetGroupName

The DB subnet group name to use for the new instance.

Constraints: Must contain no more than 255 alphanumeric characters, periods, underscores, spaces, or hyphens. Must not be default.

Example: `mySubnetgroup`

Type: String

Required: No

Domain

Specify the Active Directory Domain to restore the instance in.

Type: String

Required: No

DomainIAMRoleName

Specify the name of the IAM role to be used when making API calls to the Directory Service.

Type: String

Required: No

Engine

The database engine to use for the new instance.

Default: The same as source

Constraint: Must be compatible with the engine of the source

Valid Values: `MySQL` | `mariadb` | `oracle-se1` | `oracle-se` | `oracle-ee` | `sqlserver-ee` | `sqlserver-se` | `sqlserver-ex` | `sqlserver-web` | `postgres` | `aurora`

Type: String

Required: No

IOPS

The amount of Provisioned IOPS (input/output operations per second) to be initially allocated for the DB instance.

Constraints: Must be an integer greater than 1000.

SQL Server

Setting the IOPS value for the SQL Server database engine is not supported.

Type: Integer

Required: No

LicenseModel

License model information for the restored DB instance.

Default: Same as source.

Valid values: `license-included` | `bring-your-own-license` | `general-public-license`

Type: String

Required: No

MultiAZ

Specifies if the DB instance is a Multi-AZ deployment.

Constraint: You cannot specify the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to `true`.

Type: Boolean

Required: No

OptionGroupName

The name of the option group to be used for the restored DB instance.

Permanent options, such as the TDE option for Oracle Advanced Security TDE, cannot be removed from an option group, and that option group cannot be removed from a DB instance once it is associated with a DB instance

Type: String

Required: No

Port

The port number on which the database accepts connections.

Constraints: Value must be 1150-65535

Default: The same port as the original DB instance.

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance. A value of true specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address. A value of false specifies an internal instance with a DNS name that resolves to a private IP address.

Default: The default behavior varies depending on whether a VPC has been requested or not. The following list shows the default behavior in each case.

- **Default VPC:**true

- **VPC:**false

If no DB subnet group has been specified as part of the request and the PubliclyAccessible value has not been set, the DB instance will be publicly accessible. If a specific DB subnet group has been specified as part of the request and the PubliclyAccessible value has not been set, the DB instance will be private.

Type: Boolean

Required: No

RestoreTime

The date and time to restore from.

Valid Values: Value must be a time in Universal Coordinated Time (UTC) format

Constraints:

- Must be before the latest restorable time for the DB instance
- Cannot be specified if UseLatestRestorableTime parameter is true

Example: 2009-09-07T23:45:00Z

Type: Timestamp

Required: No

SourceDBInstanceIdentifier

The identifier of the source DB instance from which to restore.

Constraints:

- Must be the identifier of an existing database instance
- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

StorageType

Specifies the storage type to be associated with the DB instance.

Valid values: `standard` | `gp2` | `io1`

If you specify `io1`, you must also include a value for the `Iops` parameter.

Default: `io1` if the `Iops` parameter is specified; otherwise `standard`

Type: String

Required: No

Tags.Tag.N

A list of tags.

Type: array of [Tag \(p. 354\)](#) objects

Required: No

TargetDBInstanceIdentifier

The name of the new database instance to be created.

Constraints:

- Must contain from 1 to 63 alphanumeric characters or hyphens
- First character must be a letter
- Cannot end with a hyphen or contain two consecutive hyphens

Type: String

Required: Yes

TdeCredentialArn

The ARN from the Key Store with which to associate the instance for TDE encryption.

Type: String

Required: No

TdeCredentialPassword

The password for the given ARN from the Key Store in order to access the device.

Type: String

Required: No

UseLatestRestorableTime

Specifies whether (`true`) or not (`false`) the DB instance is restored from the latest backup time.

Default: `false`

Constraints: Cannot be specified if `RestoreTime` parameter is provided.

Type: Boolean

Required: No

Response Elements

The following element is returned by the service.

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance](#) (p. 42)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)

This data type is used as a response element in the [DescribeDBInstances](#) (p. 124) action.

Type: [DBInstance](#) (p. 304) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

AuthorizationNotFound

Specified CIDRIP or EC2 security group is not authorized for the specified DB security group.

RDS may not also be authorized via IAM to perform necessary actions on your behalf.

HTTP Status Code: 404

DBInstanceAlreadyExists

User already has a DB instance with the given identifier.

HTTP Status Code: 400

DBInstanceNotFound

DBInstanceIdentifier does not refer to an existing DB instance.

HTTP Status Code: 404

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.

HTTP Status Code: 404

DBSubnetGroupDoesNotCoverEnoughAZs

Subnets in the DB subnet group should cover at least two Availability Zones unless there is only one Availability Zone.

HTTP Status Code: 400

DBSubnetGroupNotFoundFault

DBSubnetGroupName does not refer to an existing DB subnet group.

HTTP Status Code: 404

DomainNotFoundFault

Domain does not refer to an existing Active Directory Domain.

HTTP Status Code: 404

InstanceQuotaExceeded

Request would result in user exceeding the allowed number of DB instances.

HTTP Status Code: 400

InsufficientDBInstanceCapacity

Specified DB instance class is not available in the specified Availability Zone.

HTTP Status Code: 400

InvalidDBInstanceState

The specified DB instance is not in the *available* state.

HTTP Status Code: 400

InvalidRestoreFault

Cannot restore from vpc backup to non-vpc DB instance.

HTTP Status Code: 400

InvalidSubnet

The requested subnet is invalid, or multiple subnets were requested that are not all in a common VPC.

HTTP Status Code: 400

InvalidVPCNetworkStateFault

DB subnet group does not cover all Availability Zones after it is created because users' change.

HTTP Status Code: 400

KMSKeyNotAccessibleFault

Error accessing KMS key.

HTTP Status Code: 400

OptionGroupNotFoundFault

The specified option group could not be found.

HTTP Status Code: 404

PointInTimeRestoreNotEnabled

SourceDBInstanceIdentifier refers to a DB instance with *BackupRetentionPeriod* equal to 0.

HTTP Status Code: 400

ProvisionedIopsNotAvailableInAZFault

Provisioned IOPS not available in the specified Availability Zone.

HTTP Status Code: 400

StorageQuotaExceeded

Request would result in user exceeding the allowed amount of storage available across all DB instances.

HTTP Status Code: 400

StorageTypeNotSupported

StorageType specified cannot be associated with the DB Instance.

HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
  ?Action=RestoreDBInstanceToPointInTime  
  &SignatureMethod=HmacSHA256  
  &SignatureVersion=4  
  &SourceDBInstanceIdentifier=mysqldb  
  &TargetDBInstanceIdentifier=mysqldb-pitr  
  &UseLatestRestorableTime=true  
  &Version=2014-09-01  
  &X-Amz-Algorithm=AWS4-HMAC-SHA256  
  &X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
  &X-Amz-Date=20140428T233051Z  
  &X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
  &X-Amz-  
Signature=087a8eb41cblab0fc9ec1575f23e73757ffc6ale42d7d2b30b9cc0be988cff97
```

Sample Response

```
<RestoreDBInstanceToPointInTimeResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <RestoreDBInstanceToPointInTimeResult>  
    <DBInstance>  
      <BackupRetentionPeriod>7</BackupRetentionPeriod>  
      <DBInstanceStatus>creating</DBInstanceStatus>  
      <MultiAZ>>false</MultiAZ>  
      <VpcSecurityGroups/>  
      <DBInstanceIdentifier>mysqldb-pitr</DBInstanceIdentifier>  
      <PreferredBackupWindow>08:14-08:44</PreferredBackupWindow>  
      <PreferredMaintenanceWindow>fri:04:50-fri:05:20</  
PreferredMaintenanceWindow>  
      <ReadReplicaDBInstanceIdentifiers/>  
      <Engine>mysql</Engine>  
      <PendingModifiedValues/>  
      <LicenseModel>general-public-license</LicenseModel>  
      <DBParameterGroups>  
        <DBParameterGroup>  
          <ParameterApplyStatus>in-sync</ParameterApplyStatus>  
          <DBParameterGroupName>default.mysql5.6</DBParameterGroupName>  
        </DBParameterGroup>  
      </DBParameterGroups>  
      <EngineVersion>5.6.13</EngineVersion>  
      <OptionGroupMemberships>  
        <OptionGroupMembership>  
          <OptionGroupName>default:mysql-5-6</OptionGroupName>  
          <Status>pending-apply</Status>  
        </OptionGroupMembership>  
      </OptionGroupMemberships>  
      <PubliclyAccessible>>true</PubliclyAccessible>  
      <DBSecurityGroups>  
        <DBSecurityGroup>
```

```
    <Status>active</Status>
    <DBSecurityGroupName>default</DBSecurityGroupName>
  </DBSecurityGroup>
</DBSecurityGroups>
<DBName>mysqldb</DBName>
<AutoMinorVersionUpgrade>true</AutoMinorVersionUpgrade>
<AllocatedStorage>100</AllocatedStorage>
<MasterUsername>myawsuser</MasterUsername>
<DBInstanceClass>db.m1.medium</DBInstanceClass>
</DBInstance>
</RestoreDBInstanceToPointInTimeResult>
<ResponseMetadata>
  <RequestId>13447c70-be2c-11d3-f4c6-37db295f7674</RequestId>
</ResponseMetadata>
</RestoreDBInstanceToPointInTimeResponse>
```

RevokeDBSecurityGroupIngress

Revokes ingress from a DBSecurityGroup for previously authorized IP ranges or EC2 or VPC Security Groups. Required parameters for this API are one of CIDRIP, EC2SecurityGroupId for VPC, or (EC2SecurityGroupOwnerId and either EC2SecurityGroupName or EC2SecurityGroupId).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 358).

CIDRIP

The IP range to revoke access from. Must be a valid CIDR range. If CIDRIP is specified, EC2SecurityGroupName, EC2SecurityGroupId and EC2SecurityGroupOwnerId cannot be provided.

Type: String

Required: No

DBSecurityGroupName

The name of the DB security group to revoke ingress from.

Type: String

Required: Yes

EC2SecurityGroupId

The id of the EC2 security group to revoke access from. For VPC DB security groups, EC2SecurityGroupId must be provided. Otherwise, EC2SecurityGroupOwnerId and either EC2SecurityGroupName or EC2SecurityGroupId must be provided.

Type: String

Required: No

EC2SecurityGroupName

The name of the EC2 security group to revoke access from. For VPC DB security groups, EC2SecurityGroupId must be provided. Otherwise, EC2SecurityGroupOwnerId and either EC2SecurityGroupName or EC2SecurityGroupId must be provided.

Type: String

Required: No

EC2SecurityGroupOwnerId

The AWS Account Number of the owner of the EC2 security group specified in the EC2SecurityGroupName parameter. The AWS Access Key ID is not an acceptable value. For VPC DB security groups, EC2SecurityGroupId must be provided. Otherwise, EC2SecurityGroupOwnerId and either EC2SecurityGroupName or EC2SecurityGroupId must be provided.

Type: String

Required: No

Response Elements

The following element is returned by the service.

DBSecurityGroup

Contains the result of a successful invocation of the following actions:

- [DescribeDBSecurityGroups](#) (p. 136)
- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [CreateDBSecurityGroup](#) (p. 64)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

This data type is used as a response element in the [DescribeDBSecurityGroups](#) (p. 136) action.

Type: [DBSecurityGroup](#) (p. 312) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 360).

AuthorizationNotFound

Specified CIDRIP or EC2 security group is not authorized for the specified DB security group. RDS may not also be authorized via IAM to perform necessary actions on your behalf.
HTTP Status Code: 404

DBSecurityGroupNotFound

DBSecurityGroupName does not refer to an existing DB security group.
HTTP Status Code: 404

InvalidDBSecurityGroupState

The state of the DB security group does not allow deletion.
HTTP Status Code: 400

Example

Sample Request

```
https://rds.us-east-1.amazonaws.com/  
?Action=RevokeDBSecurityGroupIngress  
&CIDRIP=192.0.0.1%2F32  
&DBSecurityGroupName=mydbsecuritygroup01  
&SignatureMethod=HmacSHA256  
&SignatureVersion=4  
&Version=2014-09-01  
&X-Amz-Algorithm=AWS4-HMAC-SHA256  
&X-Amz-Credential=AKIADQKE4SARGYLE/20140428/us-east-1/rds/aws4_request  
&X-Amz-Date=20140428T233956Z  
&X-Amz-SignedHeaders=content-type;host;user-agent;x-amz-content-sha256;x-  
amz-date  
&X-Amz-  
Signature=d9edabccacae36138704fb2b3cf6755ef08123862191b19d74582497b75e544a
```

Sample Response

```
<RevokeDBSecurityGroupIngressResponse xmlns="http://rds.amazonaws.com/  
doc/2014-09-01/">  
  <RevokeDBSecurityGroupIngressResult>  
    <DBSecurityGroup>  
      <EC2SecurityGroups/>  
      <DBSecurityGroupDescription>My new DBSecurityGroup</  
DBSecurityGroupDescription>  
      <IPRanges>  
        <IPRange>  
          <CIDRIP>192.0.0.1/32</CIDRIP>  
          <Status>revoking</Status>  
        </IPRange>
```

```
</IPRanges>
  <OwnerId>803#####</OwnerId>
  <DBSecurityGroupName>mydbsecuritygroup01</DBSecurityGroupName>
</DBSecurityGroup>
</RevokeDBSecurityGroupIngressResult>
<ResponseMetadata>
  <RequestId>579d8ba0-be2d-11d3-ae4f-ec568ed6b36</RequestId>
</ResponseMetadata>
</RevokeDBSecurityGroupIngressResponse>
```


Data Types

The Amazon Relational Database Service API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountQuota](#) (p. 287)
- [AvailabilityZone](#) (p. 288)
- [Certificate](#) (p. 289)
- [CharacterSet](#) (p. 290)
- [DBCluster](#) (p. 291)
- [DBClusterMember](#) (p. 295)
- [DBClusterOptionGroupStatus](#) (p. 296)
- [DBClusterParameterGroup](#) (p. 297)
- [DBClusterRole](#) (p. 298)
- [DBClusterSnapshot](#) (p. 299)
- [DBClusterSnapshotAttribute](#) (p. 301)
- [DBClusterSnapshotAttributesResult](#) (p. 302)
- [DBEngineVersion](#) (p. 303)
- [DBInstance](#) (p. 304)
- [DBInstanceStatusInfo](#) (p. 309)
- [DBParameterGroup](#) (p. 310)
- [DBParameterGroupStatus](#) (p. 311)
- [DBSecurityGroup](#) (p. 312)
- [DBSecurityGroupMembership](#) (p. 313)
- [DBSnapshot](#) (p. 314)
- [DBSnapshotAttribute](#) (p. 317)
- [DBSnapshotAttributesResult](#) (p. 318)
- [DBSubnetGroup](#) (p. 319)
- [DescribeDBLogFilesDetails](#) (p. 320)
- [DomainMembership](#) (p. 321)

- [EC2SecurityGroup](#) (p. 322)
- [Endpoint](#) (p. 323)
- [EngineDefaults](#) (p. 324)
- [Event](#) (p. 325)
- [EventCategoriesMap](#) (p. 326)
- [EventSubscription](#) (p. 327)
- [Filter](#) (p. 329)
- [IPRange](#) (p. 330)
- [Option](#) (p. 331)
- [OptionConfiguration](#) (p. 332)
- [OptionGroup](#) (p. 333)
- [OptionGroupMembership](#) (p. 334)
- [OptionGroupOption](#) (p. 335)
- [OptionGroupOptionSetting](#) (p. 337)
- [OptionSetting](#) (p. 338)
- [OptionVersion](#) (p. 339)
- [OrderableDBInstanceOption](#) (p. 340)
- [Parameter](#) (p. 342)
- [PendingMaintenanceAction](#) (p. 344)
- [PendingModifiedValues](#) (p. 345)
- [RecurringCharge](#) (p. 347)
- [ReservedDBInstance](#) (p. 348)
- [ReservedDBInstancesOffering](#) (p. 350)
- [ResourcePendingMaintenanceActions](#) (p. 351)
- [SourceRegion](#) (p. 352)
- [Subnet](#) (p. 353)
- [Tag](#) (p. 354)
- [Timezone](#) (p. 355)
- [UpgradeTarget](#) (p. 356)
- [VpcSecurityGroupMembership](#) (p. 357)

AccountQuota

Describes a quota for an AWS account, for example, the number of DB instances allowed.

Contents

AccountQuotaName

The name of the Amazon RDS quota for this AWS account.

Type: String

Required: No

Max

The maximum allowed value for the quota.

Type: Long

Required: No

Used

The amount currently used toward the quota maximum.

Type: Long

Required: No

AvailabilityZone

Contains Availability Zone information.

This data type is used as an element in the following data type:

- [OrderableDBInstanceOption](#) (p. 340)

Contents

Name

The name of the availability zone.

Type: String

Required: No

Certificate

A CA certificate for an AWS account.

Contents

CertificateArn

The Amazon Resource Name (ARN) for the certificate.

Type: String

Required: No

CertificateIdentifier

The unique key that identifies a certificate.

Type: String

Required: No

CertificateType

The type of the certificate.

Type: String

Required: No

Thumbprint

The thumbprint of the certificate.

Type: String

Required: No

ValidFrom

The starting date from which the certificate is valid.

Type: Timestamp

Required: No

ValidTill

The final date that the certificate continues to be valid.

Type: Timestamp

Required: No

CharacterSet

This data type is used as a response element in the action [DescribeDBEngineVersions](#) (p. 121).

Contents

CharacterSetDescription

The description of the character set.

Type: String

Required: No

CharacterSetName

The name of the character set.

Type: String

Required: No

DBCluster

Contains the result of a successful invocation of the following actions:

- [CreateDBCluster](#) (p. 30)
- [DeleteDBCluster](#) (p. 78)
- [FailoverDBCluster](#) (p. 189)
- [ModifyDBCluster](#) (p. 194)
- [RestoreDBClusterFromSnapshot](#) (p. 258)
- [RestoreDBClusterToPointInTime](#) (p. 263)

This data type is used as a response element in the [DescribeDBClusters](#) (p. 112) action.

Contents

AllocatedStorage

Specifies the allocated storage size in gigabytes (GB).

Type: Integer

Required: No

AssociatedRoles.DBClusterRole.N

Provides a list of the AWS Identity and Access Management (IAM) roles that are associated with the DB cluster. IAM roles that are associated with a DB cluster grant permission for the DB cluster to access other AWS services on your behalf.

Type: array of [DBClusterRole](#) (p. 298) objects

Required: No

AvailabilityZones.AvailabilityZone.N

Provides the list of EC2 Availability Zones that instances in the DB cluster can be created in.

Type: array of Strings

Required: No

BackupRetentionPeriod

Specifies the number of days for which automatic DB snapshots are retained.

Type: Integer

Required: No

CharacterSetName

If present, specifies the name of the character set that this cluster is associated with.

Type: String

Required: No

ClusterCreateTime

Specifies the time when the DB cluster was created, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

DatabaseName

Contains the name of the initial database of this DB cluster that was provided at create time, if one was specified when the DB cluster was created. This same name is returned for the life of the DB cluster.

Type: String

Required: No

DBClusterArn

The Amazon Resource Name (ARN) for the DB cluster.

Type: String

Required: No

DBClusterIdentifier

Contains a user-supplied DB cluster identifier. This identifier is the unique key that identifies a DB cluster.

Type: String

Required: No

DBClusterMembers.DBClusterMember.N

Provides the list of instances that make up the DB cluster.

Type: array of [DBClusterMember](#) (p. 295) objects

Required: No

DBClusterOptionGroupMemberships.DBClusterOptionGroup.N

Provides the list of option group memberships for this DB cluster.

Type: array of [DBClusterOptionGroupStatus](#) (p. 296) objects

Required: No

DBClusterParameterGroup

Specifies the name of the DB cluster parameter group for the DB cluster.

Type: String

Required: No

DbClusterResourceId

The region-unique, immutable identifier for the DB cluster. This identifier is found in AWS CloudTrail log entries whenever the KMS key for the DB cluster is accessed.

Type: String

Required: No

DBSubnetGroup

Specifies information on the subnet group associated with the DB cluster, including the name, description, and subnets in the subnet group.

Type: String

Required: No

EarliestRestorableTime

Specifies the earliest time to which a database can be restored with point-in-time restore.

Type: Timestamp

Required: No

Endpoint

Specifies the connection endpoint for the primary instance of the DB cluster.

Type: String

Required: No

Engine

Provides the name of the database engine to be used for this DB cluster.

Type: String

Required: No

EngineVersion

Indicates the database engine version.

Type: String

Required: No

HostedZoneId

Specifies the ID that Amazon Route 53 assigns when you create a hosted zone.

Type: String

Required: No

KmsKeyId

If `StorageEncrypted` is true, the KMS key identifier for the encrypted DB cluster.

Type: String

Required: No

LatestRestorableTime

Specifies the latest time to which a database can be restored with point-in-time restore.

Type: Timestamp

Required: No

MasterUsername

Contains the master username for the DB cluster.

Type: String

Required: No

MultiAZ

Specifies whether the DB cluster has instances in multiple Availability Zones.

Type: Boolean

Required: No

PercentProgress

Specifies the progress of the operation as a percentage.

Type: String

Required: No

Port

Specifies the port that the database engine is listening on.

Type: Integer

Required: No

PreferredBackupWindow

Specifies the daily time range during which automated backups are created if automated backups are enabled, as determined by the `BackupRetentionPeriod`.

Type: String

Required: No

PreferredMaintenanceWindow

Specifies the weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Type: String

Required: No

ReaderEndpoint

The reader endpoint for the DB cluster. The reader endpoint for a DB cluster load-balances connections across the Aurora Replicas that are available in a DB cluster. As clients request new connections to the reader endpoint, Aurora distributes the connection requests among the Aurora Replicas in the DB cluster. This functionality can help balance your read workload across multiple Aurora Replicas in your DB cluster.

If a failover occurs, and the Aurora Replica that you are connected to is promoted to be the primary instance, your connection will be dropped. To continue sending your read workload to other Aurora Replicas in the cluster, you can then reconnect to the reader endpoint.

Type: String

Required: No

ReadReplicaIdentifiers.ReadReplicaIdentifier.N

Contains one or more identifiers of the Read Replicas associated with this DB cluster.

Type: array of Strings

Required: No

ReplicationSourceIdentifier

Contains the identifier of the source DB cluster if this DB cluster is a Read Replica.

Type: String

Required: No

Status

Specifies the current state of this DB cluster.

Type: String

Required: No

StorageEncrypted

Specifies whether the DB cluster is encrypted.

Type: Boolean

Required: No

VpcSecurityGroups.VpcSecurityGroupMembership.N

Provides a list of VPC security groups that the DB cluster belongs to.

Type: array of [VpcSecurityGroupMembership](#) (p. 357) objects

Required: No

DBClusterMember

Contains information about an instance that is part of a DB cluster.

Contents

DBClusterParameterGroupStatus

Specifies the status of the DB cluster parameter group for this member of the DB cluster.

Type: String

Required: No

DBInstanceIdentifier

Specifies the instance identifier for this member of the DB cluster.

Type: String

Required: No

IsClusterWriter

Value that is `true` if the cluster member is the primary instance for the DB cluster and `false` otherwise.

Type: Boolean

Required: No

PromotionTier

A value that specifies the order in which an Aurora Replica is promoted to the primary instance after a failure of the existing primary instance. For more information, see [Fault Tolerance for an Aurora DB Cluster](#).

Type: Integer

Required: No

DBClusterOptionGroupStatus

Contains status information for a DB cluster option group.

Contents

DBClusterOptionGroupName

Specifies the name of the DB cluster option group.

Type: String

Required: No

Status

Specifies the status of the DB cluster option group.

Type: String

Required: No

DBClusterParameterGroup

Contains the result of a successful invocation of the [CreateDBClusterParameterGroup](#) (p. 36) or [CopyDBClusterParameterGroup](#) (p. 16) action.

This data type is used as a request parameter in the [DeleteDBClusterParameterGroup](#) (p. 81) action, and as a response element in the [DescribeDBClusterParameterGroups](#) (p. 106) action.

Contents

DBClusterParameterGroupArn

The Amazon Resource Name (ARN) for the DB cluster parameter group.

Type: String

Required: No

DBClusterParameterGroupName

Provides the name of the DB cluster parameter group.

Type: String

Required: No

DBParameterGroupFamily

Provides the name of the DB parameter group family that this DB cluster parameter group is compatible with.

Type: String

Required: No

Description

Provides the customer-specified description for this DB cluster parameter group.

Type: String

Required: No

DBClusterRole

Describes an AWS Identity and Access Management (IAM) role that is associated with a DB cluster.

Contents

RoleArn

The Amazon Resource Name (ARN) of the IAM role that is associated with the DB cluster.

Type: String

Required: No

Status

Describes the state of association between the IAM role and the DB cluster. The Status property returns one of the following values:

- `ACTIVE` - the IAM role ARN is associated with the DB cluster and can be used to access other AWS services on your behalf.
- `PENDING` - the IAM role ARN is being associated with the DB cluster.
- `INVALID` - the IAM role ARN is associated with the DB cluster, but the DB cluster is unable to assume the IAM role in order to access other AWS services on your behalf.

Type: String

Required: No

DBClusterSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBClusterSnapshot](#) (p. 39)
- [DeleteDBClusterSnapshot](#) (p. 83)

This data type is used as a response element in the [DescribeDBClusterSnapshots](#) (p. 117) action.

Contents

AllocatedStorage

Specifies the allocated storage size in gigabytes (GB).

Type: Integer

Required: No

AvailabilityZones.AvailabilityZone.N

Provides the list of EC2 Availability Zones that instances in the DB cluster snapshot can be restored in.

Type: array of Strings

Required: No

ClusterCreateTime

Specifies the time when the DB cluster was created, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

DBClusterIdentifier

Specifies the DB cluster identifier of the DB cluster that this DB cluster snapshot was created from.

Type: String

Required: No

DBClusterSnapshotArn

The Amazon Resource Name (ARN) for the DB cluster snapshot.

Type: String

Required: No

DBClusterSnapshotIdentifier

Specifies the identifier for the DB cluster snapshot.

Type: String

Required: No

Engine

Specifies the name of the database engine.

Type: String

Required: No

EngineVersion

Provides the version of the database engine for this DB cluster snapshot.

Type: String

Required: No

KmsKeyId

If `StorageEncrypted` is true, the KMS key identifier for the encrypted DB cluster snapshot.

Type: String

Required: No

LicenseModel

Provides the license model information for this DB cluster snapshot.

Type: String

Required: No

MasterUsername

Provides the master username for the DB cluster snapshot.

Type: String

Required: No

PercentProgress

Specifies the percentage of the estimated data that has been transferred.

Type: Integer

Required: No

Port

Specifies the port that the DB cluster was listening on at the time of the snapshot.

Type: Integer

Required: No

SnapshotCreateTime

Provides the time when the snapshot was taken, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

SnapshotType

Provides the type of the DB cluster snapshot.

Type: String

Required: No

Status

Specifies the status of this DB cluster snapshot.

Type: String

Required: No

StorageEncrypted

Specifies whether the DB cluster snapshot is encrypted.

Type: Boolean

Required: No

VpcId

Provides the VPC ID associated with the DB cluster snapshot.

Type: String

Required: No

DBClusterSnapshotAttribute

Contains the name and values of a manual DB cluster snapshot attribute.

Manual DB cluster snapshot attributes are used to authorize other AWS accounts to restore a manual DB cluster snapshot. For more information, see the [ModifyDBClusterSnapshotAttribute \(p. 201\)](#) API action.

Contents

AttributeName

The name of the manual DB cluster snapshot attribute.

The attribute named `restore` refers to the list of AWS accounts that have permission to copy or restore the manual DB cluster snapshot. For more information, see the [ModifyDBClusterSnapshotAttribute \(p. 201\)](#) API action.

Type: String

Required: No

AttributeValues.AttributeValue.N

The value(s) for the manual DB cluster snapshot attribute.

If the `AttributeName` field is set to `restore`, then this element returns a list of IDs of the AWS accounts that are authorized to copy or restore the manual DB cluster snapshot. If a value of `all` is in the list, then the manual DB cluster snapshot is public and available for any AWS account to copy or restore.

Type: array of Strings

Required: No

DBClusterSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBClusterSnapshotAttributes \(p. 115\)](#) API action.

Manual DB cluster snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB cluster snapshot. For more information, see the [ModifyDBClusterSnapshotAttribute \(p. 201\)](#) API action.

Contents

DBClusterSnapshotAttributes.DBClusterSnapshotAttribute.N

The list of attributes and values for the manual DB cluster snapshot.

Type: array of [DBClusterSnapshotAttribute \(p. 301\)](#) objects

Required: No

DBClusterSnapshotIdentifier

The identifier of the manual DB cluster snapshot that the attributes apply to.

Type: String

Required: No

DBEngineVersion

This data type is used as a response element in the action [DescribeDBEngineVersions](#) (p. 121).

Contents

DBEngineDescription

The description of the database engine.

Type: String

Required: No

DBEngineVersionDescription

The description of the database engine version.

Type: String

Required: No

DBParameterGroupFamily

The name of the DB parameter group family for the database engine.

Type: String

Required: No

DefaultCharacterSet

The default character set for new instances of this engine version, if the `CharacterSetName` parameter of the `CreateDBInstance` API is not specified.

Type: [CharacterSet](#) (p. 290) object

Required: No

Engine

The name of the database engine.

Type: String

Required: No

EngineVersion

The version number of the database engine.

Type: String

Required: No

SupportedCharacterSets.CharacterSet.N

A list of the character sets supported by this engine for the `CharacterSetName` parameter of the `CreateDBInstance` action.

Type: array of [CharacterSet](#) (p. 290) objects

Required: No

SupportedTimezones.Timezone.N

A list of the time zones supported by this engine for the `Timezone` parameter of the `CreateDBInstance` action.

Type: array of [Timezone](#) (p. 355) objects

Required: No

ValidUpgradeTarget.UpgradeTarget.N

A list of engine versions that this database engine version can be upgraded to.

Type: array of [UpgradeTarget](#) (p. 356) objects

Required: No

DBInstance

Contains the result of a successful invocation of the following actions:

- [CreateDBInstance](#) (p. 42)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)

This data type is used as a response element in the [DescribeDBInstances](#) (p. 124) action.

Contents

AllocatedStorage

Specifies the allocated storage size specified in gigabytes.

Type: Integer

Required: No

AutoMinorVersionUpgrade

Indicates that minor version patches are applied automatically.

Type: Boolean

Required: No

AvailabilityZone

Specifies the name of the Availability Zone the DB instance is located in.

Type: String

Required: No

BackupRetentionPeriod

Specifies the number of days for which automatic DB snapshots are retained.

Type: Integer

Required: No

CACertificateIdentifier

The identifier of the CA certificate for this DB instance.

Type: String

Required: No

CharacterSetName

If present, specifies the name of the character set that this instance is associated with.

Type: String

Required: No

CopyTagsToSnapshot

Specifies whether tags are copied from the DB instance to snapshots of the DB instance.

Type: Boolean

Required: No

DBClusterIdentifier

If the DB instance is a member of a DB cluster, contains the name of the DB cluster that the DB instance is a member of.

Type: String

Required: No

DBInstanceArn

The Amazon Resource Name (ARN) for the DB instance.

Type: String

Required: No

DBInstanceClass

Contains the name of the compute and memory capacity class of the DB instance.

Type: String

Required: No

DBInstanceIdentifier

Contains a user-supplied database identifier. This identifier is the unique key that identifies a DB instance.

Type: String

Required: No

DBInstancePort

Specifies the port that the DB instance listens on. If the DB instance is part of a DB cluster, this can be a different port than the DB cluster port.

Type: Integer

Required: No

DBInstanceStatus

Specifies the current state of this database.

Type: String

Required: No

DBInstanceResourceId

The region-unique, immutable identifier for the DB instance. This identifier is found in AWS CloudTrail log entries whenever the KMS key for the DB instance is accessed.

Type: String

Required: No

DBName

The meaning of this parameter differs according to the database engine you use. For example, this value returns MySQL, MariaDB, or PostgreSQL information when returning values from `CreateDBInstanceReadReplica` since Read Replicas are only supported for these engines.

MySQL, MariaDB, SQL Server, PostgreSQL, Amazon Aurora

Contains the name of the initial database of this instance that was provided at create time, if one was specified when the DB instance was created. This same name is returned for the life of the DB instance.

Type: String

Oracle

Contains the Oracle System ID (SID) of the created DB instance. Not shown when the returned parameters do not apply to an Oracle DB instance.

Type: String

Required: No

DBParameterGroups.DBParameterGroup.N

Provides the list of DB parameter groups applied to this DB instance.

Type: array of [DBParameterGroupStatus \(p. 311\)](#) objects

Required: No

DBSecurityGroups.DBSecurityGroup.N

Provides List of DB security group elements containing only `DBSecurityGroup.Name` and `DBSecurityGroup.Status` subelements.

Type: array of [DBSecurityGroupMembership \(p. 313\)](#) objects

Required: No

DBSubnetGroup

Specifies information on the subnet group associated with the DB instance, including the name, description, and subnets in the subnet group.

Type: [DBSubnetGroup \(p. 319\)](#) object

Required: No

DomainMemberships.DomainMembership.N

The Active Directory Domain membership records associated with the DB instance.

Type: array of [DomainMembership](#) (p. 321) objects

Required: No

Endpoint

Specifies the connection endpoint.

Type: [Endpoint](#) (p. 323) object

Required: No

Engine

Provides the name of the database engine to be used for this DB instance.

Type: String

Required: No

EngineVersion

Indicates the database engine version.

Type: String

Required: No

EnhancedMonitoringResourceArn

The Amazon Resource Name (ARN) of the Amazon CloudWatch Logs log stream that receives the Enhanced Monitoring metrics data for the DB instance.

Type: String

Required: No

InstanceCreateTime

Provides the date and time the DB instance was created.

Type: Timestamp

Required: No

Iops

Specifies the Provisioned IOPS (I/O operations per second) value.

Type: Integer

Required: No

KmsKeyId

If `StorageEncrypted` is true, the KMS key identifier for the encrypted DB instance.

Type: String

Required: No

LatestRestorableTime

Specifies the latest time to which a database can be restored with point-in-time restore.

Type: Timestamp

Required: No

LicenseModel

License model information for this DB instance.

Type: String

Required: No

MasterUsername

Contains the master username for the DB instance.

Type: String

Required: No

MonitoringInterval

The interval, in seconds, between points when Enhanced Monitoring metrics are collected for the DB instance.

Type: Integer

Required: No

MonitoringRoleArn

The ARN for the IAM role that permits RDS to send Enhanced Monitoring metrics to CloudWatch Logs.

Type: String

Required: No

MultiAZ

Specifies if the DB instance is a Multi-AZ deployment.

Type: Boolean

Required: No

OptionGroupMemberships.OptionGroupMembership.N

Provides the list of option group memberships for this DB instance.

Type: array of [OptionGroupMembership](#) (p. 334) objects

Required: No

PendingModifiedValues

Specifies that changes to the DB instance are pending. This element is only included when changes are pending. Specific changes are identified by subelements.

Type: [PendingModifiedValues](#) (p. 345) object

Required: No

PreferredBackupWindow

Specifies the daily time range during which automated backups are created if automated backups are enabled, as determined by the `BackupRetentionPeriod`.

Type: String

Required: No

PreferredMaintenanceWindow

Specifies the weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Type: String

Required: No

PromotionTier

A value that specifies the order in which an Aurora Replica is promoted to the primary instance after a failure of the existing primary instance. For more information, see [Fault Tolerance for an Aurora DB Cluster](#).

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance. A value of true specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address. A value of false specifies an internal instance with a DNS name that resolves to a private IP address.

Default: The default behavior varies depending on whether a VPC has been requested or not. The following list shows the default behavior in each case.

- **Default VPC:**true
- **VPC:**false

If no DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be publicly accessible. If a specific DB subnet group has been specified as part of the request and the `PubliclyAccessible` value has not been set, the DB instance will be private.

Type: Boolean

Required: No

ReadReplicaDBInstanceIdentifiers.ReadReplicaDBInstanceIdentifier.N

Contains one or more identifiers of the Read Replicas associated with this DB instance.

Type: array of Strings

Required: No

ReadReplicaSourceDBInstanceIdentifier

Contains the identifier of the source DB instance if this DB instance is a Read Replica.

Type: String

Required: No

SecondaryAvailabilityZone

If present, specifies the name of the secondary Availability Zone for a DB instance with multi-AZ support.

Type: String

Required: No

StatusInfos.DBInstanceStatusInfo.N

The status of a Read Replica. If the instance is not a Read Replica, this will be blank.

Type: array of [DBInstanceStatusInfo](#) (p. 309) objects

Required: No

StorageEncrypted

Specifies whether the DB instance is encrypted.

Type: Boolean

Required: No

StorageType

Specifies the storage type associated with DB instance.

Type: String

Required: No

TdeCredentialArn

The ARN from the key store with which the instance is associated for TDE encryption.

Type: String

Required: No

Timezone

The time zone of the DB instance. In most cases, the `Timezone` element is empty. `Timezone` content appears only for Microsoft SQL Server DB instances that were created with a time zone specified.

Type: String

Required: No

VpcSecurityGroups.VpcSecurityGroupMembership.N

Provides a list of VPC security group elements that the DB instance belongs to.

Type: array of [VpcSecurityGroupMembership](#) (p. 357) objects

Required: No

DBInstanceStatusInfo

Provides a list of status information for a DB instance.

Contents

Message

Details of the error if there is an error for the instance. If the instance is not in an error state, this value is blank.

Type: String

Required: No

Normal

Boolean value that is true if the instance is operating normally, or false if the instance is in an error state.

Type: Boolean

Required: No

Status

Status of the DB instance. For a StatusType of read replica, the values can be replicating, error, stopped, or terminated.

Type: String

Required: No

StatusType

This value is currently "read replication."

Type: String

Required: No

DBParameterGroup

Contains the result of a successful invocation of the [CreateDBParameterGroup \(p. 61\)](#) action.

This data type is used as a request parameter in the [DeleteDBParameterGroup \(p. 89\)](#) action, and as a response element in the [DescribeDBParameterGroups \(p. 131\)](#) action.

Contents

DBParameterGroupArn

The Amazon Resource Name (ARN) for the DB parameter group.

Type: String

Required: No

DBParameterGroupFamily

Provides the name of the DB parameter group family that this DB parameter group is compatible with.

Type: String

Required: No

DBParameterGroupName

Provides the name of the DB parameter group.

Type: String

Required: No

Description

Provides the customer-specified description for this DB parameter group.

Type: String

Required: No

DBParameterGroupStatus

The status of the DB parameter group.

This data type is used as a response element in the following actions:

- [CreateDBInstance](#) (p. 42)
- [CreateDBInstanceReadReplica](#) (p. 55)
- [DeleteDBInstance](#) (p. 85)
- [ModifyDBInstance](#) (p. 204)
- [RebootDBInstance](#) (p. 238)
- [RestoreDBInstanceFromDBSnapshot](#) (p. 268)

Contents

DBParameterGroupName

The name of the DP parameter group.

Type: String

Required: No

ParameterApplyStatus

The status of parameter updates.

Type: String

Required: No

DBSecurityGroup

Contains the result of a successful invocation of the following actions:

- [DescribeDBSecurityGroups](#) (p. 136)
- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [CreateDBSecurityGroup](#) (p. 64)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

This data type is used as a response element in the [DescribeDBSecurityGroups](#) (p. 136) action.

Contents

DBSecurityGroupArn

The Amazon Resource Name (ARN) for the DB security group.

Type: String

Required: No

DBSecurityGroupDescription

Provides the description of the DB security group.

Type: String

Required: No

DBSecurityGroupName

Specifies the name of the DB security group.

Type: String

Required: No

EC2SecurityGroups.EC2SecurityGroup.N

Contains a list of [EC2SecurityGroup](#) (p. 322) elements.

Type: array of [EC2SecurityGroup](#) (p. 322) objects

Required: No

IPRanges.IPRange.N

Contains a list of [IPRange](#) (p. 330) elements.

Type: array of [IPRange](#) (p. 330) objects

Required: No

OwnerId

Provides the AWS ID of the owner of a specific DB security group.

Type: String

Required: No

VpcId

Provides the VpcId of the DB security group.

Type: String

Required: No

DBSecurityGroupMembership

This data type is used as a response element in the following actions:

- [ModifyDBInstance](#) (p. 204)
- [RebootDBInstance](#) (p. 238)
- [RestoreDBInstanceFromDBSnapshot](#) (p. 268)
- [RestoreDBInstanceToPointInTime](#) (p. 275)

Contents

DBSecurityGroupName

The name of the DB security group.

Type: String

Required: No

Status

The status of the DB security group.

Type: String

Required: No

DBSnapshot

Contains the result of a successful invocation of the following actions:

- [CreateDBSnapshot](#) (p. 66)
- [DeleteDBSnapshot](#) (p. 93)

This data type is used as a response element in the [DescribeDBSnapshots](#) (p. 141) action.

Contents

AllocatedStorage

Specifies the allocated storage size in gigabytes (GB).

Type: Integer

Required: No

AvailabilityZone

Specifies the name of the Availability Zone the DB instance was located in at the time of the DB snapshot.

Type: String

Required: No

DBInstanceIdentifier

Specifies the DB instance identifier of the DB instance this DB snapshot was created from.

Type: String

Required: No

DBSnapshotArn

The Amazon Resource Name (ARN) for the DB snapshot.

Type: String

Required: No

DBSnapshotIdentifier

Specifies the identifier for the DB snapshot.

Type: String

Required: No

Encrypted

Specifies whether the DB snapshot is encrypted.

Type: Boolean

Required: No

Engine

Specifies the name of the database engine.

Type: String

Required: No

EngineVersion

Specifies the version of the database engine.

Type: String

Required: No

InstanceCreateTime

Specifies the time when the snapshot was taken, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

Iops

Specifies the Provisioned IOPS (I/O operations per second) value of the DB instance at the time of the snapshot.

Type: Integer

Required: No

KmsKeyId

If `Encrypted` is true, the KMS key identifier for the encrypted DB snapshot.

Type: String

Required: No

LicenseModel

License model information for the restored DB instance.

Type: String

Required: No

MasterUsername

Provides the master username for the DB snapshot.

Type: String

Required: No

OptionGroupName

Provides the option group name for the DB snapshot.

Type: String

Required: No

PercentProgress

The percentage of the estimated data that has been transferred.

Type: Integer

Required: No

Port

Specifies the port that the database engine was listening on at the time of the snapshot.

Type: Integer

Required: No

SnapshotCreateTime

Provides the time when the snapshot was taken, in Universal Coordinated Time (UTC).

Type: Timestamp

Required: No

SnapshotType

Provides the type of the DB snapshot.

Type: String

Required: No

SourceDBSnapshotIdentifier

The DB snapshot Arn that the DB snapshot was copied from. It only has value in case of cross customer or cross region copy.

Type: String

Required: No

SourceRegion

The region that the DB snapshot was created in or copied from.

Type: String

Required: No

Status

Specifies the status of this DB snapshot.

Type: String

Required: No

StorageType

Specifies the storage type associated with DB snapshot.

Type: String

Required: No

TdeCredentialArn

The ARN from the key store with which to associate the instance for TDE encryption.

Type: String

Required: No

Timezone

The time zone of the DB snapshot. In most cases, the `Timezone` element is empty. `Timezone` content appears only for snapshots taken from Microsoft SQL Server DB instances that were created with a time zone specified.

Type: String

Required: No

VpcId

Provides the VPC ID associated with the DB snapshot.

Type: String

Required: No

DBSnapshotAttribute

Contains the name and values of a manual DB snapshot attribute

Manual DB snapshot attributes are used to authorize other AWS accounts to restore a manual DB snapshot. For more information, see the [ModifyDBSnapshotAttribute \(p. 217\)](#) API.

Contents

AttributeName

The name of the manual DB snapshot attribute.

The attribute named `restore` refers to the list of AWS accounts that have permission to copy or restore the manual DB cluster snapshot. For more information, see the [ModifyDBSnapshotAttribute \(p. 217\)](#) API action.

Type: String

Required: No

AttributeValues.AttributeValue.N

The value or values for the manual DB snapshot attribute.

If the `AttributeName` field is set to `restore`, then this element returns a list of IDs of the AWS accounts that are authorized to copy or restore the manual DB snapshot. If a value of `all` is in the list, then the manual DB snapshot is public and available for any AWS account to copy or restore.

Type: array of Strings

Required: No

DBSnapshotAttributesResult

Contains the results of a successful call to the [DescribeDBSnapshotAttributes \(p. 139\)](#) API action.

Manual DB snapshot attributes are used to authorize other AWS accounts to copy or restore a manual DB snapshot. For more information, see the [ModifyDBSnapshotAttribute \(p. 217\)](#) API action.

Contents

DBSnapshotAttributes.DBSnapshotAttribute.N

The list of attributes and values for the manual DB snapshot.

Type: array of [DBSnapshotAttribute \(p. 317\)](#) objects

Required: No

DBSnapshotIdentifier

The identifier of the manual DB snapshot that the attributes apply to.

Type: String

Required: No

DBSubnetGroup

Contains the result of a successful invocation of the following actions:

- [CreateDBSubnetGroup](#) (p. 69)
- [ModifyDBSubnetGroup](#) (p. 220)
- [DescribeDBSubnetGroups](#) (p. 145)
- [DeleteDBSubnetGroup](#) (p. 95)

This data type is used as a response element in the [DescribeDBSubnetGroups](#) (p. 145) action.

Contents

DBSubnetGroupArn

The Amazon Resource Name (ARN) for the DB subnet group.

Type: String

Required: No

DBSubnetGroupDescription

Provides the description of the DB subnet group.

Type: String

Required: No

DBSubnetGroupName

The name of the DB subnet group.

Type: String

Required: No

SubnetGroupStatus

Provides the status of the DB subnet group.

Type: String

Required: No

Subnets.Subnet.N

Contains a list of [Subnet](#) (p. 353) elements.

Type: array of [Subnet](#) (p. 353) objects

Required: No

Vpclid

Provides the Vpclid of the DB subnet group.

Type: String

Required: No

DescribeDBLogFilesDetails

This data type is used as a response element to [DescribeDBLogFiles](#) (p. 128).

Contents

LastWritten

A POSIX timestamp when the last log entry was written.

Type: Long

Required: No

LogFileName

The name of the log file for the specified DB instance.

Type: String

Required: No

Size

The size, in bytes, of the log file for the specified DB instance.

Type: Long

Required: No

DomainMembership

An Active Directory Domain membership record associated with the DB instance.

Contents

Domain

The identifier of the Active Directory Domain.

Type: String

Required: No

FQDN

The fully qualified domain name of the Active Directory Domain.

Type: String

Required: No

IAMRoleName

The name of the IAM role to be used when making API calls to the Directory Service.

Type: String

Required: No

Status

The status of the DB instance's Active Directory Domain membership, such as joined, pending-join, failed etc).

Type: String

Required: No

EC2SecurityGroup

This data type is used as a response element in the following actions:

- [AuthorizeDBSecurityGroupIngress](#) (p. 13)
- [DescribeDBSecurityGroups](#) (p. 136)
- [RevokeDBSecurityGroupIngress](#) (p. 282)

Contents

EC2SecurityGroupId

Specifies the id of the EC2 security group.

Type: String

Required: No

EC2SecurityGroupName

Specifies the name of the EC2 security group.

Type: String

Required: No

EC2SecurityGroupOwnerId

Specifies the AWS ID of the owner of the EC2 security group specified in the `EC2SecurityGroupName` field.

Type: String

Required: No

Status

Provides the status of the EC2 security group. Status can be "authorizing", "authorized", "revoking", and "revoked".

Type: String

Required: No

Endpoint

This data type is used as a response element in the following actions:

- [CreateDBInstance](#) (p. 42)
- [DescribeDBInstances](#) (p. 124)
- [DeleteDBInstance](#) (p. 85)

Contents

Address

Specifies the DNS address of the DB instance.

Type: String

Required: No

HostedZoneId

Specifies the ID that Amazon Route 53 assigns when you create a hosted zone.

Type: String

Required: No

Port

Specifies the port that the database engine is listening on.

Type: Integer

Required: No

EngineDefaults

Contains the result of a successful invocation of the [DescribeEngineDefaultParameters](#) (p. 150) action.

Contents

DBParameterGroupFamily

Specifies the name of the DB parameter group family that the engine default parameters apply to.

Type: String

Required: No

Marker

An optional pagination token provided by a previous EngineDefaults request. If this parameter is specified, the response includes only records beyond the marker, up to the value specified by `MaxRecords`.

Type: String

Required: No

Parameters.Parameter.N

Contains a list of engine default parameters.

Type: array of [Parameter](#) (p. 342) objects

Required: No

Event

This data type is used as a response element in the [DescribeEvents \(p. 155\)](#) action.

Contents

Date

Specifies the date and time of the event.

Type: Timestamp

Required: No

EventCategories.EventCategory.N

Specifies the category for the event.

Type: array of Strings

Required: No

Message

Provides the text of this event.

Type: String

Required: No

SourceArn

The Amazon Resource Name (ARN) for the event.

Type: String

Required: No

SourceIdentifier

Provides the identifier for the source of the event.

Type: String

Required: No

SourceType

Specifies the source type for this event.

Type: String

Valid Values: `db-instance` | `db-parameter-group` | `db-security-group` | `db-snapshot` | `db-cluster` | `db-cluster-snapshot`

Required: No

EventCategoriesMap

Contains the results of a successful invocation of the [DescribeEventCategories](#) (p. 153) action.

Contents

EventCategories.EventCategory.N

The event categories for the specified source type

Type: array of Strings

Required: No

SourceType

The source type that the returned categories belong to

Type: String

Required: No

EventSubscription

Contains the results of a successful invocation of the [DescribeEventSubscriptions](#) (p. 159) action.

Contents

CustomerAwsId

The AWS customer account associated with the RDS event notification subscription.

Type: String

Required: No

CustSubscriptionId

The RDS event notification subscription Id.

Type: String

Required: No

Enabled

A Boolean value indicating if the subscription is enabled. True indicates the subscription is enabled.

Type: Boolean

Required: No

EventCategoriesList.EventCategory.N

A list of event categories for the RDS event notification subscription.

Type: array of Strings

Required: No

EventSubscriptionArn

The Amazon Resource Name (ARN) for the event subscription.

Type: String

Required: No

SnsTopicArn

The topic ARN of the RDS event notification subscription.

Type: String

Required: No

SourceIdsList.SourceId.N

A list of source IDs for the RDS event notification subscription.

Type: array of Strings

Required: No

SourceType

The source type for the RDS event notification subscription.

Type: String

Required: No

Status

The status of the RDS event notification subscription.

Constraints:

Can be one of the following: creating | modifying | deleting | active | no-permission | topic-not-exist

The status "no-permission" indicates that RDS no longer has permission to post to the SNS topic.

The status "topic-not-exist" indicates that the topic was deleted after the subscription was created.

Type: String

Required: No

SubscriptionCreationTime

The time the RDS event notification subscription was created.

Type: String
Required: No

Filter

This type is not currently supported.

Contents

Name

This parameter is not currently supported.

Type: String

Required: Yes

Values.Value.N

This parameter is not currently supported.

Type: array of Strings

Required: Yes

IPRange

This data type is used as a response element in the [DescribeDBSecurityGroups \(p. 136\)](#) action.

Contents

CIDRIP

Specifies the IP range.

Type: String

Required: No

Status

Specifies the status of the IP range. Status can be "authorizing", "authorized", "revoking", and "revoked".

Type: String

Required: No

Option

Option details.

Contents

DBSecurityGroupMemberships.DBSecurityGroup.N

If the option requires access to a port, then this DB security group allows access to the port.

Type: array of [DBSecurityGroupMembership \(p. 313\)](#) objects

Required: No

OptionDescription

The description of the option.

Type: String

Required: No

OptionName

The name of the option.

Type: String

Required: No

OptionSettings.OptionSetting.N

The option settings for this option.

Type: array of [OptionSetting \(p. 338\)](#) objects

Required: No

OptionVersion

The version of the option.

Type: String

Required: No

Permanent

Indicate if this option is permanent.

Type: Boolean

Required: No

Persistent

Indicate if this option is persistent.

Type: Boolean

Required: No

Port

If required, the port configured for this option to use.

Type: Integer

Required: No

VpcSecurityGroupMemberships.VpcSecurityGroupMembership.N

If the option requires access to a port, then this VPC security group allows access to the port.

Type: array of [VpcSecurityGroupMembership \(p. 357\)](#) objects

Required: No

OptionConfiguration

A list of all available options

Contents

DBSecurityGroupMemberships.DBSecurityGroupName.N

A list of DBSecurityGroupMemembrship name strings used for this option.

Type: array of Strings

Required: No

OptionName

The configuration of options to include in a group.

Type: String

Required: Yes

OptionSettings.OptionSetting.N

The option settings to include in an option group.

Type: array of [OptionSetting \(p. 338\)](#) objects

Required: No

OptionVersion

The version for the option.

Type: String

Required: No

Port

The optional port for the option.

Type: Integer

Required: No

VpcSecurityGroupMemberships.VpcSecurityGroupId.N

A list of VpcSecurityGroupMemembrship name strings used for this option.

Type: array of Strings

Required: No

OptionGroup

Contents

AllowsVpcAndNonVpcInstanceMemberships

Indicates whether this option group can be applied to both VPC and non-VPC instances. The value `true` indicates the option group can be applied to both VPC and non-VPC instances.

Type: Boolean

Required: No

EngineName

Indicates the name of the engine that this option group can be applied to.

Type: String

Required: No

MajorEngineVersion

Indicates the major engine version associated with this option group.

Type: String

Required: No

OptionGroupArn

The Amazon Resource Name (ARN) for the option group.

Type: String

Required: No

OptionGroupDescription

Provides a description of the option group.

Type: String

Required: No

OptionGroupName

Specifies the name of the option group.

Type: String

Required: No

Options.Option.N

Indicates what options are available in the option group.

Type: array of [Option \(p. 331\)](#) objects

Required: No

VpcId

If **AllowsVpcAndNonVpcInstanceMemberships** is `false`, this field is blank. If **AllowsVpcAndNonVpcInstanceMemberships** is `true` and this field is blank, then this option group can be applied to both VPC and non-VPC instances. If this field contains a value, then this option group can only be applied to instances that are in the VPC indicated by this field.

Type: String

Required: No

OptionGroupMembership

Provides information on the option groups the DB instance is a member of.

Contents

OptionGroupName

The name of the option group that the instance belongs to.

Type: String

Required: No

Status

The status of the DB instance's option group membership. Valid values are: `in-sync`, `pending-apply`, `pending-removal`, `pending-maintenance-apply`, `pending-maintenance-removal`, `applying`, `removing`, and `failed`.

Type: String

Required: No

OptionGroupOption

Available option.

Contents

DefaultPort

If the option requires a port, specifies the default port for the option.

Type: Integer

Required: No

Description

The description of the option.

Type: String

Required: No

EngineName

The name of the engine that this option can be applied to.

Type: String

Required: No

MajorEngineVersion

Indicates the major engine version that the option is available for.

Type: String

Required: No

MinimumRequiredMinorEngineVersion

The minimum required engine version for the option to be applied.

Type: String

Required: No

Name

The name of the option.

Type: String

Required: No

OptionGroupOptionSettings.OptionGroupOptionSetting.N

The option settings that are available (and the default value) for each option in an option group.

Type: array of [OptionGroupOptionSetting \(p. 337\)](#) objects

Required: No

OptionGroupOptionVersions.OptionVersion.N

The versions that are available for the option.

Type: array of [OptionVersion \(p. 339\)](#) objects

Required: No

OptionsConflictsWith.OptionConflictName.N

The options that conflict with this option.

Type: array of Strings

Required: No

OptionsDependedOn.OptionName.N

The options that are prerequisites for this option.

Type: array of Strings

Required: No

Permanent

Permanent options can never be removed from an option group. An option group containing a permanent option can't be removed from a DB instance.

Type: Boolean

Required: No

Persistent

Persistent options can't be removed from an option group while DB instances are associated with the option group. If you disassociate all DB instances from the option group, you can remove the persistent option from the option group.

Type: Boolean

Required: No

PortRequired

Specifies whether the option requires a port.

Type: Boolean

Required: No

OptionGroupOptionSetting

Option group option settings are used to display settings available for each option with their default values and other information. These values are used with the DescribeOptionGroupOptions action.

Contents

AllowedValues

Indicates the acceptable values for the option group option.

Type: String

Required: No

ApplyType

The DB engine specific parameter type for the option group option.

Type: String

Required: No

DefaultValue

The default value for the option group option.

Type: String

Required: No

IsModifiable

Boolean value where true indicates that this option group option can be changed from the default value.

Type: Boolean

Required: No

SettingDescription

The description of the option group option.

Type: String

Required: No

SettingName

The name of the option group option.

Type: String

Required: No

OptionSetting

Option settings are the actual settings being applied or configured for that option. It is used when you modify an option group or describe option groups. For example, the `NATIVE_NETWORK_ENCRYPTION` option has a setting called `SQLNET.ENCRYPTION_SERVER` that can have several different values.

Contents

AllowedValues

The allowed values of the option setting.

Type: String

Required: No

ApplyType

The DB engine specific parameter type.

Type: String

Required: No

DataType

The data type of the option setting.

Type: String

Required: No

DefaultValue

The default value of the option setting.

Type: String

Required: No

Description

The description of the option setting.

Type: String

Required: No

IsCollection

Indicates if the option setting is part of a collection.

Type: Boolean

Required: No

IsModifiable

A Boolean value that, when true, indicates the option setting can be modified from the default.

Type: Boolean

Required: No

Name

The name of the option that has settings that you can set.

Type: String

Required: No

Value

The current value of the option setting.

Type: String

Required: No

OptionVersion

The version for an option. Option group option versions are returned by the [DescribeOptionGroupOptions \(p. 162\)](#) action.

Contents

IsDefault

True if the version is the default version of the option; otherwise, false.

Type: Boolean

Required: No

Version

The version of the option.

Type: String

Required: No

OrderableDBInstanceOption

Contains a list of available options for a DB instance

This data type is used as a response element in the [DescribeOrderableDBInstanceOptions](#) (p. 171) action.

Contents

AvailabilityZones.AvailabilityZone.N

A list of Availability Zones for the orderable DB instance.

Type: array of [AvailabilityZone](#) (p. 288) objects

Required: No

DBInstanceClass

The DB instance class for the orderable DB instance.

Type: String

Required: No

Engine

The engine type of the orderable DB instance.

Type: String

Required: No

EngineVersion

The engine version of the orderable DB instance.

Type: String

Required: No

LicenseModel

The license model for the orderable DB instance.

Type: String

Required: No

MultiAZCapable

Indicates whether this orderable DB instance is multi-AZ capable.

Type: Boolean

Required: No

ReadReplicaCapable

Indicates whether this orderable DB instance can have a Read Replica.

Type: Boolean

Required: No

StorageType

Indicates the storage type for this orderable DB instance.

Type: String

Required: No

SupportsEnhancedMonitoring

Indicates whether the DB instance supports enhanced monitoring at intervals from 1 to 60 seconds.

Type: Boolean

Required: No

SupportsIOPS

Indicates whether this orderable DB instance supports provisioned IOPS.

Type: Boolean

Required: No

SupportsStorageEncryption

Indicates whether this orderable DB instance supports encrypted storage.

Type: Boolean

Required: No

Vpc

Indicates whether this is a VPC orderable DB instance.

Type: Boolean

Required: No

Parameter

This data type is used as a request parameter in the [ModifyDBParameterGroup](#) (p. 215) and [ResetDBParameterGroup](#) (p. 249) actions.

This data type is used as a response element in the [DescribeEngineDefaultParameters](#) (p. 150) and [DescribeDBParameters](#) (p. 133) actions.

Contents

AllowedValues

Specifies the valid range of values for the parameter.

Type: String

Required: No

ApplyMethod

Indicates when to apply parameter updates.

Type: String

Valid Values: `immediate` | `pending-reboot`

Required: No

ApplyType

Specifies the engine specific parameters type.

Type: String

Required: No

DataType

Specifies the valid data type for the parameter.

Type: String

Required: No

Description

Provides a description of the parameter.

Type: String

Required: No

IsModifiable

Indicates whether (`true`) or not (`false`) the parameter can be modified. Some parameters have security or operational implications that prevent them from being changed.

Type: Boolean

Required: No

MinimumEngineVersion

The earliest engine version to which the parameter can apply.

Type: String

Required: No

ParameterName

Specifies the name of the parameter.

Type: String

Required: No

ParameterValue

Specifies the value of the parameter.

Type: String

Required: No

Source

Indicates the source of the parameter value.

Type: String

Required: No

PendingMaintenanceAction

Provides information about a pending maintenance action for a resource.

Contents

Action

The type of pending maintenance action that is available for the resource.

Type: String

Required: No

AutoAppliedAfterDate

The date of the maintenance window when the action will be applied. The maintenance action will be applied to the resource during its first maintenance window after this date. If this date is specified, any `next-maintenance` opt-in requests are ignored.

Type: Timestamp

Required: No

CurrentApplyDate

The effective date when the pending maintenance action will be applied to the resource. This date takes into account opt-in requests received from the [ApplyPendingMaintenanceAction \(p. 11\)](#) API, the `AutoAppliedAfterDate`, and the `ForcedApplyDate`. This value is blank if an opt-in request has not been received and nothing has been specified as `AutoAppliedAfterDate` or `ForcedApplyDate`.

Type: Timestamp

Required: No

Description

A description providing more detail about the maintenance action.

Type: String

Required: No

ForcedApplyDate

The date when the maintenance action will be automatically applied. The maintenance action will be applied to the resource on this date regardless of the maintenance window for the resource. If this date is specified, any `immediate` opt-in requests are ignored.

Type: Timestamp

Required: No

OptInStatus

Indicates the type of opt-in request that has been received for the resource.

Type: String

Required: No

PendingModifiedValues

This data type is used as a response element in the [ModifyDBInstance](#) (p. 204) action.

Contents

AllocatedStorage

Contains the new `AllocatedStorage` size for the DB instance that will be applied or is in progress.

Type: Integer

Required: No

BackupRetentionPeriod

Specifies the pending number of days for which automated backups are retained.

Type: Integer

Required: No

CACertificateIdentifier

Specifies the identifier of the CA certificate for the DB instance.

Type: String

Required: No

DBInstanceClass

Contains the new `DBInstanceClass` for the DB instance that will be applied or is in progress.

Type: String

Required: No

DBInstanceIdentifier

Contains the new `DBInstanceIdentifier` for the DB instance that will be applied or is in progress.

Type: String

Required: No

DBSubnetGroupName

The new DB subnet group for the DB instance.

Type: String

Required: No

EngineVersion

Indicates the database engine version.

Type: String

Required: No

IOPS

Specifies the new Provisioned IOPS value for the DB instance that will be applied or is being applied.

Type: Integer

Required: No

LicenseModel

The license model for the DB instance.

Valid values: `license-included` | `bring-your-own-license` | `general-public-license`

Type: String

Required: No

MasterUserPassword

Contains the pending or in-progress change of the master credentials for the DB instance.

Type: String

Required: No

MultiAZ

Indicates that the Single-AZ DB instance is to change to a Multi-AZ deployment.

Type: Boolean

Required: No

Port

Specifies the pending port for the DB instance.

Type: Integer

Required: No

StorageType

Specifies the storage type to be associated with the DB instance.

Type: String

Required: No

RecurringCharge

This data type is used as a response element in the [DescribeReservedDBInstances \(p. 177\)](#) and [DescribeReservedDBInstancesOfferings \(p. 180\)](#) actions.

Contents

RecurringChargeAmount

The amount of the recurring charge.

Type: Double

Required: No

RecurringChargeFrequency

The frequency of the recurring charge.

Type: String

Required: No

ReservedDBInstance

This data type is used as a response element in the [DescribeReservedDBInstances](#) (p. 177) and [PurchaseReservedDBInstancesOffering](#) (p. 236) actions.

Contents

CurrencyCode

The currency code for the reserved DB instance.

Type: String

Required: No

DBInstanceClass

The DB instance class for the reserved DB instance.

Type: String

Required: No

DBInstanceCount

The number of reserved DB instances.

Type: Integer

Required: No

Duration

The duration of the reservation in seconds.

Type: Integer

Required: No

FixedPrice

The fixed price charged for this reserved DB instance.

Type: Double

Required: No

MultiAZ

Indicates if the reservation applies to Multi-AZ deployments.

Type: Boolean

Required: No

OfferingType

The offering type of this reserved DB instance.

Type: String

Required: No

ProductDescription

The description of the reserved DB instance.

Type: String

Required: No

RecurringCharges.RecurringCharge.N

The recurring price charged to run this reserved DB instance.

Type: array of [RecurringCharge](#) (p. 347) objects

Required: No

ReservedDBInstanceArn

The Amazon Resource Name (ARN) for the reserved DB instance.

Type: String

Required: No

ReservedDBInstanceid

The unique identifier for the reservation.

Type: String

Required: No

ReservedDBInstancesOfferingId

The offering identifier.

Type: String

Required: No

StartTime

The time the reservation started.

Type: Timestamp

Required: No

State

The state of the reserved DB instance.

Type: String

Required: No

UsagePrice

The hourly price charged for this reserved DB instance.

Type: Double

Required: No

ReservedDBInstancesOffering

This data type is used as a response element in the [DescribeReservedDBInstancesOfferings](#) (p. 180) action.

Contents

CurrencyCode

The currency code for the reserved DB instance offering.

Type: String

Required: No

DBInstanceClass

The DB instance class for the reserved DB instance.

Type: String

Required: No

Duration

The duration of the offering in seconds.

Type: Integer

Required: No

FixedPrice

The fixed price charged for this offering.

Type: Double

Required: No

MultiAZ

Indicates if the offering applies to Multi-AZ deployments.

Type: Boolean

Required: No

OfferingType

The offering type.

Type: String

Required: No

ProductDescription

The database engine used by the offering.

Type: String

Required: No

RecurringCharges.RecurringCharge.N

The recurring price charged to run this reserved DB instance.

Type: array of [RecurringCharge](#) (p. 347) objects

Required: No

ReservedDBInstancesOfferingId

The offering identifier.

Type: String

Required: No

UsagePrice

The hourly price charged for this offering.

Type: Double

Required: No

ResourcePendingMaintenanceActions

Describes the pending maintenance actions for a resource.

Contents

PendingMaintenanceActionDetails.PendingMaintenanceAction.N

A list that provides details about the pending maintenance actions for the resource.

Type: array of [PendingMaintenanceAction \(p. 344\)](#) objects

Required: No

ResourceIdentifier

The ARN of the resource that has pending maintenance actions.

Type: String

Required: No

SourceRegion

Contains an AWS Region name as the result of a successful call to the [DescribeSourceRegions](#) (p. 183) action.

Contents

Endpoint

The source region endpoint.

Type: String

Required: No

RegionName

The source region name.

Type: String

Required: No

Status

The status of the source region.

Type: String

Required: No

Subnet

This data type is used as a response element in the [DescribeDBSubnetGroups \(p. 145\)](#) action.

Contents

SubnetAvailabilityZone

Contains Availability Zone information.

This data type is used as an element in the following data type:

- [OrderableDBInstanceOption \(p. 340\)](#)

Type: [AvailabilityZone \(p. 288\)](#) object

Required: No

SubnetIdentifier

Specifies the identifier of the subnet.

Type: String

Required: No

SubnetStatus

Specifies the status of the subnet.

Type: String

Required: No

Tag

Metadata assigned to an Amazon RDS resource consisting of a key-value pair.

Contents

Key

A key is the required name of the tag. The string value can be from 1 to 128 Unicode characters in length and cannot be prefixed with "aws:" or "rds:". The string can only contain only the set of Unicode letters, digits, white-space, '_', '.', '/', '=', '+', '-' (Java regex: "`^\p{L}\p{Z}\p{N}_./=+\-]*$`").

Type: String

Required: No

Value

A value is the optional value of the tag. The string value can be from 1 to 256 Unicode characters in length and cannot be prefixed with "aws:" or "rds:". The string can only contain only the set of Unicode letters, digits, white-space, '_', '.', '/', '=', '+', '-' (Java regex: "`^\p{L}\p{Z}\p{N}_./=+\-]*$`").

Type: String

Required: No

Timezone

A time zone associated with a [DBInstance](#) (p. 304) or a [DBSnapshot](#) (p. 314). This data type is an element in the response to the [DescribeDBInstances](#) (p. 124), the [DescribeDBSnapshots](#) (p. 141), and the [DescribeDBEngineVersions](#) (p. 121) actions.

Contents

TimezoneName

The name of the time zone.

Type: String

Required: No

UpgradeTarget

The version of the database engine that a DB instance can be upgraded to.

Contents

AutoUpgrade

A value that indicates whether the target version will be applied to any source DB instances that have AutoMinorVersionUpgrade set to true.

Type: Boolean

Required: No

Description

The version of the database engine that a DB instance can be upgraded to.

Type: String

Required: No

Engine

The name of the upgrade target database engine.

Type: String

Required: No

EngineVersion

The version number of the upgrade target database engine.

Type: String

Required: No

IsMajorVersionUpgrade

A value that indicates whether a database engine will be upgraded to a major version.

Type: Boolean

Required: No

VpcSecurityGroupMembership

This data type is used as a response element for queries on VPC security group membership.

Contents

Status

The status of the VPC security group.

Type: String

Required: No

VpcSecurityGroupld

The name of the VPC security group.

Type: String

Required: No

Common Parameters

The following table lists the parameters that all actions use for signing Signature Version 4 requests. Any action-specific parameters are listed in the topic for that action. To view sample requests, see [Examples of Signed Signature Version 4 Requests](#) or [Signature Version 4 Test Suite](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service. For a list of services that support AWS Security Token Service, go to [Using Temporary Security Credentials to Access AWS](#) in *Using Temporary Security Credentials*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the common errors that all actions return. Any action-specific errors are listed in the topic for the action.

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

Throttling

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400